


## 3.2-3.8kW Single-Phase Switched PDU, 200-240V (20-C13 & 4-C19), C20/L6-20P Cable, 0U Vertical, 70 in., TAA

MODEL NUMBER: **PDUMV20HVNET**



### Description

Tripp Lite single phase Switched PDU / Power Distribution Unit offers advanced network control and monitoring with the ability to turn on, turn off, recycle or lock-out power to each individual receptacle, monitor site electrical conditions and remotely monitor output power consumption. PowerAlert interface supports remote control and custom notification of user-specified conditions via email, secure web, SNMP, Telnet or SSH interface. Individually switched outlets can be controlled in real-time to remotely reboot unresponsive network hardware, or be custom programmed for user-defined power-up and power-down sequences to ensure proper startup of interdependent IT systems and prevent inrush-related overloads as network equipment is first energized. Unused PDU outlets can be electronically locked off to prevent the connection of unauthorized hardware. PDU output current consumption in amps is continuously displayed locally via visual meter and remotely via web/network interface to warn of potential overloads before critical IT mains or branch breakers trip.

### Features

- 16/20A 200/208/230/240V Switched PDU with built-in web/network interface in 0U 70 inch / 178cm vertical rackmount form factor (Agency derated to 16 amps)
- C20 inlet accepts a variety of site specific cordsets; 10 ft. / 3m L6-20P power cable included
- 24 switched outlets (20 C13; 4 C19)
- Supports power-on, power-off or reboot of each outlet on a real-time or programmable basis
- Enables reboot of locked equipment, custom power-on/power-off sequences, load-shedding of optional loads and disabling unused outlets
- Network interface provides PDU control and data regarding input voltage, frequency and loading information
- Digital display reports load level information in amps

### Highlights

- Switched 16/20A 200-240V PDU, 0U 70 in / 178cm Vertical Rackmount format
- Reports voltage, frequency & loading information via ethernet interface
- Visual current meter; Toolless button mount installation
- C20 inlet; 10ft / 3m L6-20P input cable
- 24 switched outlets (20 C13; 4 C19) with cord retention brackets
- Temperature, humidity and contact-closure monitoring options
- TAA Compliant

### Package Includes

- Rackmount PDU
- L6-20P to C19 detachable input cord
- Rackmount brackets
- PDUMVROTATEBRKT mounting accessory



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

- Supports user-specified alarm notification thresholds
- In-rack environmental reporting with optional ENVIROSENSE temperature / humidity sensor and rack access notification with up to 4 optional SRSWITCH door sensors
- DHCP/Manual configuration support
- 10/100 Mbps auto-sensing
- Real-time clock backup maintains the time of day and date even if the PDU is not powered on
- Tiered access privileges allow an administrator and a guest to login via web browser
- Alert notifications via email or SNMP traps offer immediate event notification
- Firmware upgrade ability supports future product enhancements
- Supports HTTP, HTTPS, PowerAlert Network Management System, SMTP, SNMPv1, SNMPv2, SNMPv3, Telnet, SSH, FTP, DHCP, BOOTP, NTP protocols
- Fully compatible with FREE PowerAlert Network Management System / NMS Software
- Included cord retention brackets keep vital network equipment plugged in and continuously powered
- Toolless mounting supported in button-mount compatible racks, plus nut-and-bolt mounting brackets for other mounting applications
- Federal Trade Agreements Act / TAA Compliant for GSA Schedule purchases

## Specifications

| OVERVIEW                               |  |
|--|--|
| UPC Code                               | 037332139733   |
| PDU Type                               | Switched   |
| OUTPUT                                 |  |
| Frequency Compatibility                | 50 / 60 Hz   |
| Output Capacity Details                | 3.84kW (240V), 3.68kW (230V), 3.52kW (220V), 3.33kW (208V), 3.2kW (200V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet |
| Output Receptacles                     | (20) C13; (4) C19  |
| Output Nominal Voltage                 | 200; 208; 220; 230; 240  |
| Overload Protection                    | n/a  |
| Customized Load Management Receptacles | Each outlet is individually controllable via remote interface  |
| INPUT                                  |  |
| PDU Input Voltage                      | 200; 208; 220; 230; 240  |
| Recommended Electrical Service         | 20A 208/240V; 16A 230V   |
| Maximum Input Amps                     | 20   |
| Maximum Input Amps Details             | Agency de-rated to 16A continuous  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|  |   |
|--|---|
| Input Connection Type                        | C20 inlet accepts included L6-20P input cable   |
| PDU Plug Type                                | NEMA L6-20P; IEC-320 C20  |
| Input Phase                                  | Single-Phase  |
| Input Cord Length (ft.)                      | 10  |
| Input Cord Length (m)                        | 3.05  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Front Panel LCD Display                      | Digital meter reports PDU output current in amps  |
| Front Panel LEDs                             | 24 power availability LEDs confirm power off/on status for each built-in outlet   |
| <b>PHYSICAL</b>                              |   |
| Form Factors Supported                       | 0U vertical rackmount; includes rackmount brackets. Supports toolless mounting in button-mount compatible racks   |
| PDU Form Factor                              | Vertical (0U)   |
| Shipping Dimensions (hwd / cm)               | 13.46 x 16.26 x 185.42  |
| Shipping Dimensions (hwd / in.)              | 5.30 x 6.40 x 73.00   |
| Shipping Weight (kg)                         | 6.44  |
| Shipping Weight (lbs.)                       | 14.20   |
| Unit Dimensions (hwd / cm)                   | 177.8 x 5.6 x 6.7   |
| Unit Dimensions (hwd / in.)                  | 70 x 2.19 x 2.65  |
| Unit Weight (kg)                             | 3.86  |
| Unit Weight (lbs.)                           | 8.50  |
| <b>ENVIRONMENTAL</b>                         |   |
| Relative Humidity                            | 0-95% non-condensing  |
| <b>COMMUNICATIONS</b>                        |   |
| SNMP Compatibility                           | Pre-installed &nbsp;<a class="productLink" href="//www.tripplite.com/SNMP-Web-Management-Accessory-Card-SmartPro-SmartOnline-UPS-Systems~SNMPWEBCARD">SNMPWEBCARD</a>&nbsp; provides remote monitoring via web, Telnet, and SNMP management systems. Remote management enables outlets to be turned on and off individually |
| <b>CERTIFICATIONS</b>                        |   |
| Certifications                               | Tested to UL 60950-1 (USA, Canada), CE (Int'l), Class A (Emissions), NOM (Mexico), RoHS compliant, TAA Compliant  |
| <b>WARRANTY</b>                              |   |
| Product Warranty Period (Worldwide)          | 2-year limited warranty   |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>