Thermofit Molded Parts Specification Control Drawing

Limited Distribution


NOTES


- 1. All dimensions are in $\frac{\text{monoc}}{\text{[millimeters]}}$
- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
- Parts shall have color stripe .12 wide x 360' around outside surface approx. as shown and must meet requirements set forth in MS3109. colors shall be as follows:

Color White Red Yellow

Dash No. -3 -4 -12

5. Parts to have only one lip because of core change.





202D1XX-X-60

Boot, Straight, With Lip

TABLE OF DIMENSIONS											
PART NUMBER	н		J			Р	R	s	Т	JO	w
	Min	Max	Min	Min	Max	±10%	Ref	Ref	Ref	±10%	±20%
	a	ь	-3,-4 a	-12 a	ь	ь	ь	ь	ь	ь	ь
202D121-X-60	.92	<u>.41</u>	<u>.92</u>	.49	.22	1.50	.83	.12	.04	.40	<u>.07</u>
	[23,3]	[10,5]	[23,3]	[12,4]	[5,6]	[38,1]	[21,1]	[3,0]	[1,0]	[10,2]	[1,78]
202D132-X-60	1.12	.56	1.12	.58	.26	2.16	1.09	. <u>12</u>	.04	<u>.65</u>	<u>.07</u>
	[28,4]	[14,3]	[28,4]	[14,7]	[6,6]	[54,9]	[27,7]	[3,0]	[1,0]	[16,5]	[1,78]
202D142-X-60	1.22	.70	1.22	.63	.28	2.63	1.39	. <u>12</u>	. <u>04</u>	<u>.70</u>	<u>.08</u>
	[31,0]	[17,8]	[31,0]	[16,0]	[7,2]	[66,8]	[35,3]	[3,0]	[1,0]	[17,8]	[2,03]
202D153-X-60	1.42	.88	1.42	<u>.73</u>	. <u>33</u>	3.15	1.63	. <u>12</u>	<u>.04</u>	.82	<u>.08</u>
	[36,0]	[22,4]	[36,0]	[18,5]	[8,4]	[80,0]	[41,4]	[3,0]	[1,0]	[20,8]	[2,03]
202D163-X-60	1.68	1.11	1.68	.87	.39	4.08	2.22	.12	. <u>065</u>	.97	<u>.09</u>
	[42,7]	[28,2]	[42,7]	[22,0]	[9,9]	[103,6]	[56,4]	[3,0]	[1,65]	[24,6]	[2,29]
202D174-X-60	2.04	1.38	2.04	1.39	.62	5.13	2.54	.12	. <u>065</u>	1.56	.13
	[51,8]	[35,1]	[51,8]	[35,3]	[15,8]	[130,3]	[64,5]	[3,0]	[1,65]	[39,6]	[3,3]
202D185-X-60	2.60	1.75	2.60	1.80	.80	6.50	3.31	.12	. <u>08</u>	1.90	<u>.16</u>
	[66,0]	[44,5]	[66,0]	[45,7]	[20,4]	[165,1]	[84,1]	[3,0]	[2,0]	[48,3]	[4,06]
202D196-X-60	3.22	2.27	3.22	2.25	1.00	<u>7.00</u>	3.75	<u>.12</u>	. <u>08</u>	1.88	<u>.16</u>
	[81,7]	[57,6]	[81,7]	[57,1]	[25,4]	[177,8]	[95,3]	[3,0]	[2,0]	[47,8]	[4,06]

E*TE _{Reychem}*

Revision: B1

Date: 20APR11

Part Number :

Part Number :

Description :

202D1XX-X-60

Description: Boot, Straight, With Lip

Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number : 202D1XX-X-60

Description: Boot, Straight, With Lip

COMPATABILITY CHART										
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION					
-3	Polyolefin, Semi-rigid	RT-301	/42	S-1017	Adhesive					
-4	Polyolefin, Flexible	RT-1304	/42	S-1017	Adhesive					
-12	*VITON, Flexible	RT-1312	N/A							

*VITON is a Registered Trademark of Dupont

ORDERING INFORMATION 202D1XX -60 /42-XBase part number Material dash number (See Compatability Chart) Modification number (If necessary, see front of scd binder for a complete list) Adhesive slash number (If necessary, see Compatability Chart)

IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED. CHECK FOR THE LATEST REVISION.

THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

ETE Reychem

TE CONNECTIVITY
300 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025

Revision: B1 Date: 20APR11 Part Number :

202D1XX-X-60

Description: Boot, Straight, With Lip

CAD FILE MP94154

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 202D132-4-60/42-0