



FEATURES:

- Converts Double Banana Jack Test Instruments to Binding Posts for test versatility.
- Banana Plugs can be stacked vertically or horizontally.
- Wires, spade lugs and pin tip plugs can be attached by means of the insulated knurl thumb knob.
- Insulated knurl thumb knob is captive to prevent misplacement.
- Banana Plugs feature Nickel/Gold Plated, Beryllium Copper for tarnish resistance & long insertion life.

MATERIALS:

Binding Post: Body – Brass, Nickel Plated (Model 1286), Brass, Gold Plated (Model 5405)

Insulator Knurl Thumb Knob: Polycarbonate, Color: Black, Red

Insulator: ABS, Molded to the binding Post and Banana Body

Marking: “1286 POMONA ELECTRONICS” or “5405 POMONA ELECTRONICS”

Banana Plug: Body: Brass, Nickel Plated (Model 1286), Brass, Gold Plated (Model 5405)

Spring: Beryllium Copper, Nickel Plated (Model 1286)

Beryllium Copper, Gold Plated (Model 5405)

RATINGS:

Operating Voltage: 2500 VDC

Operating Temperature: +50°C (+122°F).

Current: 15 Amperes Max.

ORDERING INFORMATION: Model 1286 & 5405

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (.51 mm), .xxx = ±.005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

5405 1286