

# Flush-type connector - SACC-CI-M12FS-17CON-L90 - 1424197

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/actuator flush-type socket, 17-pos. without shroud, A-coded, with angled solder connection, contact insert only

## Your advantages

- ✓ Reduced mounting costs thanks to two-piece device connector
- ✓ All common pin assignments and codings available
- ✓ Easy device integration thanks to mechanical port screw connections with threaded attachment, press-in contour or direct integration in the front plate



## Key Commercial Data

|                        |               |
|------------------------|---------------|
| Packing unit           | 20 pc         |
| Minimum order quantity | 20 pc         |
| GTIN                   |               |
| GTIN                   | 4046356692915 |

## Technical data

### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket)                |
|                                 | -40 °C ... 85 °C (without mechanical actuation) |
| Degree of protection            | IP67  |

### General

|                       |  |
|-----------------------|--|
| Note                  | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration. |
| Rated current at 40°C | 1.5 A  |
| Rated voltage         | 30 V   |
| Rated surge voltage   | 0.8 kV   |
| Number of positions   | 17   |

# Flush-type connector - SACC-CI-M12FS-17CON-L90 - 1424197

## Technical data

### General

|                             |                                   |
|-----------------------------|-----------------------------------|
| Insulation resistance       | ≥ 100 MΩ                          |
| Coding                      | A - standard                      |
| Standards/regulations       | M12 connector IEC 61076-2-101     |
| Status display              | No                                |
| Overvoltage category        | III                               |
| Degree of pollution         | 3                                 |
| Connection method           | Solder pins                       |
| Insertion/withdrawal cycles | > 100                             |
| Torque                      | 3 Nm ... 4 Nm (Installation-side) |
| Mounting type               | PCB mounting                      |

### Material

|  |      |
|--|------|
| Flammability rating according to UL 94 | V0   |
| Contact material                       | CuZn |
| Contact surface material               | Au   |
| Contact carrier material               | PA6T |

### Cable

|                                    |   |
|------------------------------------|---|
| Conductor cross section            | 0.14 mm <sup>2</sup>                            |
| Conductor structure signal line    | 7x 0.16 mm                                      |
| Core diameter including insulation | 1.1 mm ±0.05 mm                                 |
| Thickness, insulation              | 0.21 mm   |
| Standards/specifications           | M12 connector IEC 61076-2-101                   |
| Insulation resistance              | ≥ 20 MΩ*km                                      |
| Conductor resistance               | ≤ 57.6 mΩ/m                                     |
| Nominal voltage, cable             | 300 V   |
| Test voltage, cable                | 2000 V AC                                       |
| Ambient temperature (operation)    | -40 °C ... 85 °C (cable, fixed installation)    |
|                                    | -25 °C ... 85 °C (cable, flexible installation) |

### Standards and Regulations

|  |                 |
|--|-----------------|
| Standard designation                   | M12 connector   |
| Standards/regulations                  | IEC 61076-2-101 |
| Flammability rating according to UL 94 | V0              |


### Environmental Product Compliance

|            |   |
|------------|---|
|            | Lead 7439-92-1  |
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings


# Flush-type connector - SACC-CI-M12FS-17CON-L90 - 1424197

Schematic diagram




Pin assignment M12, 12-pos., female side view

Dimensional drawing



M12 socket, angled

Dimensional drawing



M12 socket, angled

## Approvals

### Approvals

### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized


### Ex Approvals

## Approval details


|                            |       |   |               |
|----------------------------|-------|---|---------------|
| UL Recognized              |       | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 118976 |
| Nominal voltage UN         | 30 V  |   |               |
| Nominal current IN         | 1.5 A |   |               |
| mm <sup>2</sup> /AWG/kcmil | 26    |   |               |


# Flush-type connector - SACC-CI-M12FS-17CON-L90 - 1424197

## Approvals

|                |   |   |               |
|----------------|---|---|---------------|
| cUL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 118976 |
|----------------|---|---|---------------|

|                            |       |
|----------------------------|-------|
| Nominal voltage UN         | 30 V  |
| Nominal current IN         | 1.5 A |
| mm <sup>2</sup> /AWG/kcmil | 26    |

|     |   |         |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

|                  |   |
|------------------|---|
| cULus Recognized |  |
|------------------|---|

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>