

Note: This datasheet may be out of date.

Please download the latest datasheet of PTGL12AR150M6B72B0 from the official website of Murata

Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=PTGL12AR150M6B72B0

PTGL12AR150M6B72B0










Appearance & Shape







Features

- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise.

 Durable and strong against mechanical vibration and shock because it is a solid element.



Limited Usage	Consumer Grade
Other Usage	Transformers Transistors Fluorescent Lamps



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	250

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/09/20

0.6mm

Lead

1.46g

d: Lead Diameter

Shape

Mass

Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=PTGL12AR150M6B72B0

PTGL12AR150M6B72B0



Max. Voltage	125V
Hold Current	175mA
Measure Condition of Hold Current	(at +60°C)
Hold Current (2)	220mA
Measure Condition of Hold Current (2)	(at +25°C)
Trip Current	380mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	440mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	1A
Resistance (25°C)	15Ω
Resistance Value Tolerance (at 25°C)	±20%
Power Consumption(typ)	2W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	12.5mm
Thickness	5.5mm
F: Lead Space	7.5mm

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





URL: https://www.murata.com/

Last updated :2019/09/20


PTGL12AR150M6B72B0







Resistance-Temperature Charac.



Protective Threshold Current Range

Operating Time (Typical Curve)

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

PTGL12AR150M6B72B0