



Laser/Ink Jet Labels

Laser/Inkjet Labels

Panduit is a global leader in reliable and innovative solutions for identification and safety. Products are engineered for a wide variety of industrial applications – including electrical, electronics, industrial, and network. Panduit offers a complete leading-edge line of labeling software and high-performance label materials (all RoHS compliant) that provide enhanced productivity, dependability, and value to all infrastructure labeling requirements. Laser/Inkjet Labels are on 8.5" x 11" sheets.

*Representative offering only,
visit www.panduit.com for a
complete listing of products.*



Cable/Wire Labels

Turn-Tell® Labels.....	4
Self-Laminating Polyester Labels.....	5
Self-Laminating Tedlar® Labels	6
Self-Laminating Polyolefin Labels	6
LabelCore™ Fiber Optic Cable Identification System	7
Non-Laminated Polyolefin Labels	7

Component Labels

Polyester Component Labels	8
Silver Polyester Component Labels	9
Tamper-Evident Polyester Component Labels.....	9
Tedlar® Component Labels.....	9
Non-Adhesive Polyester Network Labels.....	10
Polyolefin Network Labels	10

Safety Labels

Polyester Safety Labels.....	11
Rigid Signs for use with Polyester Safety Labels	11
Rigid Safety Tags.....	12
Polyester Adhesive Safety Signs.....	12


Labeling Software

Easy-Mark Plus™ Software.....	13
CAD-Connect™ Software.....	13

Tedlar is a registered trademark of E. I. du Pont de Nemours and Company.

Turn-Tell® Labels

PATENTED



- Labels rotate and slide along cables after installation for visibility from any angle, and allow repositioning on the wire/cable to align legends for improved aesthetics
- Ideal for use in high-density or space-constrained cable applications
- Eliminate the need to disconnect wire or replace label in the event of re-termination
- Temperature range: -65°F to 225°F (-54°C to 107°C)



	Print-On	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire/Cable Size Range	Labels Per Row	Labels Per Sheet	Labels Per Pkg.		
Part Number	Area Color	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm						
R050X075X1J	White	0.50	12.7	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.1	Cat. 6 28 AWG / 18 – 14 AWG	12	84	5000		
R050X125X1J				1.25	31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP / 12 – 10 AWG		60			
R050X150X1J				1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP / Cat. 6UTP / Cat. 6A UTP / Cat. 5e FTP / 10 – 6 AWG		48	2500		
R100X075X1J		1.00	25.4	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.1	Cat. 6 28 AWG / 18 – 14 AWG	42	1000			
R100X125X1J				1.25	31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP / 12 – 10 AWG	30				
R100X150X1J				1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP / Cat. 6 UTP / Cat. 6A UTP / Cat. 5e FTP / 10 – 6 AWG	24	6			
R100X150X2J	TIA Blue			2.00	50.8	2.25	57.2	0.75	19.1	0.28	7.1	0.39	9.9		Cat. 6 FTP / Cat. 6A UTP / Cat. 6A FTP / 8 – 4 AWG	18	12
R100X150X3J	TIA Green																
R100X150X7J	TIA Red																
R100X225X1J	White																
R100X225X2J	TIA Blue																
R100X225X3J	TIA Green																
R100X225X7J	TIA Red	1.50	38.1	1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/ Cat. 6 UTP/ Cat. 6A UTP/ Cat. 5e FTP / 10 – 6 AWG	4	16	500		
R100X225X8J	TIA Yellow													12			
R100X400X1J	White													2.00	50.8	2.25	57.2
R150X150X1J		4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG	6						
R200X150X1J					4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG				
R200X225X1J				4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG					
R200X400X1J				4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG					

Order number of labels required in multiples of Standard Package Quantity.

Self-Laminating Polyester Labels



- Include a colored print-on area and clear over-laminate to protect the legend for clear and durable identification
- Labels are sized specifically for wire and cable applications
- Provide durability; high-temperature resistance, and dimensional stability; do not stretch or easily tear; preferred material for wire/cable labeling
- White labels are ASTM E-595 rated for airspace handling
- Temperature Range: -65°F to 225°F (-54°C to 107°C)
- For YAJ parts only: UL recognized, UL969, File # MH14979

	Print-On	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire/Cable Size Range	Labels Per Row	Labels Per Sheet	Labels Per Pkg.	
Part Number	Area Color	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm					
S050X075YAJ	White	0.50	12.7	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	18 – 14 AWG	13	169	5000	
S050X125YAJ				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/12 – 10 AWG		104		
S050X150YAJ				1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG		78		
S075X075YAJ		0.75	19.1	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	18 – 14 AWG	9	117		
S075X125YAJ				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/12 – 10 AWG		72		
S075X150YAJ				1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG		54		
S100X075YAJ		TIA Blue TIA Brown TIA Green TIA Gray TIA Orange TIA Purple TIA Red TIA Yellow			0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	18 – 14 AWG	7	91	2500
S100X125YAJ					1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/12 – 10 AWG		56	
S100X150YAJ																
S100X150YBJ																
S100X150YCJ																
S100X150YDJ																
S100X150YEJ					1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG		42	
S100X150YFJ																
S100X150YGJ																
S100X150YHJ																
S100X150YIJ																
S100X225YAJ	White	1.00	25.4									Cat. 6 FTP/Cat. 6A UPT/Cat. 6A FTP/8 – 4 AWG	8	32	1000	
S100X225YBJ	TIA Blue															
S100X225YCJ	TIA Brown															
S100X225YDJ	TIA Green															
S100X225YEJ	TIA Gray			2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1					
S100X225YFJ	TIA Orange															
S100X225YGJ	TIA Purple															
S100X225YHJ	TIA Red															
S100X225YIJ	TIA Yellow															
S100X400YAJ	White	1.00	25.4	4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG	7	14	1000	
S100X650YAJ	White			6.50	165.1	1.50	38.1	0.48	12.1	1.59	40.4	1/0 – 350 MCM		7		
S150X400YAJ	White	1.50	38.1	4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG	5	14		
S150X400YIJ	TIA Yellow													14		
S200X150YAJ	White	2.00	50.8	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	4	24	500	
S200X225YAJ	White			2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UPT/Cat. 6A FTP/8 – 4 AWG		16		
S200X400YAJ	White			4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG		8		
S200X650YAJ	White			6.50	165.1	1.50	38.1	0.48	12.1	1.59	40.4	1/0 – 350 MCM		4		

Order number of labels required in multiples of Standard Package Quantity.

Self-Laminating Tedlar® Labels



- Include a colored print-on area and clear over-laminate to protect the legend for clear and durable identification
- Labels are sized specifically for wire and cable applications
- Labels are self-extinguishing
- Temperature range: 0°F to 275°F (-18°C to 135°C)
- UL Recognized: UL969, File # MH 14576, CUL Recognized: C22.2 No 0.15-01, File # MH 14576

Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire/Cable Size Range	Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
S100X150TAJ-A	White	1.00	25.4	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/ Cat. 6 UTP/ Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG	7	42	2500
S100X225TAJ-A				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/ 8 – 4 AWG		28	1000

Tedlar® is a registered trademark of E. I du Pont de Nemours and Company.

Self-Laminating Polyolefin Labels



- Include a colored print-on area and clear over-laminate to protect the legend for clear and durable identification
- Labels are sized specifically for wire and cable applications
- Labels are Halogen-free
- Temperature range: -40°F to 176°F (-40°C to 80°C)
- UL Recognized: UL969, File # MH 14979

Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire/Cable Size Range	Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				

Laser Only


S100X125FAL	White	1.00	25.4	1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 – 10 AWG	8	56	2500
S100X150FAL				1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/ Cat. 6 UTP/ Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG		48	
S100X160FAL				1.60	40.6	0.80	20.3	0.25	6.4	0.25	6.4	Cat. 5e UTP/ Cat. 6 UTP/ Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG		48	
S100X220FAL				2.20	55.9	1.10	27.9	0.35	8.9	0.35	8.9	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/ 8 – 4 AWG	4	32	1000
S100X225FAL				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/ 8 – 4 AWG		16	
S100X400FAL				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG		8	
S200X225FAL		2.00	50.8	2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/ 8 – 4 AWG	4	8	500
S200X400FAL				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG			

Inkjet Only

S100X125FAI	White	1.00	25.4	1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 – 10 AWG	8	56	2500
S100X150FAI				1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/ Cat. 6 UTP/ Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG		48	
S100X160FAI				1.60	40.6	0.80	20.3	0.25	6.4	0.25	6.4	Cat. 5e UTP/ Cat. 6 UTP/ Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG		48	
S100X220FAI				2.20	55.9	1.10	27.9	0.35	8.9	0.35	8.9	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/ 8 – 4 AWG	4	32	1000
S100X225FAI				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/ 8 – 4 AWG		16	
S100X400FAI				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG		8	
S200X225FAI		2.00	50.8	2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/ 8 – 4 AWG	4	8	500
S200X400FAI				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG			

LabelCore™ Fiber Optic Cable Identification System

PATENTED




- Provides a larger labeling surface on small fiber cables and allows legends to be clearly seen
- Sleeve is made of flexible PVC material
- Locate sleeve on straight section of cable at least 2 inches from fiber boot

Part Number	Color	Part Description	Std. Pkg. Qty.
NWSLC-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex fiber cable, 1 inch long, 100 per pack, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VATY (Thermal Transfer Printer).	100
NWSLC-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 1 inch long, 100 per pack, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 1 inch long, 100 per pack, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 1 inch long, 100 per pack, use with labels: S100X225YAJ (Laser/Inkjet); S100X225VAC (LS8E Hand-held Printer); S100X225VATY or S200X225VATY (Thermal Transfer Printer).	
NWSLC2-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex cable, 2 inches long, 100 per pack, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 2 inches long, 100 per pack, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 2 inches long, 100 per pack, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 2 inches long, 100 per pack, use with labels: S200X225YAJ (Laser/Inkjet) S200X225VATY (Thermal Transfer Printer).	

Order number of sleeves by Standard Package Quantity.

Non-Laminated Polyolefin Labels



- Use as wrap-around label or flag-style marker for wire/cable labeling
- Temperature range: -40°F to 180°F (-40°C to 82°C)
- Conformable material for general identification

Part Number	Color	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Wire/Cable Size Range	Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm	In.	mm	In.	mm				
N025X075FJJ	White	0.25	6.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	25	275	10000
N025X125FJJ				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		175	
N025X150FJJ				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG	67	150	
N050X075FJJ		0.50	12.7	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	14	154	5000
N050X125FJJ				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		98	
N050X150FJJ				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		84	
N100X075FJJ		1.00	25.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	7	77	2500
N100X125FJJ				1.25	31.8	0.20	4.1	0.32	8.1	10 – 6 AWG		49	
N100X150FJJ				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		42	

Order number of labels required in multiples of Standard Package Quantity.

Polyester Component Labels



- Used to identify patch panels, faceplates, punch-down blocks, and other network systems hardware
- Used to identify electrical and electronic components and devices
- Temperature range: -40°F to 311°F (-40°C to 154°C)
- UL recognized, UL969, File# MH14979
- cUL recognized, C22.2 No. 0.15-01, File# MH14979

Part Number	Color	Width		Height		Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm			
C038X038YJJ	White	0.38	9.7	0.38	9.7	16	352	10000
C038X038YLJ	Yellow							
C050X044YJJ	White	0.50	12.7	0.44	11.2	13	247	
C060X020YJJ		0.60	15.2	0.20	5.1	11	385	
C075X025YJJ		0.75	19.1	0.25	6.4	9	270	
C075X025YLJ	0.75			19.1	0.25		6.4	
C075X050YJJ	White	0.80	20.3	0.20	5.1	8	280	
C080X020YJJ				0.25	6.4	7	210	
C100X025YJJ		1.00	25.4	0.38	9.7		140	5000
C100X038YJJ				0.50	12.7		119	10000
C100X050YJJ				0.75	19.1	84	5000	
C100X050YLJ	Yellow	1.50	38.1	1.50	38.1	5	42	2500
C100X075YJJ	White			0.50	12.7		80	
C150X050YJJ				0.75	19.1		60	
C150X050YLJ	Yellow	1.60	40.6	0.20	5.1	4	140	5000
C150X075YJJ	White			0.50	12.7		64	
C160X020YJJ		2.00	50.8	1.00	25.4	6	28	1000
C200X050YJJ	1.25			31.8	18			
C200X100YJJ	White	2.75	69.9	0.38	9.7	2	40	
C200X100YLJ				1.00	25.4		18	
C200X125YJJ				2.00	50.8		8	
C275X125YJJ		3.50	88.9	1.00	25.4	1	20	1000
C300X038YJJ				2.00	50.8		10	
C300X100YJJ	4.00	101.6	4.00	101.6	4			
C300X200YJJ			0.50	12.7	16		400	
C350X100YJJ	7.88	200.2	11.00	279.4	1	1	25	
C400X100YJJ								
C400X200YJJ	Yellow	8.50	215.9					
C400X400YJJ								
C788X050YJJ								
C850X1100YJJ								
C850X1100YLJ								

Order number of labels required in multiples of Standard Package Quantity.

Silver Polyester Component Labels – FOR LASER PRINTERS ONLY

- Used to identify patch panels, faceplates, punch-down blocks, and other network systems hardware
- Used to identify electrical and electronic components and devices
- Temperature range: -65°F to 275°F (-54°C to 135°C)
- UL recognized, UL969, File# MH14979
- cUL recognized, C22.2 No. 0.15-01, File# MH14979

Part Number	Color	Width		Height		Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm			
C075X025YML	Silver	0.75	19.1	0.25	6.4	9	270	10000
C100X050YML		1.00	25.4	0.50	12.7	7	119	
C150X050YML		1.50	38.1	0.50	12.7	5	85	
C200X100YML		2.00	50.8	1.00	25.4	4	28	1000
C275X125YML		2.75	69.9	1.25	31.8	6	18	
C850X1100YML		8.50	215.9	11.00	279.4	1	1	

Order number of labels required in multiples of Standard Package Quantity.

Tamper-Evident Polyester Component Labels – FOR LASER PRINTERS ONLY



- Allow you to see if there has been label tampering
- Leave checkerboard of silver material when label is removed
- Temperature range: -40°F to 302°F (-40°C to 150°C)

Part Number	Color	Width		Height		Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm			
C075X025AAL	Silver	0.75	19.1	0.25	6.4	9	270	10000
C100X050AAL		1.00	25.4	0.50	12.7	7	119	
C200X100AAL		2.00	50.8	1.00	25.4	6	28	1000
C275X125AAL		2.75	69.9	1.25	31.8	6	18	

Order number of labels required in multiples of Standard Package Quantity.

Tedlar® Component Labels



- Self-extinguishing and ideal for labeling high-temperature areas
- Temperature range: -40°F to 275°F (-40°C to 135°C)
- UL969 recognized, File # MH 14576, CUL recognized, C22.2 No 0.15-01, File # MH 14676

Part Number	Color	Width		Height		Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm			
C050X125TJJ	White	0.5	12.7	1.25	31.8	5	80	1000
C090X025TJJ		0.9	22.9	0.25	6.4	8	224	5000
C100X038TJJ		1	25.4	0.38	9.7	7	140	
C100X150TJJ				1.5	38.1		42	2500
C200X038TJJ		2	50.8	0.38	9.7	3	60	1000
C300X038TJJ		3	76.2			2	40	

Order number of labels required in multiples of Standard Package Quantity.

Tedlar® is a registered trademark of E. I du Pont de Nemours and Company.

Non-Adhesive Polyester Network Labels




- Used to identify patch panels, faceplates, punchdown blocks and other systems hardware
- Temperature range: -10°F to 150°F (-23°C to 65°C)
- Die-cut labels designed to provide maximum aesthetic quality and appearance

Part Number	Color	Width		Height		Application	Labels Per Row	Labels Per Sheet	Labels Per Pkg.
		In.	mm	In.	mm				
C150X030Y1J	White	1.5	38.1	0.3	7.6	3-port identifier	4	112	1000
C195X040Y1J		1.95	49.5	0.4	10.2	Single-gang faceplate	3	60	
C261X035Y1J		2.61	66.3	0.35	8.9	4-port identifier	2	48	
C282X030Y1J		2.82	71.6	0.3	7.6	4-port identifier		52	
C288X040Y1J		2.88	73.2	0.4	10.2	Double-gang faceplate		40	
C390X030Y1J		3.9	99.1	0.3	7.6	6-port identifier		48	
C750X050Y1J		7.5	190.5	0.5	12.7	110 block	1	16	500
C788X050Y1J		7.88	200.2			GP6™ Punchdown System			

Order number of labels required in multiples of Standard Package Quantity.

Polyolefin Network Labels



- Used to identify patch panels, faceplates, punchdown blocks, and other systems hardware
- Temperature range: -40°F to 180°F (-40°C to 82°C)
- Used to identify electrical and electronic components and devices

	Color	Width		Height		Type of Application	Labels Per Row	Labels Per Sheet	Labels Per Pkg
Part Number		In.	mm	In.	mm				
C061X030FJJ	White	0.61	15.5	0.30	7.6	1-port identifier	13	325	5000
C100X038FJJ		1.00	25.4	0.38	9.7	General Identifier	7	140	
C125X030FJJ		1.25	31.8	0.30	7.6	2-port identifier	6	150	
C138X019FJJ		1.38	35.1	0.19	4.8	Module identifier	5	170	2500
C150X075FJJ		1.50	38.1	0.75	19.1	General Identifier		60	
C188X030FJJ		1.88	47.8	0.30	7.6	3-port identifier	4	100	1000
C200X100FJJ		2.00	50.8	1.00	25.4	General Identifier		36	
C225X450FJJ		2.25	57.2	4.50	114.3		4-port identifier	3	6
C252X030FJJ		TIA Blue	2.52	64.0	0.30	7.6			75
C252X030FRJ									
C252X030FTJ	TIA Green								
C261X030FJJ	White	2.61	66.3	0.30	7.6	5-port identifier	2	50	100
C315X030FJJ		3.15	80.0					4	
C350X500FJJ		3.50	88.9	5.00	127.0	General identifier		50	1000
C379X030FJJ		3.79	96.3	0.30	7.6	6-port identifier		2	
C500X700FJJ		5.00	127.0	7.00	177.8	General identifier	1	2	50
C700X250FJJ		7.00	177.8	2.50	63.5			4	100
C788X050FJJ		7.88	200.2	0.50	12.7	GP6™ Punuchdown System		25	420

Order number of labels required in multiples of Standard Package Quantity.

Polyester Safety Labels



- Specially designed polyester media withstands moisture and provides chemical and tough abrasion resistance for outstanding durability in demanding industrial environments
- Excellent durability rating when recommended inks* are used for extended life in harsh environments
- Super-tack permanent adhesive for inkjet and laser media; strong adhesion eliminates curling and maintains fixed mounting over the life of the sign
- Create custom sign legends with Easy-Mark Plus™ Labeling Software
- Temperature range: -65°F to 225°F (-54°C to 107°C)

Part Number	Printer Type	Description	Width		Height		Signs Per Sheet	Std. Pkg. Qty.
			In.	mm	In.	mm		
SEZ0204I	Inkjet	Polyester inkjet permanent adhesive	2.40	60.9	4.00	101.6	8	25
SEZ0405I			4.00	101.6	4.90	124.5	4	
SEZ0508I			4.90	124.5	8.00	203.2	2	
SEZ0810I			7.75	196.9	10.25	260.4	1	
SEZ0811I			8.50	215.9	11.00	279.4		
SEZ0204RI		Polyester inkjet removable adhesive	2.40	60.9	4.00	101.6	8	25
SEZ0304RI			4.50	114.3	3.00	76.2	4	
SEZ0405RI			4.00	101.6	4.90	124.5		
SEZ0508RI			4.90	124.5	8.00	203.2	1	
SEZ0810RI			7.75	196.9	10.25	260.4		
SEZ0811RI			8.50	215.9	11.00	279.4		
SEZ0204L	Laser	Polyester laser permanent adhesive	2.40	60.9	4.00	101.6	8	25
SEZ0405L			4.00	101.6	4.90	124.5	4	
SEZ0508L			4.90	124.5	8.00	203.2	2	
SEZ0810L			7.75	196.9	10.25	260.4	1	
SEZ0811L			8.50	215.9	11.00	279.4		

* Recommended inks include Epson DURABrite Inks

Rigid Sign for Use with Polyester Safety Labels

Part Number	Description	Width		Height		Std. Pkg. Qty.
		In.	mm	In.	mm	
SEZ-RSB1	Non-adhesive polyethylene blank rigid sign for use with SEZ0508I or SEZ0508L	5.00	127.0	8.00	203.2	5
SEZ-RSB2	Non-adhesive polyethylene blank rigid sign for use with SEZ0810I or SEZ0810L	8.00	203.2	10.00	254.0	

Rigid Safety Tags



- Create your own rigid indoor tags with protected legends in minutes using a laser or inkjet printer
- Innovative tag design of the SEZ0305T2L allows for fast, single pass, printing through your laser printer that includes an integrated clear laminate to protect the printed information
- Create custom tags using SEZ0304RI, peel off, and insert into the self-laminating carrier - the PST Tag Carrier allows tags to be resistant to chemicals and acids
- Create custom tag legends with Easy-Mark Plus™ Labeling Software
- Temperature range for SEZ0305T2L: -51°F to 275°F (-46°C to 135°C)
- Temperature range for SEZ0304RI: -65°F to 225°F (-54°C to 107°C)
- Temperature range for PST-2, 4 & 5: -50°F to 200°F (-46°C to 93°C)

Part Number	Description	Width		Height		Signs Per Sheet
		In.	mm	In.	mm	
SEZ0305T2L	Self-laminating tag for Laser printer, two-sided tag, 8.50" x 14.00" sheet, one tag per sheet	3.00	76.2	5.75	146.1	25
SEZ0304RI	Polyester inkjet removable adhesive printable media for use with tag carriers, four tags per sheet			4.75	120.7	
PST-2	Self-laminating tag carriers for use with SEZ0304RI, Front only lamination	3.25	82.6	5.75	146.1	5
PST-4	Self-laminating tag carriers for use with SEZ0304RI, Front only lamination	3.50	88.9			
PST-5	Self-laminating tag carriers for use with SEZ0304RI, Front and back lamination					

Polyester Adhesive Safety Signs

- Signs can be printed with a standard laser printer
- 8.5" x 11" Polyester signs are halogen free
- Temperature range: -40°F to 311°F (-40°C to 154°C)
- Create custom sign legends with Easy-Mark Plus™ Labeling Software



Part Number	Color	Width		Height		Legend	Signs Per Pkg.
		In.	mm	In.	mm		
SEZ-1CLL	Black / Yellow	8.50	215.9	11.00	279.4	CAUTION	25
SEZ-1DLL	Red, White / Black					DANGER	
SEZ-1NLL	Blue / White					NOTICE	
SEZ-1WLL	Black / Orange					WARNING	
SEZ-1WHLL	White					BLANK	
SEZ-1YLL	Yellow					BLANK	

Easy-Mark Plus™ Labeling Software

- Quickly create complex labels or design detailed labels with multiple zones and objects
- Advanced features such as “drag and drop” functionality and wizard tools
- Labels appear on-screen as they will when printed, eliminating guesswork
- Multiple versions available for greater flexibility
- Use with all existing Panduit Easy-Mark™ and Pan-Mark™ files designed in the past, or update them with new objects and styling

System Requirements:

- 300 MB hard drive space and 2 GB Memory
- 32 or 64-bit operating systems
- Windows XP, Vista, 7, 8, 8.1, or 10
- Microsoft.NET Framework 4.0 or higher
- Mouse or compatible pointing device
- Keyboard
- Optical Disc Drive or USB Port



Part Number	Description	Std Pkg Qty.	Std Pkg Qty.
EMPLUS-CD	Easy-Mark Plus™ Labeling Software, CD-ROM	1	10
EMPLUS-DL	Easy-Mark Plus™ Labeling Software, online download		
EMPLUS-2GO	Easy-Mark Plus™ Labeling Software, USB Flash Drive		
EMPLUS-SERVER	Easy-Mark Plus™ Labeling Software, networkable server based version		

^Windows is a registered trademark of Microsoft Corp. in the United States and/or other countries.

CAD-Connect™ Labeling Software

- Facilitates quick and easy organization of identifiers from CAD for printing within Easy-Mark Plus™ Labeling Software
- Easily capture and organize CAD data for future use and documentation
- Saves time and reduces errors by utilizing identifiers previously created in CAD files to eliminate manual entry of data into labeling software
- Compatible with full versions of AutoCAD* 2002 to 2017 and Visio versions 2002 or newer
- Exports to alternative formats such as Excel^ (XLS) or Text (CSV) files for future use and documentation

- Upgrades available at www.panduit.com

System Requirements:

- 64 MB hard drive space and 64 MB RAM (256 MB RAM recommended)
- Windows 2000, XP, Vista, 7, 8, 8.1 or 10
- Mouse or compatible pointing device
- Microsoft.NET Framework 2.0 or higher
- CD-ROM Drive



Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PROG-CCCD	CAD-Connect™ Labeling Software, including Easy-Mark Plus™ Labeling Software, CD-ROM.	1	10

*AutoCAD is a registered trademark of Autodesk, Inc.

^Visio, Windows, and Excel are registered trademarks of Microsoft Corp. in the United States and/or other countries.

For additional information or questions please call:

Customer Service – 800-777-3300

Technical Support for USA & Canada – 866-871-4571

Latin America – +52-33-3777-6000

Brazil – 5511-3613-2353

Europe – +31-0-546-580-452

Asia Pacific Region – 65-6379-6700

Japan – 81-3-6863-6060

Australia – 61-3-9794-9020



PANDUIT®

Panduit Corp.
World Headquarters
Tinley Park, IL 60487

cs@panduit.com
US and Canada: 800.777.3300
Europe, Middle East, and Africa:
44.20.8601.7200
Latin America: 52.33.3777.6000
Asia Pacific: 65.6305.7575

www.panduit.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[S100X225FAL](#) [S100X400FAL](#) [S100X125FAL](#)