
| | 4 | | 3 | | | 2 | | | | 1 | | | | |
|---|--|--------------------------------|---------------------------|-------------------|--|--------------------------|----------------------|-----------|-----------|------------------|---------------------|------------------|-----------|----|
| | THIS DRAWING IS UNPUBLISHED. | | R PUBLICATION JUNE ,2006. | | LOC | DIST | | RE\ | VISION | 1S | | | | |
| | C COPYRIGHT 2006 BY TYCO ELECTRONICS | CORPORATION. | RIGHTS RESERVED. | |] E | | | DES | SCRIPTIO | N | DATE | DWN | APVD | I |
| | NOTES: | | | | | B ECR- | -06-0134 | 423 | | | 13JUN06 | 6 JMSF | -WK | |
| _ | \triangle pack in accordance with amp sp | PEC 107-3275 | | | | | | | | | 1 | | | _ |
| D | \sim 100 tray pack in accordance wit | | -3275 | | | | | | | | | | | D |
| | Ag PLATING | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | 5 THIS ITEM MUST BE WHITE | | | | | | | | | | | | | |
| | 6 ELECTRICAL CHARACTERISTICS | | | | | | | | | | | | | |
| | FREQUENCY RANGE: NOMINAL IMPEDANCE: | DC — 2 GHz 75 Ohm | | | (1) (2) (3) | 345678 | | | | | | | - | |
| | INSULATION RESISTANCE: WORKING VOLTAGE: | 5000 MOhm 500 Volts RMS d | it Sea Level | | | | | | | | | | | |
| | DIELECTRIC WITHSTAND VOLTAGE: CONTACT RESISTANCE: | 1500 Volts RMS | Max | Ì | | | 2 | |] | 1 | | | | |
| | CENTRE CONTACT: OUTER CONTACT: | 1.50 m0hm Max 0.20 m0hm Max | | | | | | | | | | | | |
| | VSWR @ xGHz: INSERTION LOSS xdb: | N/A N/A | | | | | <u>IIII</u> | | | | | | | |
| | 7 MECHANICAL CHARATERISTICS | | | 4.50 | | | $\gamma\gamma\gamma$ | | | • 1 | | | | |
| | COUPLING RETENTION FORCE: CABLE RETENETION FORCE: | N/A N/A | | ø | | | | | 5 | 2 | | | | I |
| | DURABILITY: | 500 Cycles Min | | | | | | | | | | | | |
| С | 8 <u>ENVIRONMENTAL CHARACTERISTICS</u> OPERATING TEMPERATURE: | -65 to +165 De | egC | | | | | | | | | | | С |
| | 9 FOR TECHNICAL DATA REFER TO YOU | JR LOCAL TYCO ELE | CTRONICS SALES OFFICE | | 14.80 | | 14.80 | | | | | | | I |
| | 10 ALL DIMENSIONS ARE NOMINAL FOR | REFERENCE ONLY I | JNLESS OTHERWISE STATED | | - 14.00 | | 1 7.00 | | | | | | | |
| | | | | | | 31.60 | | | | | | | | |
| | | | | | | | | | | | | | F | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | I |
| | | | | | | | | | | | | | | |
| | | | | | | | · · · · · | | | | A 1 | , | | |
| В | | | | | | | | 2 | 2 | - | 3 RETAIN 3 CONTA | NING RING Act | 8 | Βl |
| | | | | | | | | 1 | 1 | BRASS Z | BODY | | 6 | U |
| | | | | | | | | 2 | 2 | | | | 5 | |
| | | | | | | | | 2 | 2 | SPRING STEEL | 4 SPRIN 5 GASKE | | 4 | |
| | | | | | | | | 2 | 2 | PTFE | | ATION | 2 | |
| | | | | | | | | 2 | 2) 10 | BRASS Z | SHELL | - CRIPTION | 1 ITEM | |
| | | | | | | | | <u> </u> | | MATERIAL | DESC | | | |
| | | | | | | DUAL 47 | c | TY PER | | PART | S LIST | | | |
| | | | | THIS DRAWING IS A | CONTROLLED DOCUMENT. | DWN 13JUNO J.SANDWELL | | CO | _ | Tyco Electronics | | า | | |
| | | | | DIMENSIONS: | TOLERANCES UNLESS OTHERWISE SPECIFIED: | CHK 13JUNO | EIBO | ctronics | | Bideford EX39 4 | ΗE | | | |
| | | | | mm | | APVD 13JUNO | | BNC | STRA | AIGHT ADAPTOR P | -P 75 (| ОНМ | | |
| А | | | | ↓ <u> </u> | 0 PLC 1 PLC | PRODUCT SPEC | | | | — | | | | A |
| | | | | | $\begin{array}{c} 2 \\ 3 \\ 4 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2$ | APPLICATION SPEC | | CAGE CODE | | | | RESTRICTI | ED TO | |
| | | | | MATERIAL | 4 PLC ± - ANGLES ± - FINISH | WEIGHT | | | | | | | | |
| | | | | | | WEIGHT | IAJ(| 00775 | | 1 478043 | | | · | I |

SEE TABLE

_

CUSTOMER DRAWING

| | | | | _ | | | | | | |
|---|------|---------------------------|--------------|----------------------|-------|------|---------------|-----|--|--|
| | SIZE | SIZE CAGE CODE DRAWING NO | | | | RES | RESTRICTED TO | | | |
| _ | A3 | 00779 | C- 14 | | | | | | | |
| | | | | ^{scale} NTS | SHEET | 1 04 | 1 | REV | | |
| | | | | | | | | • | | |



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 1-1478043-0