

Tool set - TOOL-KIT STANDARD - 1212422

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Toolbag case, equipped with: ferrule crimping pliers, stripping pliers, insulation stripper, cable cutter, screwdriver bladed: 0.6x3.5, 50 pcs. 5-pos. junction box connectors up to 2.5 mm², tool compartment

Product Features

- Rugged and heavy-duty tool bags
- Universal tool sets, with cutting, stripping, crimping, and testing tools from the TOOL fox tool range

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	1900.0 g
Custom tariff number	82060000
Country of origin	Germany

Technical data

Dimensions

Length (b)	165 mm
Width (a)	65 mm
Height	315 mm

General

Color	black
-------	-------

Articles in set

Crimping pliers - CRIMPFOX 6S-F - 1212043



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.5 mm² ... 6 mm², front entry, square crimp

Tool set - TOOL-KIT STANDARD - 1212422

Articles in set

Stripping tool - WIREFOX 10 - 1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

Stripping tool - WIREFOX-D 40 - 1212161



Stripping tool, for stripping cables of 4.5 mm - 40 mm-Ø, insulation thickness of up to 4.5 mm, pivoting blade for round, lengthwise, and spiral cuts

Cable-cutting tool - CUTFOX 18 - 1212129



Cable cutter, angled, for copper and aluminum up to 18 mm diameter (up to 50 mm²)

Screwdriver - SZF 1-0,6X3,5 - 1204517



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Socket terminal block - JBC 2,5/5 - 3240165



5-pos. socket terminal block with spring-cage connection, for toolless wiring with push-in connection method, for one and multi-strand conductors with a cross section of 0.5 to 2.5 mm², insulation housing transparent.

Tool set - TOOL-KIT STANDARD - 1212422

Articles in set

Tool bag, unequipped - TOOL-KIT STANDARD EMPTY - 1212423



Tool box, unequipped

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21043090
eCl@ss 5.1	21043090
eCl@ss 6.0	21049190
eCl@ss 7.0	21049190
eCl@ss 8.0	21045003
eCl@ss 9.0	21045003

ETIM

ETIM 2.0	EC000149
ETIM 3.0	EC000149
ETIM 4.0	EC000149
ETIM 5.0	EC000149

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

EAC

Tool set - TOOL-KIT STANDARD - 1212422

Approvals

Ex Approvals

Approvals submitted

Approval details

EAC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1212422](#)