

Surface Mount Type

Series : **FC** Type : **V**

Low impedance



Features

- Endurance : 105 °C 1000 h
- Low impedance (1/2 for HA series)
- Vibration-proof product is available upon request. ($\phi 8$ mm and larger)
- RoHS compliant

Specifications


Category temperature range	-40 °C to +105 °C							
Rated voltage range	6.3 V.DC to 50 V.DC							
Capacitance range	1 μ F to 1500 μ F							
Capacitance tolerance	± 20 % (120 Hz/+20 °C)							
Leakage current	$I \leq 0.01$ CV or 3 (μ A) After 2 minutes (Whichever is greater)							
Dissipation factor (tan δ)	Please see the attached characteristics list							
Characteristics at low temperature	V.DC	6.3	10	16	25	35	50	(Impedance ratio at 120 Hz)
	Z(-25 °C) / Z(+20 °C)	2	2	2	2	2	2	
	Z(-40 °C) / Z(+20 °C)	3	3	3	3	3	3	
Endurance	After applying rated working voltage for 1000 hours at +105 °C ± 2 °C and then being stabilized at +20 °C, Capacitors shall meet the following limits.							
	Capacitance change	Within ± 20 % of the initial value						
	tan δ	≤ 200 % of the initial limit						
Shelf life	After storage for 1000 hours at +105 °C ± 2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance.(With voltage treatment)							
	After reflow soldering and then being stabilized at +20 °C, capacitor shall meet the following limits.							
Resistance to soldering heat	Capacitance change	Within ± 10 % of the initial value						
	tan δ	Within the initial limit						
	DC leakage current	Within the initial limit						
AEC-Q200	AEC-Q200 compliant							

Frequency correction factor for ripple current

Frequency (Hz)	50, 60	120	1 k	10 k	100 k to
Correction factor	0.70	0.75	0.90	0.95	1.00


Marking

Example : 6.3 V.DC 22 μ F
Marking color : BLACK



R. Voltage (V.DC)	6.3	10	16	25	35	50
Code	j	A	C	E	V	H

Dimensions



() Reference size

(Unit : mm)

Size code	ϕD	L	A, B	H	I	W	P	K
B	4.0	$5.4^{+0.1}_{-0.2}$	4.3	5.5 max.	1.8	0.65 ± 0.1	1.0	$0.35^{+0.15}_{-0.20}$
C	5.0	$5.4^{+0.1}_{-0.2}$	5.3	6.5 max.	2.2	0.65 ± 0.1	1.5	$0.35^{+0.15}_{-0.20}$
D	6.3	$5.4^{+0.1}_{-0.2}$	6.6	7.8 max.	2.6	0.65 ± 0.1	1.8	$0.35^{+0.15}_{-0.20}$
E	8.0	6.2 ± 0.3	8.3	9.5 max.	3.4	0.65 ± 0.1	2.2	$0.35^{+0.15}_{-0.20}$
F	8.0	10.2 ± 0.3	8.3	10.0 max.	3.4	0.90 ± 0.2	3.1	0.70 ± 0.2
G	10.0	10.2 ± 0.3	10.3	12.0 max.	3.5	0.90 ± 0.2	4.6	0.70 ± 0.2

Characteristics list

Endurance : 105 °C 1000 h

Rated voltage (V.DC)	Cap. (±20 %) (μF)	Case size (mm)		Size code	Specification			Part No.	Reflow	Min. Packaging Qty
		φD	L		Ripple current (100 kHz) (+105 °C) (mA r.m.s.)	Impedance (100 kHz) (+20 °C) (Ω)	tan δ (120 Hz) (+20 °C)			Taping (pcs)
6.3	22	4	5.4	B	60	3.00	0.26	EEEF0J220R	(1)	2000
	47	5	5.4	C	95	1.80	0.26	EEEF0J470R	(1)	1000
	68	6.3	5.4	D	140	1.00	0.26	EEEF0J680P	(1)	1000
	100	6.3	5.4	D	140	1.00	0.26	EEEF0J101P	(1)	1000
	220	8	6.2	E	230	0.40	0.26	EEEF0J221P	(2)	1000
	330	8	10.2	F	450	0.30	0.26	EEEF0J331P	(2)	500
	1000	10	10.2	G	670	0.15	0.26	EEEF0J102P	(2)	500
	1500	10	10.2	G	670	0.15	0.26	EEEF0J152P	(2)	500
10	33	5	5.4	C	95	1.80	0.19	EEEF1A330R	(1)	1000
	100	8	6.2	E	230	0.40	0.19	EEEF1A101P	(2)	1000
	150	8	6.2	E	230	0.40	0.19	EEEF1A151P	(2)	1000
	220	8	10.2	F	450	0.30	0.19	EEEF1A221P	(2)	500
	470	10	10.2	G	670	0.15	0.19	EEEF1A471P	(2)	500
	1000	10	10.2	G	670	0.15	0.19	EEEF1A102P	(2)	500
16	10	4	5.4	B	60	3.00	0.16	EEEF1C100R	(1)	2000
	22	5	5.4	C	95	1.80	0.16	EEEF1C220R	(1)	1000
	47	6.3	5.4	D	140	1.00	0.16	EEEF1C470P	(1)	1000
	68	8	6.2	E	230	0.40	0.16	EEEF1C680P	(2)	1000
	100	8	6.2	E	230	0.40	0.16	EEEF1C101P	(2)	1000
	220	10	10.2	G	670	0.15	0.16	EEEF1C221P	(2)	500
	330	10	10.2	G	670	0.15	0.16	EEEF1C331P	(2)	500
	470	10	10.2	G	670	0.15	0.16	EEEF1C471P	(2)	500
	680	10	10.2	G	670	0.15	0.16	EEEF1C681P	(2)	500
25	6.8	4	5.4	B	60	3.00	0.14	EEEF1E68R	(1)	2000
	22	6.3	5.4	D	140	1.00	0.14	EEEF1E220P	(1)	1000
	33	6.3	5.4	D	140	1.00	0.14	EEEF1E330P	(1)	1000
	47	8	6.2	E	230	0.40	0.14	EEEF1E470P	(2)	1000
	68	8	10.2	F	450	0.30	0.14	EEEF1E680P	(2)	500
	100	8	10.2	F	450	0.30	0.14	EEEF1E101P	(2)	500
	220	10	10.2	G	670	0.15	0.14	EEEF1E221P	(2)	500
	330	10	10.2	G	670	0.15	0.14	EEEF1E331P	(2)	500
	470	10	10.2	G	670	0.15	0.14	EEEF1E471P	(2)	500
35	1	4	5.4	B	60	3.00	0.12	EEEF1V1R0R	(1)	2000
	2.2	4	5.4	B	60	3.00	0.12	EEEF1V2R2R	(1)	2000
	3.3	4	5.4	B	60	3.00	0.12	EEEF1V3R3R	(1)	2000
	4.7	4	5.4	B	60	3.00	0.12	EEEF1V4R7R	(1)	2000
	6.8	5	5.4	C	95	1.80	0.12	EEEF1V6R8R	(1)	1000
	10	5	5.4	C	95	1.80	0.12	EEEF1V100R	(1)	1000
	22	6.3	5.4	D	140	1.00	0.12	EEEF1V220P	(1)	1000
	33	8	6.2	E	230	0.40	0.12	EEEF1V330P	(2)	1000
	47	8	6.2	E	230	0.40	0.12	EEEF1V470P	(2)	1000
	100	10	10.2	G	670	0.15	0.12	EEEF1V101P	(2)	500
	220	10	10.2	G	670	0.15	0.12	EEEF1V221P	(2)	500
	330	10	10.2	G	670	0.15	0.12	EEEF1V331P	(2)	500
50	1	4	5.4	B	30	5.00	0.12	EEEF1H1R0R	(1)	2000
	2.2	4	5.4	B	30	5.00	0.12	EEEF1H2R2R	(1)	2000
	3.3	4	5.4	B	30	5.00	0.12	EEEF1H3R3R	(1)	2000
	4.7	5	5.4	C	50	3.00	0.12	EEEF1H4R7R	(1)	1000
	10	6.3	5.4	D	70	2.00	0.12	EEEF1H100P	(1)	1000
	22	8	6.2	E	120	0.70	0.12	EEEF1H220P	(2)	1000
	33	8	10.2	F	300	0.60	0.12	EEEF1H330P	(2)	500
	47	10	10.2	G	500	0.30	0.12	EEEF1H470P	(2)	500
	100	10	10.2	G	500	0.30	0.12	EEEF1H101P	(2)	500
	220	10	10.2	G	500	0.30	0.12	EEEF1H221P	(2)	500

- Please refer to the page of "Reflow Profile" and "The Taping Dimensions".
- When requesting vibration-proof product, please put the last "V" instead to "P"

Guidelines and precautions regarding the technical information and use of our products described in this online catalog.

- If you want to use our products described in this online catalog for applications requiring special qualities or reliability, or for applications where the failure or malfunction of the products may directly jeopardize human life or potentially cause personal injury (e.g. aircraft and aerospace equipment, traffic and transportation equipment, combustion equipment, medical equipment, accident prevention, anti-crime equipment, and/or safety equipment), it is necessary to verify whether the specifications of our products fit to such applications. Please ensure that you will ask and check with our inquiry desk as to whether the specifications of our products fit to such applications use before you use our products.
- The quality and performance of our products as described in this online catalog only apply to our products when used in isolation. Therefore, please ensure you evaluate and verify our products under the specific circumstances in which our products are assembled in your own products and in which our products will actually be used.
- If you use our products in equipment that requires a high degree of reliability, regardless of the application, it is recommended that you set up protection circuits and redundancy circuits in order to ensure safety of your equipment.
- The products and product specifications described in this online catalog are subject to change for improvement without prior notice. Therefore, please be sure to request and confirm the latest product specifications which explain the specifications of our products in detail, before you finalize the design of your applications, purchase, or use our products.
- The technical information in this online catalog provides examples of our products' typical operations and application circuits. We do not guarantee the non-infringement of third party's intellectual property rights and we do not grant any license, right, or interest in our intellectual property.
- If any of our products, product specifications and/or technical information in this online catalog is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially with regard to security and export control, shall be observed.

<Regarding the Certificate of Compliance with the EU RoHS Directive/REACH Regulations>

- The switchover date for compliance with the RoHS Directive/REACH Regulations varies depending on the part number or series of our products.
- When you use the inventory of our products for which it is unclear whether those products are compliant with the RoHS Directive/REACH Regulation, please select "Sales Inquiry" in the website inquiry form and contact us.

We do not take any responsibility for the use of our products outside the scope of the specifications, descriptions, guidelines and precautions described in this online catalog.
