UNCONTROLLED DOCUMENT

8.89 [0.350]

0.50 [0.020]

(8 PLS₁)

4.00 [0.1573 -	
9.94 [0.391]		0.25 [0.010] (2 PLS,) 7.62 [0.300]

C.N.	NAWREK	ANU	REVISION	COMMENTS	U/	ΑTI
- ^ \	MUMBER	ANID	DEMONS	COMMENTS		
	SSB-	—L)	X2685	5ID		

REV.

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	E.C.N. #10208.	7 .8. 96
В	E.C.N. #10BRDR. & REDRAWN.	6.25.01

PART NUMBER

<u> </u>	1	2	3	4	5	6	7	<u> </u>		
			20.0	04	E0.7	89]	I —	-		
<u> </u>	 									
6.10 [0.240]									_ 1.02	[0.040]

- 17.78 [0.700] -


7 10 11 14 15

9 12 13 16

2.54 [0.100]

(7 PLS.)

– 19.05 [0.750] —



ELECTRO-OPTICAL CH	ARACTERIS	TICS TA=25	5°C I	f=20mA	
PARAMETER	MIN	ΤΥP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635		nm	
FORWARD VOLTAGE		2.1	2.8	V_{f}	
REVERSE VOLTAGE	5.0			V_r	I _r = 1 00μΑ
AXIAL INTENSITY		80		mcd	$I_f = 20mA$
VIEWING ANGLE		160		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	RED DIFF	FUSED			

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	' C
SOLDERING TEMP.	+ 260	' C
2.0mm FROM BODY		3 SEC. MAX
* 1/10.5		

t<10µS

UNCONTROLLED DOCUMENT *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.0010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD S

REV. PART NUMBER SSB-LX2685ID

8

19.05mm x 8.89mm LIGHT BAR, RED DIFFUSED.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



CT

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY:

APPROVED BY: DATE: 4.8.93 PAGE: 1 OF 1 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSB-LX2685ID