

UNCONTROLLED DOCL *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX.= +0.00 -DCCIMAL PRECISION CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF 290 E. HELEN ROAD REV. PART NUMBER Α PALATINE, IL 60067-6976 LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX В SSL-LX3034ID PHONE: +1.847.359.2790 INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION US WEB: www.lumex.com CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR TW WEB: www.lumex.com.tw IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. T-3mm (T-1) 635nm RED LED, RELIABILITY NOTE CHECKED BY: APPROVED BY: DATE: DRAWN BY: 3.11.99 OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT PAGE: 1 OF 1 SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. RED DIFFUSED LENS. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS. SCALE: N/A BC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSL-LX3034ID