


# SMD TCXO

## 2.5 x 2.0 x 0.8 mm

### 7L Series

Oscillators  
Series




#### Features

- Temperature Stability:  $\pm 0.5$  ppm ~  $\pm 2.0$  ppm
- Operating Temperature Range:  $-30$  °C ~  $85$  °C
- Supply Voltage:  $1.8$  V ~  $3.3$  V
- Voltage Control Function Available
- Frequencies: 16.367667 MHz, 16.368 MHz, 16.369 MHz, 19.2 MHz, 26 MHz, 33.6 MHz, 38.4 MHz, 40 MHz
- Applications: GPS, WiMAX, Cellular and Wireless Communications
- RoHS Compliant / Pb Free

#### Electrical Specifications


Item / Type		7L
Output Type		Clipped Sinewave
Output Load		10K $\Omega$ // 10 pF
Oscillation Mode		Fundamental
Supply Voltage		1.8 ~ 3.3 V
Frequency Range		13 ~ 52 MHz
Clipped Sinewave Output Voltage		0.8 Vp-p typical
Frequency Stability	Vs. Temperature ( $-30$ ~ $+85$ °C)	$\pm 0.5$ / $\pm 2.0$ ppm
	Vs. Load ( Load varies $\pm 10$ % )	$\pm 0.2$ ppm Max.
	Vs. Supply Voltage ( $V_{cc}$ = Typical $\pm 0.1$ V )	$\pm 0.2$ ppm Max.
Frequency Tolerance	at 25 °C after 2 Reflows with Typical Applied to Auto Frequency Control Pin	$\pm 2.5$ ppm Max.
Slope of Frequency Drift		$\pm 0.1$ ppm / °C Typical ; $\pm 0.5$ ppm / °C Max.
Storage Temperature Range		$-40$ ~ $+85$ °C
Auto Frequency Control ( AFC ) Range ( Center @ 1.4 V )		$\pm 7$ ~ $\pm 16$ ppm / V
Supply Current		2.0 mA Max.
Start-up Time		5 ms Max.
Harmonics		- 5 dBc Max.
Phase Noise at 1 KHz offset		- 130 dBc / Hz
Aging ( at 25 °C )		$\pm 1$ ppm / year Max.

#### Dimensions



#### Pin Connection

Name	Function
Pin 1	AFC
Pin 2	GND
Pin 3	OUTPUT
Pin 4	VCC



Units: mm

Remark : Specification subject to change without prior notice. Please confirm with our sales.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## [TXC Corporation:](#)

[7L-16.367667MCG-T](#) [7L-16.367667MCS-T](#) [7L-16.3676MCG-T](#) [7L-16.3676MCS-T](#) [7L-16.368MCG-T](#) [7L-16.368MCS-T](#) [7L-16.369MCG-T](#) [7L-16.369MCS-T](#) [7L-19.200MCG-T](#) [7L-19.200MCS-T](#) [7L-26.000MCG-T](#) [7L-26.000MCS-T](#) [7L-38.400MCG-T](#) [7L-38.400MCS-T](#) [7L-40.000MCG-T](#) [7L-40.000MCS-T](#) [7L-16.367667MBG-T](#) [7L-16.367667MBS-T](#) [7L-16.367667MDG-T](#) [7L-16.367667MDS-T](#) [7L-16.3676MBG-T](#) [7L-16.3676MBS-T](#) [7L-16.3676MDG-T](#) [7L-16.3676MDS-T](#) [7L-16.368MBG-T](#) [7L-16.368MBS-T](#) [7L-16.368MDG-T](#) [7L-16.368MDS-T](#) [7L-16.369MBG-T](#) [7L-16.369MBS-T](#) [7L-16.369MDG-T](#) [7L-16.369MDS-T](#) [7L-19.200MBG-T](#) [7L-19.200MBS-T](#) [7L-19.200MBV-T](#) [7L-19.200MCV-T](#) [7L-19.200MDG-T](#) [7L-19.200MDS-T](#) [7L-19.200MDV-T](#) [7L-26.000MBG-T](#) [7L-26.000MBN-T](#) [7L-26.000MBS-T](#) [7L-26.000MCN-T](#) [7L-26.000MDG-T](#) [7L-26.000MDN-T](#) [7L-26.000MDS-T](#) [7L-38.400MBG-T](#) [7L-38.400MBS-T](#) [7L-38.400MDG-T](#) [7L-38.400MDS-T](#) [7L-40.000MBG-T](#) [7L-40.000MBN-T](#) [7L-40.000MBS-T](#) [7L-40.000MCN-T](#) [7L-40.000MDG-T](#) [7L-40.000MDN-T](#) [7L-40.000MDS-T](#) [7L26076001](#) [7L30073001](#) [7L26002009](#) [7L26001018](#) [7L40022002](#) [7L26001005](#) [7L19273001](#) [7L40021001](#) [7L40081002](#) [7L26002022](#) [7L26002017](#) [7L26003006](#) [7L16303002](#) [7L40001002](#) [7L19202002](#) [7L26002007](#) [7L-38.400MDN-T](#) [7L-38.400MBN-T](#) [7L-38.400MCN-T](#)