




Single Port PoE Gigabit Switch Powered by Ultra PoE Extends Ethernet Data and PoE to 200 Meters



Features

- IEEE802.3at Compliant Output
- 0-55C Operating Temperature Range
- Gigabit Compatible
- Extends Ethernet to 200 meters
- Powered by Ultra PoE
- Detects 12.5K signature resistance
- Boost Circuit to Compensate for Wire Drops
- 1 Year Warranty

Applications

- IP Cameras
- Access Controls
- Wireless Access Points

Safety Approvals

- CE

Mechanical Characteristics

- Length: 120mm (4.72in)
- Width: 60mm (2.36in)
- Height: 32mm (1.26in)
- Weight: 0.6Kg (1.3lb)

Output Specifications

Model	DC Output Voltage			Output Current		Output Power
	Min.	Typ.	Max.	Min.	Max.	
POE30S-1ATG	54V	56V	57V	10mA	550mA	30W

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:**Input Source**

Receives power from Ultra PoE Midspan

Input Detection

12.5K Detection

DC Input Voltage Range

50VDC to 57VDC

DC Input Current

1.6A at 57VDC and maximum load

OUTPUT:**Total Output Power**

30W with Ultra PoE Input

Ripple and Noise (Vp-p)

250mV maximum

Output Detection

25K Detection IEEE802.3at compliance

Efficiency

75% minimum at maximum load

ENVIRONMENTAL

Operating Temperature 0 to 40°C
(gigabit data rates)

Operating Temperature 0 to 55°C
(10Mb and 100Mb data rates)

Storage Temperature -25 to +65°C

Humidity 5 to 90%

EMI

EN55022 Class A, FCC part 15 Class A

Warranty

1 Year

Immunity

ESD EN61000-4-2 Level 3

RS EN61000-4-3 Level 3

Surge EN61000-4-5 Level 2

Isolation (HI-POT)

2121VDC for 1 min, 10mA

Insulation Resistance

Input to Ground: >10M OHM 500VDC

Output to Ground: >10M OHM 500VDC

FEATURES**Over Current Protection**

For PoE Class 0-3 Detection on Output: 450mA maximum

For PoE Class 4 Detection on Output: 650mA maximum

Short Circuit Protection

Outputs equipped with short circuit protection
The output can be shorted permanently without damage

Indicators

Ethernet – IN/OUT **Green LED1 and LED2** -
10Mb Activity

Green LED1 – 100Mb Activity

Green LED2 – 1Gb Activity

Orange LED3 – Link Activity

POE **Blinking GREEN** – Unit is ON
Active with No Load

Solid GREEN – Unit has
detected a valid IEEE802.3at
load

Blinking RED/GREEN – unit
has detected an invalid load

Solid RED – unit is in over-load
condition

Input/Output Connectors


RJ45

Input Connection

Pins: 1,2 7,8 GND / Pins: 3,6 4,5 +VIN

Output Connection

Pins: 1,2 GND / Pins: 3,6 +VIN



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phihong:](#)

[POE30S-1ATG-R](#)