


(1.27 mm) .050"



# SMT & THROUGH-HOLE HEADER

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?TFM](http://www.samtec.com?TFM) or [www.samtec.com?TFML](http://www.samtec.com?TFML)

**Insulator Material:** Black Liquid Crystal Polymer  
**Terminal Material:** Phosphor Bronze  
**Plating:** Au or Sn over 50 μ" (1.27 μm) Ni  
**Current Rating (TFM/SFM):** 3.2 A per pin (2 pins powered)  
**Voltage Rating:** 250 VAC mated with SFM  
**Operating Temp Range:** -55 °C to +125 °C  
**RoHS Compliant:** Yes


**TFM Board Mates:** SFM, SFMC

**TFM Cable Mates:** SFSD


**TFML Board Mates:** SFML

**TFM-DH Board Mates:** SFM (-DH), SFMC

**TFM-DH Cable Mates:** SFSDX (-S, -D, -SR, -DR)



## APPLICATIONS



## PROCESSING

**Lead-Free Solderable:** Yes  
**SMT Lead Coplanarity:** (0.10 mm) .004" max (05-25) (0.15 mm) .006" max (30-50)\*  
 \*(.004" stencil solution may be available; contact [IPG@samtec.com](mailto:IPG@samtec.com))

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



**TYPE STRIP**

1

**NO. PINS PER ROW**

**LEAD STYLE**

**PLATING OPTION**

**TFM**  
= Standard

**TFML**  
= Locking (-01 & -02 lead style only)

03, 04, 06, 08  
(TFM -01 & -02 only)

05, 07, 10, 15, 20, 25, 30, 35, 40, 45, 50  
(Standard sizes)

Specify LEAD STYLE from chart

-L  
= 15 μ" (0.38 μm) Gold on post, Matte Tin on tail (Call Samtec for E.L.P.™ plating option)


## MATED HEIGHTS

| LEAD STYLE |     | MATED HEIGHT* |
|------------|-----|---------------|
| TFM        | SFM |               |
| -02        | -02 | (6.35) .250   |
| -12        |     | (8.13) .320   |
| -22        |     | (9.91) .390   |
| -32        |     | (11.81) .465  |
| LEAD STYLE |     | MATED HEIGHT* |
| TFM        | SFM |               |
| -01        | -01 | (5.97) .235   |
| -03        |     | (5.97) .235   |
| -11        |     | (7.75) .305   |
| -13        |     | (7.75) .305   |
| -21        |     | (9.53) .375   |
| -23        |     | (9.53) .375   |
| -31        |     | (11.43) .450  |

\*Processing conditions will affect mated height.




| LEAD STYLE (T/H) | B            | C           |
|------------------|--------------|-------------|
| -01              | (5.59) .220  | (1.97) .078 |
| -03*             | (5.59) .220  | (2.77) .109 |
| -11*             | (7.37) .290  | (1.97) .078 |
| -13*             | (7.37) .290  | (2.77) .109 |
| -21*             | (9.14) .360  | (1.97) .078 |
| -23*             | (9.14) .360  | (2.77) .109 |
| -31*             | (11.05) .435 | (1.97) .078 |

\* Not Available with 07 or -S row option



| LEAD STYLE (SMT) | A            |
|------------------|--------------|
| -02              | (5.72) .225  |
| -12*             | (7.49) .295  |
| -22*             | (9.27) .365  |
| -32*             | (11.18) .440 |

\* N/A with 07, -DH or -S row option




**Note:** Some sizes, styles and options are non-standard, non-returnable.



Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.




**TFM, TFML SERIES**



- Passes 10 Year MFG
- Locking option
- Locking clip option
- Weld tab option
- Screw down option


**ROW OPTION**

- S**  
= Single Row (TFM only)
- D**  
= Double Row
- DH\***  
= Double Horizontal (TFM lead style -02 only) (05 thru 50 positions only) (-TR option only available)



**OPTION**

- Specify only -RA, -RE1 or -RE2
- RA**  
= Right-angle (Lead style -01 only)
- RE1**  
= Right-angle Elevated for (1.58 mm) .062" PCB (Requires TFM lead style -01, -D row and -WT)
- RE2**  
= Right-angle Elevated for (2.36 mm) .093" PCB (Requires TFM lead style -01, -D row and -WT)



- Specify only -A, -LC, -DS or -WT. Not available with -RA, -RE1 and -RE2 unless otherwise noted.
- A**  
= Alignment Pin
- LC**  
= Locking Clip (Manual Placement required)
- DS**  
= Dual Screw Down for (1.60 mm) .062" PCB (05, 07, 10, 15, 20, 25, 30, 35, 40 positions only) (TFM lead styles -01 and -02 only) (Requires -D row option) (Mates with SFM-DS option and SFSD/SFSDT -SS and -DS option only) (Not available with -A, -LC, -WT, -K, -P, -TR)
- WT**  
= Weld Tab (TFM lead styles -01 and -02 only) (Required callout for -RE1 & -RE2) (Mates to SFSS/SFSD -SR and -DR option only) (05, 07, 10, 15, 20, 25, 30, 35, 40, 45, 50 positions only)

- SMT lead styles only. Specify only -K or -P
- K**  
= Polyimide Film Pick & Place Pad
- P**  
= Plastic Pick & Place Pad (5 positions minimum) (Not available with 5 position with -WT)
- Specify -TR last
- TR**  
= Tape & Reel (Not available with -DS)

**ALSO AVAILABLE (MOQ Required)**

- Solder nail option
- Other sizes
- Other platings

\* Notes:  
Weld tab is standard on -DH option.  
No need to specify -WT.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[TFM-110-02-S-D-WT-TR](#)