

The image displays three distinct types of industrial connectors. On the left is a D-sub connector with a black plastic housing and a metal shield. In the center is a circular connector with a black plastic housing and a metal shield. On the right is a fiber optic connector with a black plastic housing and a metal shield. All three connectors have multiple pins or fibers protruding from the bottom.

- Roller Lever
- Overtravel

Part Number	Oper. Force	Release Force	Pretravel	Overtravel	Movement Diff.	Operating Point
72-1160 Roller Lever (1)	10 oz max	1.5 oz min	.150 max	.035 min	.070 ± .015	1.0 ± .031
72-2080 over travel (2)	17 ± 5 oz	4 oz min	.060 max	.215 min	.030 ± .007	.828 ± .031

(1) When used with 22-104 basic switch or 22-204 basic switch. (2) When used with 22-304 basic switch

[illegible]

15/32-32 HEX NUT

21.03 ± 0.79
.828 ± .031
OPER. PT.

STAINLESS STEEL
INTERNAL TOOTH
LOCKWASHER

17V
CHICAGO, ILL.
U.S.A.

TYPICAL SWITCH APPLICATION
(SWITCH NOT INCLUDED)

71

800.544.3354

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ITW Switches:](#)

[72-1160](#) [72-2080](#)