

Cable - FLK 14/EZ-DR/ 150/KONFEK - 2288927

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Round cable set, with two 14-pos. socket strips (1:1 connection), for connecting 8 channels, cable length: 1.5 m



Key Commercial Data

| | |
|--------------------------------------|--|
| Packing unit | 1 pc |
| GTIN |  4 017918 057312 |
| Weight per Piece (excluding packing) | 120.0 g |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

General

| | |
|---|---|
| Nominal voltage U _N | < 50 V AC 60 V DC |
| Max. current carrying capacity per path | 1 A |
| Max. conductor resistance | 0.16 Ω/m |
| Length of cable | 1.5 m |
| Single wire, cross section | 0.14 mm ² |
| Single wire, cross section [AWG] | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| External diameter | 6.4 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding | no |
| Outer sheath, material | PVC |

Cable - FLK 14/EZ-DR/ 150/KONFEK - 2288927

Technical data

General

| | |
|------------------------|---------------|
| External sheath, color | gray RAL 7035 |
|------------------------|---------------|

Environmental conditions

| | |
|---|------------------------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Flame resistance | IEC 60332-1 |
| | DIN VDE 0482 Part 332-1 |
| Resistance to oil | DIN VDE 0472 Part 803, test type B |
| Gasoline resistance | Against occasional splashes |

Connector, module side

| | |
|-----------------------|--------------------------------|
| Connection method | IDC/FLK socket strip (2.54 mm) |
| Number of connections | 1 |
| Number of positions | 14 |

Connector, controller side

| | |
|-----------------------|--------------------------------|
| Connection method | IDC/FLK socket strip (2.54 mm) |
| Number of connections | 1 |
| Number of positions | 14 |

Supported controller

| | |
|---------------------|----------------|
| Controller | GE-FANUC 90-30 |
| - suitable I/O card | IC693 ALG220 |
| | IC693 ALG221 |
| | IC693 ALG222 |
| | IC693 ALG223 |
| | IC693 ALG390 |
| | IC693 ALG391 |
| | IC693 ALG392 |
| | IC693 ALG442 |
| | IC693 MDL241 |
| | IC693 MDL634 |
| | IC693 MDL645 |
| | IC693 MDL646 |
| | IC693 MDL732 |
| | IC693 MDL733 |
| | IC693 MDL740 |
| | IC693 MDL741 |
| | IC693 MDL742 |

Cable - FLK 14/EZ-DR/ 150/KONFEK - 2288927

Technical data

Supported controller

| | |
|---------------------|---------------------------|
| Controller | SIEMENS S7-300 / ET 200 M |
| - suitable I/O card | CPU 312C |
| | CPU 313C |
| | CPU 313C-2DP |
| | CPU 313C-2PtP |
| | CPU 314C-2DP |
| | CPU 314C-2PtP |
| | 6ES7 321-1BH02-0AA0 |
| | 6ES7 321-1BH10-0AA0 |
| | 6ES7 321-1BH50-0AA0 |
| | 6ES7 321-1BL00-0AA0 |
| | 6ES7 321-7BH01-0AB0 |
| | 6ES7 322-1BH01-0AA0 |
| | 6ES7 322-1BH10-0AA0 |
| | 6ES7 322-1BL00-0AA0 |
| | 6ES7 322-8BF00-0AB0 |
| | 6ES7 322-8BH01-0AB0 |
| | 6ES7 323-1BH01-0AA0 |
| | 6ES7 323-1BL00-0AA0 |
| | 6ES7 331-7HF01-0AB0 |
| | 6ES7 331-7KB02-0AB0 |
| | 6ES7 331-7KF02-0AB0 |
| | 6ES7 331-7NF00-0AB0 |
| | 6ES7 331-7PF01-0AB0 |
| | 6ES7 331-7PF11-0AB0 |
| | 6ES7 332-5HD01-0AB0 |
| | 6ES7 332-5HB01-0AB0 |
| | 6ES7 332-7ND02-0AB0 |
| | 6ES7 332-8TF01-0AB0 |
| | 6ES7 334-0CE01-0AA0 |
| | 6ES7 334-0KE00-0AB0 |
| | 6ES7 335-7HG01-0AB0 |
| | 6ES7 336-4GE00-0AB0 |
| | 6ES7 338-4BC01-0AB0 |
| | 6ES7 350-1AH03-0AE0 |
| | 6ES7 350-2AH01-0AE0 |
| | 6ES7 351-1AH01-0AE0 |

Cable - FLK 14/EZ-DR/ 150/KONFEK - 2288927

Technical data

Supported controller

| | |
|---------------------|-----------------------------|
| | 6ES7 352-1AH02-0AE0 |
| | 6ES7 353-1AH01-0AE0 |
| | 6ES7 354-1AH01-0AE0 |
| | 6ES7 355-0VH10-0AE0 |
| | 6ES7 355-1VH10-0AE0 |
| | 6ES7 357-4AH01-0AE0 |
| Controller | ALLEN-BRADLEY ControlLogix |
| - suitable I/O card | 1756-IN16 |
| | 1756-IA8D |
| | 1756-IA16 |
| | 1756-IB16 |
| | 1756-IC16 |
| | 1756-OB16E |
| | 1756-IF6I |
| | 1756-IR6I |
| | 1756-IT6I |
| | 1756-OF4 |
| | 1756-OF6CI |
| | 1756-OF8 |
| | 1756-PLS |
| Controller | ALLEN-BRADLEY SLC 500 |
| - suitable I/O card | 1746 OB16 |
| | 1746 OV16 |
| | 1746 OG16 |
| | 1746 IA16 |
| | 1746 IB16 |
| | 1746 ITB16 |
| | 1746 IN16 |
| | 1746 IV16 |
| | 1746 ITV16 |
| | 1746 IG16 |
| Controller | HONEYWELL Experion PKS C200 |
| - suitable I/O card | TC-IDX 081 |
| | TC-IDA 161 |
| | TC-IAH 061 |
| | TC-IXR 061 |
| | TC-IXL 061 |

Cable - FLK 14/EZ-DR/ 150/KONFEK - 2288927

Technical data

Supported controller

| | |
|---------------------|--|
| | TC-OAH 061 |
| | TC-OAV 061 |
| | TC-OAV 081 |
| Controller | Schneider Electric MODICON TSX QUANTUM |
| - suitable I/O card | DDI 353 |
| | DDI 853 |
| | DAI 353 |
| | DAI 453 |
| | DDO 353 |

Standards and Regulations

| | |
|----------------------------------|------------------------------------|
| Resistance to oil | DIN VDE 0472 Part 803, test type B |
| Connection in acc. with standard | CUL |
| Flame resistance | IEC 60332-1 |
| | DIN VDE 0482 Part 332-1 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27249205 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000237 |
| ETIM 3.0 | EC000237 |
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC000237 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121620 |
| UNSPSC 7.0901 | 26121620 |
| UNSPSC 11 | 26121620 |
| UNSPSC 12.01 | 26121620 |

Cable - FLK 14/EZ-DR/ 150/KONFEK - 2288927

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 26121620 |
|-------------|----------|

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

Ex Approvals

Approvals submitted


Approval details

| |
|---|
| UL Recognized  |
|---|

| |
|--|
| cUL Recognized  |
|--|

| |
|-----|
| EAC |
|-----|

| |
|-----|
| EAC |
|-----|

| |
|--|
| cULus Recognized  |
|--|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2288927](#)