

Product: [8450](#) 

Audio & Instrumentation, #22-1pr, TC, O/A Foil, CM



Product Description

22 AWG solid tinned copper conductors, polypropylene insulation, twisted pair, overall Beldfoil® shield (100% coverage), 22 AWG solid TC drain wire, PVC jacket.

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring |
|------------------------|---|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | Nominal Diameter | No. of Pairs |
|-----|-----------|--------------------|------------------|--------------|
| 22 | Solid | TC - Tinned Copper | 0.02635 in | 1 |

| | |
|------------------------|---|
| Conductor Count: | 2 |
| Total Number of Pairs: | 1 |

Insulation

| Material | Nominal Wall Thickness |
|--------------------|------------------------|
| PP - Polypropylene | 0.007 in |

Color Chart

| Number | Color |
|--------|-------------|
| 1 | Black & Red |

Outer Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire Diameter | Drainwire AWG | Drainwire Construction n x D |
|------|-------------|---------------------|--------------|--------------------|--------------------|---------------|------------------------------|
| Tape | Alum / Poly | Beldfoil® (Z-Fold®) | 100 % | TC - Tinned Copper | 0.02635 mm | 22 | Solid |

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.118 in | 0.018 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Conductor DCR | Conductor Resistance | Nominal Outer Shield DCR |
|-----------------------|-----------------------|----------------------|--------------------------|
| 16.1 Ohm/1000ft | 16.1 Ohm/1000ft | | 12.65 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
| 40 pF/ft | 76 pF/ft |

Inductance

| Nominal Inductance |
|--------------------|
| 0.08 µH/ft |

Impedance

Nominal Characteristic Impedance

40 Ohm

Delay

Nominal Delay Nominal Velocity of Propagation (VP) [%]

1.5 ns/ft 66 %

Current

Max. Recommended Current [A]

2.9 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

| | |
|-----------------------|-----------------|
| UL Temp Rating: | 75°C |
| Operating Temp Range: | -20°C To +105°C |

Mechanical Characteristics

| | |
|----------------------------------|---------------|
| Bulk Cable Weight: | 12 lbs/1000ft |
| Max Recommended Pulling Tension: | 37 lbs |
| Min Bend Radius/Minor Axis: | 1.25 in |

Standards

| | |
|--------------------------|-----|
| NEC/(UL) Specification: | CM |
| CEC/C(UL) Specification: | CM |
| CPR Euroclass: | Eca |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| Environmental Space: | Indoor (Not Riser or Plenum) |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| MII Order #39 (China RoHS): | Yes |

Flammability, LSOH, Toxicity Testing

| | |
|-----------------------|-------------------|
| UL Flammability: | UL1685 UL Loading |
| ISO/IEC Flammability: | IEC 60332-1-2 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|-------|------------|----------|--------------|
| 8450 010U500 | Black | UnReel | 500 ft | 612825207672 |
| 8450 0101000 | Black | Reel | 1,000 ft | 612825207627 |
| 8450 010U1000 | Black | UnReel | 1,000 ft | 612825207634 |
| 8450 0081000 | Gray | Reel | 1,000 ft | 612825207641 |

History

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[8450 0101000](#) [8450 010U1000](#)