

Specification Sheet

Part Number: TSR1FW-8A



One Piece Surface Raceway, 3/4", 8.0 ft Long, PVC, Office White, 160ft/Carton

|                     |   |
|---------------------|---|
| Article Number      | 250-01800   |
| Type                | TSR1-8A   |
| Color               | Office White (OEWH)   |
| Features & Benefits | <ul style="list-style-type: none"><li>• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.</li><li>• PVC construction is lightweight, durable and more affordable than metallic raceway systems.</li><li>• Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing.</li><li>• Foam tape backing with rubber based adhesive conforms to any flat surface to assist with temporary positioning and mounting.</li><li>• Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.</li><li>• Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.</li></ul> |
| Quantity Per        | carton  |

|                            |   |
|----------------------------|---|
| <b>Product Description</b> | HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. |
| <b>Short Description</b>   | One Piece Surface Raceway, 3/4", 8.0 ft Long, PVC, Office White, 160ft/Carton   |
| <b>Global Part Name</b>    | TSR1-8A-PVC-WH  |
| <b>Length L (Imperial)</b> | 8.0   |
| <b>Length L (Metric)</b>   | 2.44  |
| <b>Width W (Imperial)</b>  | 0.75  |
| <b>Width W (Metric)</b>    | 19.05   |
| <b>Height H (Imperial)</b> | .50   |
| <b>Height H (Metric)</b>   | 12.70   |
| <b>Material</b>            | Polyvinylchloride (PVC)   |
| <b>Material Shortcut</b>   | PVC   |

|                                       |                |
|---------------------------------------|----------------|
| <b>Flammability</b>                   | UL 94 V0       |
| <b>Halogen free</b>                   | No             |
| <b>Operating Temperature (Metric)</b> | +122°F (+50°C) |
| <b>Reach Complaint(Article 33)</b>    | No             |
| <b>ROHS Complaint</b>                 | Yes            |
| <b>Package Quantity(Imperial)</b>     | 160            |
| <b>Package Quantity (Metric)</b>      | 48.80          |
| <b>Customs Number</b>                 | 3925900000     |