


1. THIS CONNECTOR MEETS ALL APPLICABLE SPECIFICATIONS OF MIL-C-81659.
2. CONTACTS ARE RELEASED FROM FRONT AND REMOVED FROM REAR OF CONNECTOR.
3. POLARIZING KEYS ARE ASSEMBLED IN POSITION 01; (445595-1 THRU -6)
4. REPLACEMENT SOCKET CONTACT ASSY PART NUMBER IS 445591-1.
5. CONTACTS AND SEALING PLUGS ARE NOT INSTALLED. PACKAGED BULK IN SEPARATE BAGS.
6. FLOATING BUSHING, IN 4 CORNER MOUNTING HOLES, 4 REQUIRED  
MATERIAL: STAINLESS STEEL  
FINISH: PASSIVATED
7. WITHOUT CONTACTS
8. WITHOUT CONTACTS AND SEALING PLUGS
9. POLARIZING KEYS ARE ASSEMBLED IN POSITION 05; (445595-7 ONLY)

LOC		DIST		REVISIONS			
DF		AO		REV	DESCRIPTION	DATE	OWN
				K	REV PER ECO 13-006427	12APR2013	RJM

BD2P124S124S-8805	9 6 8	445595-7
BD2P124S124S-8001	3 8	445595-6
BD2P124S124S-8801	3 6 8	445595-5
BD2P124S124S-8801	3 6 8	445595-4
BD2P124S124S-8001	3 8	445595-3
BD2P124S124S-8801	3 445595-1 6	445595-2
BD2P124S124S-8001	3 AS SHOWN	445595-1
AMP DESCRIPTIVE NO.	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN BRENT YOHN 9-15-88	 TE Connectivity	
DIMENSIONS: INCHES		CHK EDWARD J. HOWARD 9-15-88	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD E. HOWARD 9-15-88	PRODUCT SPEC	
0 P/LC ± -		APPLICATION SPEC		SIZE A1
1 P/LC ± -		WEIGHT		
2 P/LC ± -		CUSTOMER DRAWING		SCALE 2:1
3 P/LC ± .005		SHEET 1 OF 1		
4 P/LC ± -		REV K		RESTRICTED TO
ANGLES ± -		DRAWING NO. 00779		
FINISH SEE CALLOUTS		CAGE CODE 445595		PART NUMBER 445595
MATERIAL SEE CALLOUTS		DRAWING NO. 445595		

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[445595-4](#)