




DESCRIPTION: CAT5E ASSEMBLED PATCH CABLE
 MODEL NUMBER: 73-777X-XXX
 APPLICATION: PATCH CABLE
 CRIMP TOOL: N/A
 IMPEDANCE: N/A
 TEMPERATURE RANGE: 0 ~ 75 DEG C
 MATERIAL: PLUG RJ-45, GOLD PLATED ON CONTACTS
 CABLE UTP, 24 AWG, 4 TWISTED PAIRS, STRANDED BARE COPPER,
 UL ETL EIA/TIA-568B VERIFIED CATEGORY 5E
 RoHS COMPLIANCE: YES
 TECHNICAL DETAIL: N/A



PIN ASSIGNMENT		
	P1	P2
WHITE/ORANGE	1	1
ORANGE	2	2
WHITE/GREEN	3	3
GREEN	6	6
BLUE	4	4
WHITE/BLUE	5	5
WHITE/BROWN	7	7
BROWN	8	8

X=COLOR
 0-GRAY
 1-BLACK
 2-BLUE
 3-GREEN
 4-RED
 5-YELLOW
 6-WHITE
 7-ORANGE
 8-PINK
 9-PURPLE

TABLE 1

MODEL NUMBER	LENGTH (FEET)	DESCRIPTION
73-777X-1	1	CATE 5E ASSEMBLED PATCH CABLE , 1FT
73-777X-3	3	CATE 5E ASSEMBLED PATCH CABLE , 3FT
73-777X-5	5	CATE 5E ASSEMBLED PATCH CABLE , 5FT
73-777X-7	7	CATE 5E ASSEMBLED PATCH CABLE , 7FT
73-777X-10	10	CATE 5E ASSEMBLED PATCH CABLE , 10FT
73-777X-14	14	CATE 5E ASSEMBLED PATCH CABLE , 14FT
73-777X-25	25	CATE 5E ASSEMBLED PATCH CABLE , 25FT
73-777X-50	50	CATE 5E ASSEMBLED PATCH CABLE , 50FT
73-777X-100	100	CATE 5E ASSEMBLED PATCH CABLE , 100FT

THIS PROPRIETARY DOCUMENT IS PROPERTY OF CINCH CONNECTIVITY SOLUTIONS. IT IS CONFIDENTIAL IN NATURE, NON-TRANSFERABLE, AND ISSUED WITH THE CLEAR UNDERSTANDING THAT IT IS NOT TO BE REPRODUCED OR COPIED WITHOUT PERMISSION AND IS RETURNABLE UPON DEMAND. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.	3RD ANGLE PROJECTION 	AIM-Cambridge	
	RoHS2 2011/65/EU	Title: CAT 5E ASSEMBLED PATCH CABLE	
	.X ±.3 .XX ±.15 ANGLES ±2°	Model No. 73-777X-XXX	
	Size A	DO NOT SCALE DRAWING	Date: 2015/8/4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions:](#)

[73-7773-7](#)