

## Sleeve housing for cable connector - TU-0000000TUDU - 1605891

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Sleeve housing for cable connector, angled, Bayonet locking, M23, shielded: yes, cable diameter range: 2 mm ... 14.5 mm





## **Key Commercial Data**

Packing unit	8 pc
GTIN	4 046356 255509
GTIN	4046356255509

### Technical data

#### General

Note	Order information: Order contact inserts separately
Type of locking	Bayonet locking
Contact connection method	Crimp connection
Type of contacts	Socket
Conductor entry	2 mm 14.5 mm
Pg housing screw connection	none

#### Ambient conditions

Ambient temperature	-20 °C 125 °C
Degree of protection	IP67

#### Material

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Gasket and O-ring material	FPM

### Specifications according to DIN EN 61984:2001

	2000 m
--	--------

#### **Environmental Product Compliance**

	<u>'</u>	
REACh SVHC		Lead 7439-92-1




# Sleeve housing for cable connector - TU-0000000TUDU - 1605891


## Technical data

## **Environmental Product Compliance**

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## **Drawings**





Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1605891