
# XZCE13M785M

adaptor, metal - tapped hole Pg 13.5 - for male connector, 7/8" 16UN, 5-wire

Product availability: Non-Stock - Not normally stocked in distribution facility



# Main

Commercial Status	Commercialised
Accessory / separate part designation	5-wire connector adaptor
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector adaptor
Cable composition	5 x 1 mm²
Thread type	Pg 13.5
[In] rated current	6 A

### Complementary

Cable length	3.94 in (100 mm)	
Total number of wires	5	
Electrical connection	1 male connector 5 straight	
Cable connector fixing	Screw-on	
Body material	Metal	
Insulation resistance	> 1000000000 Ohm	
Resistance across terminals	<= 5000 mOhm	
[Ue] rated operational voltage	300 V DC 250 V AC	
Product weight	0.11 lb(US) (0.05 kg)	

### **Environment**

IP degree of protection	IP67
Ambient air temperature for operation	-13176 °F (-2580 °C)

### Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389110868760
Nbr. of units in pkg.	1
Package weight(Lbs)	0.09
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	GB

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 9830 - Schneider Electric declaration of conformity

## Contractual warranty

Period	18 months

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCE13M785M