



LOC E	DIST B	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	EBD0-0035-03	09FEB04	RS	FWK

NOTES:

- 1 SINGLE PACK IN ACCORDANCE WITH SPEC 107-3275
- 2 100 TRAY PACK IN ACCORDANCE WITH SPEC 107-3275
- 3 0.08μm Au PLATING OVER 1.27μm Ni PLATING
- 4 0.08μm Au PLATING OVER 1.27μm Ni PLATING OVER 0.76μm Cu PLATING
- 5 0.76μm Au PLATING OVER 1.27μm Ni PLATING OVER 0.76μm Cu PLATING
- 6 PASSIVATED (GOLD PLATED CABLE ENTRY)
- 7 FOR TECHNICAL DATA REFER TO YOUR LOCAL TYCO ELECTRONICS SALES OFFICE
- 8 ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED

RECOMMENDED
CABLE STRIPPING DIM'S



		1	1	-	-	-	-	BRASS	4	CAP	8
		-	-	1	1	-	-	STAINLESS STEEL	6	CAP	8
		-	-	-	-	1	1	STAINLESS STEEL	3	CAP	8
		1	1	-	-	-	-	BRASS	4	CHASSIS	7
		-	-	1	1	-	-	STAINLESS STEEL	6	CHASSIS	7
		-	-	-	-	1	1	STAINLESS STEEL	3	CHASSIS	7
		1	1	1	1	1	1	BRASS	5	CENTER CONTACT	6
		1	1	-	-	-	-	BRASS	4	BODY	5
		-	-	1	1	-	-	STAINLESS STEEL	6	BODY	5
		-	-	-	-	1	1	STAINLESS STEEL	3	BODY	5
		1	1	1	1	1	1	STAINLESS STEEL		CIRCLIP	4
		1	1	1	1	1	1	SILICON		GASKET	3
		1	1	1	1	1	1	PTFE		INSULATOR	2
		1	1	-	-	-	-	BRASS	4	SHELL	1
		-	-	1	1	-	-	STAINLESS STEEL	6	SHELL	1
		-	-	-	-	1	1	STAINLESS STEEL	3	SHELL	1
		3--1	3--0	2--1	2--0	1--1	1--0	MATERIAL		DESCRIPTION	ITEM
		2	1	2	1	2	1				
QUANTITY PER ASSY								PARTS LIST			

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL

SEE TABLE

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

FINISH -

DWN
R.SMITH
09FEB04

CHK
S.PARLOW
09FEB04

APVD
F.WHEELER-KING
09FEB04

PRODUCT SPEC
108-3460

APPLICATION SPEC
411-3276

WEIGHT
-

CUSTOMER DRAWING

tyco
Electronics

Tyco Electronics Corporation
Bideford, UK, EX39 4HE

NAME
SMA RIGHT ANGLE PLUG DIRECT SOLDER
CAPTIVE CONTACT
RG402/U

SIZE
A3

CAGE CODE
00779

DRAWING NO
C-1478905

RESTRICTED TO
-

SCALE
1:1

SHEET
1 OF 1

REV
A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1478905-0](#)