











RECOMMENDED BOARD LAYOUTS



KEYWAY LOCATIONS (REF-SEE TABLE)
(MATING LENGTH OF POST ON NEAR SIDE)
SCALE 8:1



6 OBSOLETE	4	A,C,E,H,K,M,Q,S,U,W,Y	11	3.855	3.744	24	25	6 7-87655-5
	4	A,C,E,G,J,L,N,Q,S,U,W,Y	12	3.699	3.588	23	24	6 7-87655-4
	4	A,D,G,K,N,R,U,X	8	3.543	3.432	22	23	6 7-87655-3
	4	A,C,E,G,J,L,N,Q,S,U,W	11	3.387	3.276	21	22	6 7-87655-2
	4	A,D,G,K,N,R,U	7	3.231	3.120	20	21	6 7-87655-1
	4	A,C,E,G,J,L,N,Q,S,U	10	3.075	2.964	19	20	6 7-87655-0
	4	B,D,F,J,L,N,Q,S	8	2.919	2.808	18	19	6 6-87655-9
	4	A,D,F,J,M,P,S	7	2.763	2.652	17	18	6 6-87655-8
	4	A,D,G,K,N,R	6	2.607	2.496	16	17	6 6-87655-7
	4	A,C,E,G,J,L,N,Q	8	2.451	2.340	15	16	6 6-87655-6
	4	A,D,G,K,N	5	2.295	2.184	14	15	6 6-87655-5
	4	A,C,E,G,J,L,N	7	2.139	2.028	13	14	6 6-87655-4
	4	A,D,J,M	4	1.983	1.872	12	13	6 6-87655-3
	4	A,C,E,G,J,L	6	1.827	1.716	11	12	6 6-87655-2
6 OBSOLETE	4	A,D,G,K	4	1.671	1.560	10	11	6 6-87655-1
	4	A,C,E,G,J	5	1.515	1.404	9	10	6 6-87655-0
	4	A,D,G	3	1.359	1.248	8	9	6 5-87655-9
	4	A,C,E,G	4	1.203	1.092	7	8	6 5-87655-8
	4	A,C,E	3	1.047	.936	6	7	6 5-87655-7
6 OBSOLETE	4	A,C,E	3	.891	.780	5	6	6 5-87655-6
	4	A,D	2	.735	.624	4	5	6 5-87655-5
	4	A,C	2	.579	.468	3	4	6 5-87655-4
6 OBSOLETE	4	A	1	.423	.312	2	3	6 5-87655-3
	4	A	1	.267	.156	1	2	6 5-87655-2
6 OBSOLETE	3	A,C,E,H,K,M,Q,S,U,W,Y	11	3.855	3.744	24	25	2-87655-5
	3	A,C,E,G,J,L,N,Q,S,U,W,Y	12	3.699	3.588	23	24	2-87655-4
	3	A,D,G,K,N,R,U,X	8	3.543	3.432	22	23	2-87655-3
	3	A,C,E,G,J,L,N,Q,S,U,W	11	3.387	3.276	21	22	2-87655-2
	3	A,D,G,K,N,R,U	7	3.231	3.120	20	21	2-87655-1
	3	A,C,E,G,J,L,N,Q,S,U	10	3.075	2.964	19	20	2-87655-0
	3	B,D,F,J,L,N,Q,S	8	2.919	2.808	18	19	1-87655-9
	3	A,D,F,J,M,P,S	7	2.763	2.652	17	18	1-87655-8
	3	A,D,G,K,N,R	6	2.607	2.496	16	17	1-87655-7
	3	A,C,E,G,J,L,N,Q	8	2.451	2.340	15	16	1-87655-6
	3	A,D,G,K,N	5	2.295	2.184	14	15	1-87655-5
	3	A,C,E,G,J,L,N	7	2.139	2.028	13	14	1-87655-4
	3	A,D,J,M	4	1.983	1.872	12	13	1-87655-3
	3	A,C,E,G,J,L	6	1.827	1.716	11	12	1-87655-2
6 OBSOLETE	3	A,D,G,K	4	1.671	1.560	10	11	1-87655-1
	3	A,C,E,G,J	5	1.515	1.404	9	10	1-87655-0
6 OBSOLETE	3	A,D,G	3	1.359	1.248	8	9	87655-9
6 OBSOLETE	3	A,C,E,G	4	1.203	1.092	7	8	87655-8
6 OBSOLETE	3	A,C,E	3	1.047	.936	6	7	87655-7
	3	A,C,E	3	.891	.780	5	6	87655-6
	3	A,D	2	.735	.624	4	5	87655-5
6 OBSOLETE	3	A,C	2	.579	.468	3	4	87655-4
	3	A	1	.423	.312	2	3	87655-3
	3	A	1	.267	.156	1	2	87655-2
FINISH		KEYWAY LOCATIONS	NO OF KEYWAY	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L A MAYER	14 JUL 87	 Tyco Electronics Corporation Harrisburg, Pa 17105-3608				
		CHK J SCHIEFFER	14 JUL 87					
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	HEADER ASSEMBLY, MOD 1, RIGHT ANGLE, SINGLE ROW, .156 CL			
INCHES	0 PLG ± - 1 PLG ± - 2 PLG ± - 3 PLG ± .005 4 PLG ± - ANGLES ± -		APVD J SCHIEFFER					14 JUL 87
	108-255016		PRODUCT SPEC					
	APPLICATION SPEC		—					
	—		—					
MATERIAL	FINISH	WEIGHT	—	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
HAVING FLAME RETARDANT THERMOPLASTIC, COLOR — BLACK POSTS — BRASS	SEE TABLE			A1	00779	 87655	—	
CUSTOMER DRAWING				SCALE	4:1	SHEET	1 of 1	
							REV M3	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[87655-7](#)