

Ferrule — FWK 750V: 5-60A

FWK 5-30A (20 x 127mm) 35-60A (25 x 146mm)

Specifications

Description: Ferrule style high speed fuses.

Dimensions: See Dimensions illustrations.

Ratings:

Volts: — 750Vac

— 750Vdc (Time constant = 10-15mS)

Amps: — 5-60A

IR: — 45kA RMS Sym.

Agency Information: CE



Features and Benefits

- Excellent cycling capability and DC performance
- Low arc voltage and low energy let-through (I^2t)
- Low watts loss in a compact size
- Used with finger-safe holders/blocks

Typical Applications

- DC common bus
- DC drives
- Power converters/rectifiers
- Reduced voltage starters

Catalog Numbers

Catalog Numbers	Size	Electrical Characteristics		
		Rated Current RMS-Amps	I^2t (A ² Sec)	
			Pre-arc	Clearing at 750Vdc
FWK-5A20F	20 x 127mm ($1\frac{1}{8}$ " x 5")	5	8.5	16
FWK-8A20F		8	50	100
FWK-10A20F		10	95	200
FWK-15A20F		15	100	240
FWK-20A20F		20	125	315
FWK-30A20F		30	400	1100
FWK-35A25F	25 x 146mm (1" x 5 $\frac{7}{8}$ ")	35	1300	4300
FWK-40A25F		40	1600	5300
FWK-50A25F		50	3100	12000
FWK-60A25F		60	5900	24000

Recommended fuseholders for 20x127, CH127-1, -2, -3

Recommended fuseclips for 20x127, 1A1837

Recommended fuseclips for 25x146, A3354705

Dimensions - mm (inches)

Fig. 1: 5-30A





Fig. 2: 35-60A




Data Sheet: 720039

Ferrule — FWK 750V: 5-60A

FWK 750V: 5-30A (20 x 127mm)
 35-60A (25 x 146mm)

Time-Current Curve



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Eaton:

[FWK-10A20F](#) [FWK-15A20F](#) [FWK-20A20F](#) [FWK-25A20F](#) [FWK-30A20F](#) [FWK-35A25F](#) [FWK-40A25F](#) [FWK-50A25F](#)
[FWK-5A20F](#) [FWK-60A25F](#) [FWK-8A20F](#) [FWL-20A20F](#) [FWL-20A20FI](#) [FWL-25A20F](#) [FWL-25A20FI](#) [FWL-30A20F](#)
[FWL-30A20FI](#)