




NOTE:

1 MATERIAL:HOUSING;THERMOPLASTICS
(UL 94V-0) BLACK
CONTACT:COPPER ALLOY

2 FINISH:CONTACT:Au AT CONTACT AREA
TIN AT TINE, OVER NI

3. THESE PRODUCTS WERE COATED BY
ANTI-FLUX MIGRATION AGENT.

4 OBSOLETE

注記:

1 材料:ハウジング;熱可塑性樹脂
(UL 94V-0) 色:黒
コンタクト:銅合金

2 表面仕上げ;
コンタクト:全面ニッケル下地めっき
接触部金めっき、脚部すずめっき

3. 本製品はフラックス上がり防止処理済み

SECT "A"- "A"

0.76μm	120	19	24.13	39	49.53	77.47	26.13	51.53	79.47	82.55	90.09	2	5
	100	19	24.13	39	49.53	62.23	26.13	51.53	64.23	67.32	74.85	2	4
0.3μm	180	38	49.53	49	62.23	115.57	51.53	64.23	117.57	120.66	128.19	8	8
	160	29	36.83	49	62.23	102.87	38.83	64.23	104.87	107.96	115.49	7	7
	140	29	36.83	39	49.53	90.17	38.83	51.53	92.17	95.26	102.79	6	6
	120	19	24.13	39	49.53	77.47	26.13	51.53	79.47	82.55	90.09	5	5
	100	19	24.13	39	49.53	62.23	26.13	51.53	64.23	67.32	74.85	4	4
	80	19	24.13	39	49.53	49.53	26.13	51.53	54.62	57.71	62.15	3	3
	60	19	24.13	29	36.83	38.83	26.13	51.53	41.92	45.01	49.45	2	2
	40	19	24.13	19	24.13	26.13	26.13	51.53	29.22	32.31	36.75	1	1
5917630-1													
GOLD PLATING													
Pos. a A b B c C D E F G H P/N													

REVISED PER ECR-12-013341				28MAR2013	K.M.E.T
RELEASED (FJBO-0682-04)				09JUN04	T.K.I.E
DESCRIPTION				DATE	DWN APVD

WIRE RANGE	INSULATION DIA	NAME
mm ² (AWG -)	mmφ	AMP FH CONNECTOR RECEPTACLE (VERTICAL) FOR 10mm STAKING
MATERIAL	FINISH	GENERAL TOLERANCE
DE. T.KAWAMAE	DE. T.KAWAMAE	0<mm 10 : ±0.2 10<mm 30 : ±0.25 30<mm 100 : ±0.3 ANGLES : ±3°
CHK. I.ENOMOTO	APP. I.ENOMOTO	SIZE B J
		LOC NTS
		NUMBER C-5917630
		REV. A
		SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5917630-5](#)