


6	101.19	99.06 [3.900]	39	40	9-146466-0	
6	98.65	96.52 [3.800]	38	39	8-146466-9	
6	96.11 [3.784]	93.98 [3.700]	37	38	8-146466-8	
	93.57 [3.684]	91.44	36	37	8-146466-7	
	91.03 [3.584]	88.90 [3.500]	35	36	8-146466-6	
	<u> </u>	86.36 [3.400]	34	35	8-146466-5	
	85.95 [3.384]	83.82 [3.300]	33	34	8-146466-4	
	<u>[3.284]</u> 83.41 [3.284]	81.28 [3.200]	32	33	8-146466-3	
	80.87 [3.184]	78.74	31	32	8-146466-2	
	78.33	[3.100] 76.20	30	31	8-146466-1	
	[3.084]	[3.000] 73.66	29	30	8-146466-0	
	[2.984]	[2.900] 71.12	28	29	7-146466-9	
$\wedge$	[2.884]	[2.800] _68.58	20	23	7-146466-8	
	[2.784] 68.17	[2.700] 66.04	26	27	7-146466-7	
<u>6</u>	[2.684] 65.63	[2.600] 63.50				
	[2.584] 63.09	[2.500] 60.96	25	26	7-146466-6	
	[2.484]	[2.400] 58.42	24	25	7-146466-5	
	[2.384]	[2.300] 55.88	23	24	7-146466-4	
	[2.284]	[2.200] 53.34	22	23	7-146466-3	
	[2.184]	[2.100]	21	22	7-146466-2	
	[2.084]	[2.000]	20	21	7-146466-1	
6	50.39 [1.984]	48.26 [1.900]	19	20	7-146466-0	
6	47.85 [1.884]	45.72 [1.800]	18	19	6-146466-9	
6	45.31 [1.784]	43.18 [1.700]	17	18	6-146466-8	
6	42.77 [1.684]	40.64 [1.600]	16	17	6-146466-7	
6	40.23 [1.584]	38.10 [1.500]	15	16	6-146466-6	
6	37.69 [1.484]	35.56 [1.400]	14	15	6-146466-5	5
6	35.15 [1.384]	33.02 [1.300]	13	14	6-146466-4	
6	32.61 [1.284]	30.48 [1.200]	12	13	6-146466-3	
6	<u> </u>	27.94 [1.100]	1 1	12	6-146466-2	
6	27.53	25.40 [1.000]	10	1 1	6-146466-1	
6	24.99	22.86 [.900]	9	10	6-146466-0	
	22.45	20.32	8	9	5-146466-9	
	19.91 [.784]	17.78 [.700]	7	8	5-146466-8	
	17.37	15.24 [.600]	6	7	5-146466-7	
	<u>[.084]</u> 14.83 [.584]	[.600] 12.70 [.500]	5	6	5-146466-6	
	12.29	10.16	4	5	5-146466-5	
	[.484] 9.75	[.400] 7.62	3	4	5-146466-4	
$\wedge$	[.384]	[.300] 5.08	2	3	5-146466-3	
	[.284]	[.200] 2.54	1	2	5-146466-2	
	[.184]	[.100]	I	∠ 1	5-146466-1	
	[.084]			NO. OF		
PLATING	G			POSITIONS	PART NUMBER	THIS DRAWING IS A CON





\_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_ 

DIMENSIONS: mm [INCHES]

1ATERIAL

Λ	101.19	99.06			1
	[3.984] 98.65	[3.900] 96.52	39	40	4-146466-0
	[3.884] 96.11	[3.800] 93.98	38	39	3-146466-9
	[3.784] 93.57	[3.700] 91.44	37	38	3-146466-8
	[3.684] 91.03	[3.600] 88.90	36	37	3-146466-7
	[3.584] 88.49	[3.500] 86.36	35	36	3-146466-6
	[3.484] [3.95	[3.400] 83.82	34	35	3-146466-5
	[3.384] 83.41	[3.300]	33	34	3-146466-4
	[3.284]	81.28 [3.200]	32	33	3-146466-3
5	80.87 [3.184]	78.74 [3.100]	31	32	3-146466-2
5	78.33 [3.084]	76.20 [3.000]	30	31	3-146466-1
5	75.79 [2.984]	73.66 [2.900]	29	30	3-146466-0
	73.25 [2.884]	71.12 [2.800]	28	29	2-146466-9
	70.71 [2.784]	68.58 [2.700]	27	28	2-146466-8
$\sqrt{5}$	68.17 [2.684]	66.04 [2.600]	26	27	2-146466-7
5	65.63 [2.584]	63.50 [2.500]	25	26	2-146466-6
5	63.09 [2.484]	60.96 [2.400]	24	25	2-146466-5
5	60.55 [2.384]	58.42 [2.300]	23	24	2-146466-4
5	58.01 [2.284]	55.88 [2.200]	22	23	2-146466-3
<u>_5</u>		53.34 [2.100]	21	22	2-146466-2
5	52.93 [2.084]	50.80 [2.000]	20	21	2-146466-1
 	50.39 [1.984]	48.26 [1.900]	19	20	2-146466-0
<u></u>	47.85 [1.884]	45.72 [1.800]	18	19	1-146466-9
<u></u>	45.31 [1.784]	43.18	17	18	1-146466-8
	42.77 [1.684]	40.64	16	17	1-146466-7
	40.23	38.10 [1.500]	15	16	1-146466-6
		35.56 [1.400]	14	15	1-146466-5
	35.15 [1.384]	33.02 [1.300]	13	14	1-146466-4
	32.61 [1.284]		12	13	1-146466-3
	30.07 [1.184]	27.94 [1.100]	1 1	12	1-146466-2
	27.53 [1.084]	25.40 [1.000]	1 0	1 1	1-146466-1
	24.99	22.86	9	10	1-146466-0
25	[.984] 22.45 [ 884]	[.900] 20.32 [800]	8	9	146466-9
<u></u>	[.884] 19.91 [.784]	[.800] 17.78 [.700]	7	8	146466-8
	[.784]	[.700] 15.24 [.600]	6	7	146466-7
<u></u>	[.684] 14.83 [.584]	[.600] 12.70 [.500]	5	6	146466-6
25	[.584] 12.29 [484]	[.500] 10.16 [.400]	4	5	146466-5
<u>/5</u>	[.484] 9.75	[.400] 7.62	3	4	146466-4
	[.384] 7.21	[.300] 5.08	2	3	146466-3
$\land$	[.284] 4.67	[.200] 2.54 [.100]	1	2	146466-2
<u></u>	[.184] 2.13	[.100]		1	146466-1
25) Plating	[.084] G			NO. OF	PART NUMBER
/ING IS A CONTROLLED [	DWN	HOFFMAN	18JAN96	POSITIONS	
	СНК	. DUBNICZKI	4MAR96 4MAR96 NAME	-ETE	TE Connectivity
NCHES]	_ G	) . DUBNICZKI DUCT SPEC	4MAR96 NAME		EMBLY, MOD II, SINGLE ROW,
	$\bigcirc \square \square$				
1 PLC ± 2 PLC ± 3 PLC ±	0.51[.02]	LICATION SPEC	SIZE	.025 SQ.POS	T, UNSHROUDED

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 9-146466-0