

			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>01</td><td>RELEASED</td><td>KYLE 10-6-97</td><td>PCW 10/7/97</td></tr><tr><td>B</td><td>REVISED PER ECN 0020-0262-01</td><td>GV 1/6/03</td><td>JGH</td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	01	RELEASED	KYLE 10-6-97	PCW 10/7/97	B	REVISED PER ECN 0020-0262-01	GV 1/6/03	JGH																																																																			
			REVISIONS																																																																																						
			REV	DESCRIPTION	DATE	APPROVED																																																																																			
01	RELEASED	KYLE 10-6-97	PCW 10/7/97																																																																																						
B	REVISED PER ECN 0020-0262-01	GV 1/6/03	JGH																																																																																						
RECOMMENDED MOUNTING HOLE																																																																																									
<table><tr><th colspan="2">ELECTRICAL</th></tr><tr><td>Nominal Impedance (Ohms)</td><td>50</td></tr><tr><td>Frequency Range (GHz) DC to</td><td>22</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level</td><td>335</td></tr><tr><td>VSWR</td><td>TBD</td></tr><tr><td>Insertion Loss (dB MAX)</td><td>TBD</td></tr><tr><td>RF Leakage (dB MIN) (Interface Only, Fully Mated)</td><td>-(90-f(GHz))</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN)</td><td>250</td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level</td><td>1000</td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td></td></tr><tr><td>Center Contact</td><td>4.0</td></tr><tr><td>Outer Contact</td><td>2.0</td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz)</td><td>670</td></tr><tr><td>I.R.(Megohms MIN)</td><td>5000</td></tr></table>		ELECTRICAL		Nominal Impedance (Ohms)	50	Frequency Range (GHz) DC to	22	Volt Rating (VRMS MAX) @ Sea Level	335	VSWR	TBD	Insertion Loss (dB MAX)	TBD	RF Leakage (dB MIN) (Interface Only, Fully Mated)	-(90-f(GHz))	Corona, 70,000 Ft (VRMS MIN)	250	Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level	1000	Contact Resistance (Milliohms MAX)		Center Contact	4.0	Outer Contact	2.0	RF High Potential @ Sea Level (VRMS MIN @ 5 MHz)	670	I.R.(Megohms MIN)	5000	<table><tr><th colspan="2">MECHANICAL</th></tr><tr><td colspan="2">Interface Dimensions (DSP End Only)</td></tr><tr><td colspan="2">MIL-STD-348, Fig 321-1</td></tr><tr><td>Force to Engage</td><td></td></tr><tr><td>3.5mm (In-Lbs MAX)</td><td>2</td></tr><tr><td>DSP (Lbs MAX)</td><td>3</td></tr><tr><td>Force to Disengage</td><td></td></tr><tr><td>3.5mm (In-Lbs MAX)</td><td>2</td></tr><tr><td>DSP (Lbs MAX)</td><td>1.5</td></tr><tr><td>Center Contact Captivation</td><td></td></tr><tr><td>Axial (Lbs)</td><td>6</td></tr><tr><td>Mating Characteristics (3.5mm Only)</td><td></td></tr><tr><td>Insertion (Lbs MAX)</td><td>3</td></tr><tr><td>Withdrawal (Oz MIN)</td><td>1</td></tr></table>		MECHANICAL		Interface Dimensions (DSP End Only)		MIL-STD-348, Fig 321-1		Force to Engage		3.5mm (In-Lbs MAX)	2	DSP (Lbs MAX)	3	Force to Disengage		3.5mm (In-Lbs MAX)	2	DSP (Lbs MAX)	1.5	Center Contact Captivation		Axial (Lbs)	6	Mating Characteristics (3.5mm Only)		Insertion (Lbs MAX)	3	Withdrawal (Oz MIN)	1	<table><tr><th colspan="2">ENVIRONMENTAL</th></tr><tr><td colspan="2">TEMPERATURE RATING -65° TO +125°C</td></tr><tr><td colspan="2">Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td colspan="2">Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td colspan="2">Thermal Shock MIL-STD-202, Method 107, Condition B</td></tr><tr><td colspan="2">Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td colspan="2">Corrosion - MIL-STD-202, Method 101, Condition B</td></tr></table>		ENVIRONMENTAL		TEMPERATURE RATING -65° TO +125°C		Vibration MIL-STD-202, Method 204, Condition D		Shock MIL-STD-202, Method 213, Condition I		Thermal Shock MIL-STD-202, Method 107, Condition B		Moisture Resistance MIL-STD-202, Method 106		Corrosion - MIL-STD-202, Method 101, Condition B		<table><tr><td>HOUSING MOUNTING NUT LOCKWASHER</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>PTFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>O-RING</td><td>FLOUROSILICONE PER MIL-R-25988, CLASS I, TYPE I.</td><td>N/A</td></tr></table>		HOUSING MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	O-RING	FLOUROSILICONE PER MIL-R-25988, CLASS I, TYPE I.	N/A
ELECTRICAL																																																																																									
Nominal Impedance (Ohms)	50																																																																																								
Frequency Range (GHz) DC to	22																																																																																								
Volt Rating (VRMS MAX) @ Sea Level	335																																																																																								
VSWR	TBD																																																																																								
Insertion Loss (dB MAX)	TBD																																																																																								
RF Leakage (dB MIN) (Interface Only, Fully Mated)	-(90-f(GHz))																																																																																								
Corona, 70,000 Ft (VRMS MIN)	250																																																																																								
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level	1000																																																																																								
Contact Resistance (Milliohms MAX)																																																																																									
Center Contact	4.0																																																																																								
Outer Contact	2.0																																																																																								
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz)	670																																																																																								
I.R.(Megohms MIN)	5000																																																																																								
MECHANICAL																																																																																									
Interface Dimensions (DSP End Only)																																																																																									
MIL-STD-348, Fig 321-1																																																																																									
Force to Engage																																																																																									
3.5mm (In-Lbs MAX)	2																																																																																								
DSP (Lbs MAX)	3																																																																																								
Force to Disengage																																																																																									
3.5mm (In-Lbs MAX)	2																																																																																								
DSP (Lbs MAX)	1.5																																																																																								
Center Contact Captivation																																																																																									
Axial (Lbs)	6																																																																																								
Mating Characteristics (3.5mm Only)																																																																																									
Insertion (Lbs MAX)	3																																																																																								
Withdrawal (Oz MIN)	1																																																																																								
ENVIRONMENTAL																																																																																									
TEMPERATURE RATING -65° TO +125°C																																																																																									
Vibration MIL-STD-202, Method 204, Condition D																																																																																									
Shock MIL-STD-202, Method 213, Condition I																																																																																									
Thermal Shock MIL-STD-202, Method 107, Condition B																																																																																									
Moisture Resistance MIL-STD-202, Method 106																																																																																									
Corrosion - MIL-STD-202, Method 101, Condition B																																																																																									
HOUSING MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																																																							
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																																							
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																																							
O-RING	FLOUROSILICONE PER MIL-R-25988, CLASS I, TYPE I.	N/A																																																																																							
<table><tr><th colspan="2">COMPONENT</th></tr><tr><td colspan="2">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td></tr><tr><td>FRAC.</td><td>DEC.</td></tr><tr><td>± 1/64</td><td>± .005</td></tr><tr><td>ANGLES</td><td>± 1°</td></tr></table>		COMPONENT		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		FRAC.	DEC.	± 1/64	± .005	ANGLES	± 1°	<table><tr><td colspan="2">DRAWN BY: J. Amato</td><td colspan="2">DATE: 7/22/97</td></tr><tr><td colspan="2">CHECKED BY:</td><td colspan="2"></td></tr><tr><td colspan="2">APPROVED BY:</td><td colspan="2"></td></tr></table>		DRAWN BY: J. Amato		DATE: 7/22/97		CHECKED BY:				APPROVED BY:				<table><tr><td colspan="2">AMP Incorporated</td></tr><tr><td colspan="2">140 Fourth Avenue</td></tr><tr><td colspan="2">Waltham, MA 02451-7599</td></tr></table>		AMP Incorporated		140 Fourth Avenue		Waltham, MA 02451-7599																																																									
COMPONENT																																																																																									
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES																																																																																									
FRAC.	DEC.																																																																																								
± 1/64	± .005																																																																																								
ANGLES	± 1°																																																																																								
DRAWN BY: J. Amato		DATE: 7/22/97																																																																																							
CHECKED BY:																																																																																									
APPROVED BY:																																																																																									
AMP Incorporated																																																																																									
140 Fourth Avenue																																																																																									
Waltham, MA 02451-7599																																																																																									
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		USE ASS'Y PROCEDURE		<table><tr><td colspan="2">TITLE</td></tr><tr><td colspan="2">DSP BULKHEAD FEEDTHRU PLUG TO 3.5MM JACK ADAPTER</td></tr><tr><td>SIZE</td><td>CODE IDENT NO.</td></tr><tr><td>B</td><td>26805</td></tr><tr><td>SCALE</td><td>4:1</td></tr></table>		TITLE		DSP BULKHEAD FEEDTHRU PLUG TO 3.5MM JACK ADAPTER		SIZE	CODE IDENT NO.	B	26805	SCALE	4:1																																																																										
TITLE																																																																																									
DSP BULKHEAD FEEDTHRU PLUG TO 3.5MM JACK ADAPTER																																																																																									
SIZE	CODE IDENT NO.																																																																																								
B	26805																																																																																								
SCALE	4:1																																																																																								
NO. AP. N/A		<table><tr><td colspan="2">4585-2352-02</td><td>REV</td></tr><tr><td colspan="2"></td><td>01</td></tr></table>		4585-2352-02		REV			01	SHEET 1 OF 1																																																																															
4585-2352-02		REV																																																																																							
		01																																																																																							

CUSTOMER DRAWING

AMP PART # 1251381-1
SHEET 1 OF 1 REV B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1251381-1](#)