

SUPDM56HW - UPS Accessory - Hardwire PDU Module

MODEL NUMBER: **SUPDM56HW**



Description

The SUPDM56HW hardwire input/output PDU module converts compatible SmartOnline Hot-Swappable Modular UPS Systems (models [SU5000RT4U](#) and [SU6000RT4U](#)) to a totally hardwired solution. Easy quick-connect terminal block allows installation of hardwire distribution module in minutes. Can accept input voltages of 120/208 or 120/240 VAC split-phase power. Detachable hardwire module allows for effortless UPS maintenance without the need to power down connected loads and re-wire input/output connections.

Features

- The SUPDM56HW hardwire input/output PDU module converts compatible SmartOnline Hot-Swappable Modular UPS Systems (models [SU5000RT4U](#) and [SU6000RT4U](#)) to a totally hardwired solution
- Easy quick-connect terminal block allows installation of hardwire distribution module in minutes
- Can accept input voltages of 120/208 or 120/240 VAC split-phase power
- Detachable hardwire module allows for effortless UPS maintenance without the need to power down connected loads and re-wire input/output connections

Specifications

OVERVIEW	
Accessories Type	PDU Module
OUTPUT	

Highlights

- Converts compatible SmartOnline Hot-Swappable Modular UPS systems to hardwire input and output
- For use with input voltages of 120/208 or 120/240 VAC split-phase power
- Convenient quick-disconnect terminal block allows installation in minutes

System Requirements

- Use with SU5000RT4U and SU6000RT4U split-phase SmartOnline Hot-Swappable Modular UPS Systems

Package Includes

- SUPDM56HW hardwire PDU
- Mounting Hardware
- Owner's Manual



Frequency Compatibility	50 / 60 Hz
Output Receptacles	Hardwire
Output Nominal Voltage	120/208, 120/240
INPUT	
Nominal Input Voltage(s) Supported	100V AC; 110V AC; 115V AC; 120V AC; 127V AC; 140V AC
Input Connection Type	Split-phase hardwire (4-wire)
Voltage Compatibility (VAC)	100-140
PHYSICAL	
Shipping Dimensions (hwd / in.)	5.75 x 12 x 10
Shipping Dimensions (hwd / cm)	14.6 x 30.5 x 25.4
Shipping Weight (lbs.)	4
Shipping Weight (kg)	1.8
Unit Dimensions (hwd / in.)	6 x 8.25 x 3.25
Unit Dimensions (hwd / cm)	15.24 x 21 x 8.3
Unit Weight (lbs.)	2.75
Unit Weight (kg)	1.24
Material of Construction	Steel
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), CSA (Canada), RoHS compliant
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[SUPDM56HW](#)