

Touch panel - WP 04T - 2913632

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 8.9 cm (3.5") graphics-capable TFT display, 320 x 240 pixels, 1 x Ethernet, 2 x USB, and integrated micro browser

Product Features

- Short startup time
- Easy installation, low installation depth, and compact design
- Low maintenance costs - projects are only adapted once
- Micro browser (WebVisit client) integrated as standard in all devices
- Display available in sizes from 8.9 cm (3.5") to 38.1 cm (15")
- Easy device replacement - the visualization project is saved on the PLC (web server)
- Energy efficient due to LED backlighting

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	520.0 g
Custom tariff number	84714100
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

External dimension, width	120 mm
External dimension, height	90 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	112 mm
Installation dimension, height	82 mm
Installation dimension, depth	35 mm

Touch panel - WP 04T - 2913632

Technical data

Display

Display	8,9 cm / 3,5"-TFT
Screen resolution	320 x 240 Pixel(s) (QVGA)
Backlighting	LED
Display backlight MTBF	40000 h
Touch technology	Analog resistive
Colors	65536 colors

Computer data

Processor	ARM9™, 200 MHz
Operating systems	Windows® CE 5.0
User software	MicroBrowser
RAM	64 MB SDRAM
Mass storage	32 MByte flash memory
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB Host 2.0
Bus system	without

General

Mounting type	Front installation
---------------	--------------------

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Device supply

Power supply unit	24 V DC ±20 %
-------------------	---------------

Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Classifications

eCl@ss

eCl@ss 5.1	27242302
------------	----------

Touch panel - WP 04T - 2913632

Classifications

eCl@ss

eCl@ss 6.0	27242302
eCl@ss 8.0	27242302
eCl@ss 9.0	27330201

ETIM

ETIM 2.0	EC001412
ETIM 3.0	EC001412
ETIM 4.0	EC001412
ETIM 5.0	EC001412

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43211903
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

GL / GL-SW / UL Listed / cUL Listed / DNV / EAC / LR / ABS / RINA / BV / GL / cULus Listed

Ex Approvals

Approvals submitted

Approval details

GL

GL-SW

Touch panel - WP 04T - 2913632

Approvals

UL Listed 

cUL Listed 

DNV

EAC

LR

ABS

RINA

BV

GL

cULus Listed 

Accessories

Accessories

Mounting material

Mounting material - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

Touch panel - WP 04T - 2913632

Accessories

Mounting material - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

Mounting material - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

Operating stylus

Touch pen - TOUCH PEN - 2701379



Touch pen for HMIs, silver coated. Delivery includes self-adhesive pen holder.

PCB plug

Printed-circuit board connector - MC 1,5/ 3-STF-3,5 - 1847068



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 3, Pitch: 3.5 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin

Storage medium

Touch panel - WP 04T - 2913632

Accessories

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2913632](#)