

- NOTES:
- 1.0 SPECIFICATIONS.
- 1.1 FREQUENCY RANGE: SEE TABLE
- 1.2 IMPEDANCE: 50 OHMS NOMINAL
- 1.3 VSWR MAX.:

DC to 2.0 GHz 1.10:1
2.0 to 4.0 GHz 1.15:1
4.0 to 8.0 GHz: 1.20:1
8.0 to 12.4 GHz: 1.25:1
12.4 to 18.0 GHz: 1.35:1

- 1.4 ATTENUATION & ACCURACY: SEE TABLE

- 1.5 MAXIMUM INPUT POWER

1.5.1 2 WATTS AVG. AT +25°C DERATED LINEARLY
TO 0.5 WATTS AT +125°C

1.5.2 500 WATTS PEAK

- 1.6 OPERATING TEMP. RANGE:
-55°C to +125°C

- 1.7 WEIGHT: 0.45 Oz. MAX.

- 2.0 MARKING.

- 2.1 ENGRAVE SERIAL NO. AND DATE CODE
ON NUT AS SHOWN.

- 2.2 MARK BODY AS SHOWN.

(REF: INK-09119-27-XX) FOR NON-SCREENED.
(REF: INK-09120-27-XX) FOR SCREENED.

- 3.0 TESTING:

TEST IN CONJUNCTION WITH:

ATP-07839-60-01 FOR SCREENED UNITS.

ATP-09210-60-01 FOR NON-SCREENED UNITS.

- 4.0 BAG MARKING:

MODEL M3933/25-YYY

ATTENUATOR FIXED COAXIAL LINE

2 WATTS AVERAGE INPUT POWER

FREQ. RANGE: DC-XX GHz

MFR 34078

LOT NO. _____

DATE CODE: YYWW

YEAR & WEEK

SEE MODEL NO.
FOR LAST 3 DIGITS

SEE TABLE ON SHT. 2

*SILVER EPOXY CAPTURE HOLES
PER EPX-08003-44-01
(2 PLCS)

SMA FEMALE CONN.
PER MIL-PRF-39012

MALE CONN. CONN.
PER MIL-PRF-39012

ENGRAVE NUT
PER NOTE 2.1

EPOXY SEAL SEAM PER
EPX-08000-44-01

.317 MAX. OVER
FLATS

DIM A MAX.

±.02
.28 DIA

CLASS IV
P.N. M39
DC to XX

*N/A ON UNITS .94 O.A.L.

DATE	7/14/92	10/8/93	2/4/94	4/8/94	1/16/95	12/12/02	2/25/03	3/19/04	3/10/06
DESCRIPTION	RELEASED	13000	ECN 13307	ECN 13483	ECN 14231	ECN 18866	ECN 19058	ECN 19711	ECN 20764
REV.	-	A	B	C	D	E	F	G	H

UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 3 PLACE DECIMALS ±.005 2 PLACE DECIMALS ±.02 FRACTIONS ±1/64 PARALLELITY: T.I.R. _____ FLATNESS: T.I.R. _____ CONCENTRICITY: T.I.R. _____ ANGLES AND PERPENDICULARITY: ±1°	FSCM NO.		34078		MIDWEST MICROWAVE			
	NOTICE: The information contained in this drawing is proprietary and must not be used without the permission of Midwest Microwave				TITLE ATTENUATOR			
	DRAWN/DATE M.HOLLMAN 7/3/92		ENG./DATE G.KOZAK 7/14/92		DRAWING NUMBER M3933/25-XX(N or S)			
CHECKED/DATE G.KOZAK 7/14/92		APPROVED/DATE		SCALE: 5=1		SHEET 1 of 2		

DASH NO.	ATTENUATION dB				DIM A INCHES (MM) MAX.
	NOMINAL	DEVIATION (±)			
		DC to 2.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz	
01 N/S	1	0.3			0.87 (22.10)
02 N/S	2	0.3			0.87 (22.10)
03 N/S	3	0.3			0.87 (22.10)
04 N/S	4	0.3			0.87 (22.10)
05 N/S	5	0.3			0.87 (22.10)
06 N/S	6	0.3			0.87 (22.10)
07 N/S	7	0.3			0.87 (22.10)
08 N/S	8	0.3			0.87 (22.10)
09 N/S	9	0.3			0.87 (22.10)
10 N/S	10	0.3			0.87 (22.10)
11 N/S	11	0.3			0.87 (22.10)
12 N/S	12	0.3			0.87 (22.10)
13 N/S	13	0.3			1.03 (26.16)
14 N/S	14	0.3			1.03 (26.16)
15 N/S	15	0.3			1.03 (26.16)
16 N/S	16	0.3			1.03 (26.16)
17 N/S	17	0.3			1.03 (26.16)
18 N/S	18	0.3			1.03 (26.16)
19 N/S	19	0.3			1.03 (26.16)
20 N/S	20	0.3			1.03 (26.16)
21 N/S	21	0.5			1.03 (26.16)
22 N/S	22	0.5			1.03 (26.16)
23 N/S	23	0.5			1.03 (26.16)
24 N/S	24	0.5			1.03 (26.16)
25 N/S	25	0.5			1.03 (26.16)
26 N/S	30	0.5			1.03 (26.16)
27 N/S	1		0.3		0.87 (22.10)
28 N/S	2		0.3		0.87 (22.10)
29 N/S	3		0.3		0.87 (22.10)
30 N/S	4		0.3		0.87 (22.10)
31 N/S	5		0.3		0.87 (22.10)
32 N/S	6		0.3		0.87 (22.10)

DASH NO.	ATTENUATION dB				DIM A INCHES (MM) MAX.
	NOMINAL	DEVIATION (±)			
		DC to 2.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz	
33 N/S	7		0.4		0.87 (22.10)
34 N/S	8		0.4		0.87 (22.10)
35 N/S	9		0.4		0.87 (22.10)
36 N/S	10		0.4		0.87 (22.10)
37 N/S	11		0.4		0.87 (22.10)
38 N/S	12		0.4		0.87 (22.10)
39 N/S	13		0.4		0.94 (23.88)
40 N/S	14		0.4		0.94 (23.88)
41 N/S	15		0.4		0.94 (23.88)
42 N/S	16		0.4		0.94 (23.88)
43 N/S	17		0.4		0.94 (23.88)
44 N/S	18		0.4		0.94 (23.88)
45 N/S	19		0.4		0.94 (23.88)
46 N/S	20		0.7		1.04 (26.42)
47 N/S	21		0.7		1.04 (26.42)
48 N/S	22		0.7		1.04 (26.42)
49 N/S	23		0.7		1.04 (26.42)
50 N/S	24		0.7		1.04 (26.42)
51 N/S	25		0.7		1.04 (26.42)
52 N/S	30		1.0		1.04 (26.42)
53 N/S	35		1.0		1.35 (34.29)
54 N/S	40		1.0		1.35 (34.29)
55 N/S	45		1.5		1.35 (34.29)
56 N/S	50		2.0		1.35 (34.29)
57 N/S	60		2.0		1.35 (34.29)
58 N/S	0			0.3	0.87 (22.10)
59 N/S	0.5			0.3	0.87 (22.10)
60 N/S	1.0			0.3	0.87 (22.10)
61 N/S	1.5			0.3	0.87 (22.10)
62 N/S	2.0			0.3	0.87 (22.10)
63 N/S	2.5			0.3	0.87 (22.10)
64 N/S	3.0			0.3	0.87 (22.10)

DASH NO.	ATTENUATION dB				DIM A INCHES (MM) MAX.
	NOMINAL	DEVIATION (±)			
		DC to 2.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz	
65 N/S	3.5			0.3	0.87 (22.10)
66 N/S	4.0			0.3	0.87 (22.10)
67 N/S	4.5			0.3	0.87 (22.10)
68 N/S	5.0			0.3	0.87 (22.10)
69 N/S	5.5			0.3	0.87 (22.10)
70 N/S	6.0			0.3	0.87 (22.10)
71 N/S	6.5			0.3	0.87 (22.10)
72 N/S	7.0			0.4	0.87 (22.10)
73 N/S	7.5			0.4	0.87 (22.10)
74 N/S	8.0			0.4	0.87 (22.10)
75 N/S	8.5			0.4	0.87 (22.10)
76 N/S	9.0			0.5	0.87 (22.10)
77 N/S	9.5			0.5	0.87 (22.10)
78 N/S	10.0			0.5	0.87 (22.10)
79 N/S	11.0			0.5	0.87 (22.10)
80 N/S	12.0			0.5	0.87 (22.10)
81 N/S	13.0			0.5	0.94 (23.88)
82 N/S	14.0			0.5	0.94 (23.88)
83 N/S	15.0			0.6	1.04 (26.42)
84 N/S	16.0			0.6	1.04 (26.42)
85 N/S	17.0			0.6	1.04 (26.42)
86 N/S	18.0			0.6	1.04 (26.42)
87 N/S	19.0			0.6	1.04 (26.42)
88 N/S	20.0			0.6	1.04 (26.42)
89 N/S	25.0			1.0	1.04 (26.42)
90 N/S	30.0			1.0	1.04 (26.42)
91 N/S	35.0			1.0	1.35 (34.29)
92 N/S	40.0			1.0	1.35 (34.29)
93 N/S	45.0			1.0	1.35 (34.29)
94 N/S	50.0			2.0	1.35 (34.29)
95 N/S	60.0			2.0	1.35 (34.29)

REV.	DESCRIPTION	DATE
-	RELEASED	7/14/92

UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:

3 PLACE DECIMALS ±.005

2 PLACE DECIMALS ±.02

FRACTIONS ±1/64

PARALLELITY: T.I.R. _____

FLATNESS: T.I.R. _____

CONCENTRICITY: T.I.R. _____

ANGLES AND PERPENDICULARITY: ±1°

FSCM NO.

34078

NOTICE: The information contained in this drawing is proprietary and must not be used without the permission of Midwest Microwave

DRAWN/DATE
M.HOLLMAN
7/3/92

CHECKED/DATE
G.KOZAK
7/14/92

ENG./DATE
G.KOZAK
7/14/92

APPROVED/DATE

TITLE

ATTENUATOR

DRAWING NUMBER

M3933/25-XX(N or S)

SCALE:

1=1

SHEET

2

of

2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions:

M3933/25-28S	M3933/25-46S	M3933/25-64S	M3933/25-59S	M3933/25-33S	M3933/25-36S	M3933/25-51S
M3933/25-23S	M3933/25-13S	M3933/25-08S	M3933/25-89S	M3933/25-03S	M3933/25-18S	M3933/25-31S
M3933/25-41S	M3933/25-69S	M3933/25-43S	M3933/25-84S	M3933/25-79S	M3933/25-38S	M3933/25-26S
M3933/25-11S	M3933/25-82S	M3933/25-06S	M3933/25-72S	M3933/25-29S	M3933/25-14S	M3933/25-85S
M3933/25-67S	M3933/25-09S	M3933/25-90S	M3933/25-74S	M3933/25-01S	M3933/25-16S	M3933/25-21S
M3933/25-24S	M3933/25-39S	M3933/25-62S	M3933/25-87S	M3933/25-77S	M3933/25-92S	M3933/25-34S
M3933/25-54S	M3933/25-52S	M3933/25-70S	M3933/25-02S	M3933/25-88S	M3933/25-27S	M3933/25-63S
M3933/25-20S	M3933/25-86S	M3933/25-91S	M3933/25-76S	M3933/25-44S	M3933/25-37S	M3933/25-65S
M3933/25-75S	M3933/25-73S	M3933/25-22S	M3933/25-71S	M3933/25-25S	M3933/25-30S	M3933/25-45S
M3933/25-61S	M3933/25-47S	M3933/25-42S	M3933/25-12S	M3933/25-32S	M3933/25-07S	M3933/25-17S
M3933/25-49S	M3933/25-19S	M3933/25-60S	M3933/25-04S	M3933/25-80S	M3933/25-83S	M3933/25-68S
M3933/25-35S	M3933/25-05S	M3933/25-15S	M3933/25-58S	M3933/25-50S	M3933/25-10S	M3933/25-48S
M3933/25-81S	M3933/25-78S	M3933/25-40S	M3933/25-53S	M3933/25-66S		