

D

С

В

А

Pro/ENGINEER DRAWING



			1			
DIST		•	REVISIONS			
-	Р	LTR	DESCRIPTION	DATE	DWN	APVD
		A2	REVISED PER ECR-II-014651	20JUL2011	RK	DD
		АЗ	REVISED PER ECR-II-016987	5SEP2011	RS	DD

COPPER ALLOY, 0.20 THK. REF


2 NICKEL UNDERPLATE OVER ALL

3 0.00254 MIN THK BRIGHT TIN, LUBRICATED, OVER NICKEL UNDERPLATE

4 0.000381 THK GOLD STRIPE

 $\frac{1}{5}$ te connectivity logo located approximately as shown

6 0.000762 THK GOLD STRIPE



SECTION **A-A** SCALE 20:1

SECTION **B-B** SCALE 20:1

										В
	2.40	2.60 2.20	1.55	I.96 I.57	1.30 - 1.60	22-24 AWG	ON REEL	6	-2 06 23-6	
	2.40	2.60 2.20	Ι.55	I.96 I.57	1.30 - 1.60	22-24 AWG	ON REEL	4	-2 06 23-3	
	2.40	2.60 2.20	Ι.55	I.96 I.57	1.30 - 1.60	22-24 AWG	LOOSE PIECE	2 3	-2 06 23-2	
	2.40	2.60 2.20	Ι.55	I.96 I.57	1.30 - 1.60	22-24 AWG	ON REEL	2 3	-2 06 23-	
	3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	ON REEL	4	2 0 6 2 3 - 3	
	3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	LOOSE PIECE	2 3	2 0 6 2 3 - 2	
	3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	ON REEL	2 3	2 0 6 2 3 -	
	DIM D	DIM C	DIM B	DIM A	INSULATION DIA	WIRE RANGE	REMARKS	FINISH	PART NO	
	DIMENSIONS: TOLERANCES UNLESS OTHERWISE SPECIFIED: TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±0.13 3 PLC ±- 4 PLC ±- 4 PLC ±- ANGLES ±1° MATERIAL			TOLERANCES UNLESS HERWISE SPECIFIED: ±- ±- ±0.13 ±- S ±1° H WEIGH	04MAR20 BROWN 04MAR20 BUCHER ct spec 08-2391 cation spec 14-13261 t	9 TE Connectivity - NAME CONTACT, RECEPTACLE, CRIMP SNAP-IN SLIM SEAL SSL - SIZE CAGE CODE DRAWING NO A 2 00779 C= 2106123				
			$\angle $	-	SEE TABLE CUST	OMER DRAWING		scale 0 : 1	sheet of Rev A 3	

D

С

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-2106123-4</u>