


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.




PANDUIT PART NO. *	REC'M FASTENER	USE WITH THESE CABLE TIES **	WEIGHT lbs 100 (g) pcs
SMS-A	-----	S = STANDARD	0.81 (371)
SMS-S6	#6 F.H.C.S or B.H.C.S		0.74 (335)

TO APPLY ADHESIVE MOUNT:

1. REMOVE PROTECTIVE LINER.
2. PLACE IN DESIRED LOCATION.
3. APPLY PRESSURE TO TOP SURFACE OF MOUNT.

NOTES:

1. SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND COLOR.




ADHESIVE BACKING:
PRESSURE SENSITIVE FOAM TAPE 0.040" (1.0)
THICK WITH PROTECTIVE LINER. MOUNT IS DESIGNED
TO SUPPORT 1lb. (454g) MAX. WEIGHT ON A
CLEAN DRY, SMOOTH, GREASE-FREE SURFACE.

NO WARRANTY, EXPRESSED, OR IMPLIED, IS MADE BY PANDUIT
WITH RESPECT TO ADHESIVE BOND PERFORMANCE. AMONG OTHER
THINGS, THE CONDITIONS UNDER WHICH THESE MOUNTS MAY BE
APPLIED AND/OR THE SURFACE TO WHICH THEY MAY BE APPLIED
ARE BEYOND PANDUIT'S CONTROL.



SCALE: 3/4



SCALE: 1/2

DIMENSIONS IN BRACKETS ARE METRIC [mm]

CAD FILENAME/LAYERS G00239LA_PB_SMS_00

PANDUIT

CORP.

TINLEY PARK, ILLINOIS

SNAP IN MOUNT
(SMS-A, -S6)

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ±0.05 (1.3) (.XXX) ±0.010 (0.25)
(.XX) ±0.02 (0.5) ANGLES ± 5°

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY JAD

MAT'L:

SCALE FULL

DATE 1/28/04

ABS

DRAWING NO.

G00239LA

DWG
SIZE
A

R	1/28/04	JAD		INITIAL RELEASE	G00239LA	R							
REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[SMS-A-D15](#)