

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

—, — .

© COPYRIGHT — By —

ALL RIGHTS RESERVED.

LOC —

DIST —

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D9	REVISED PER ECO-12-012202	03JUL12	KH	MS

PHYSICAL PROPERTIES:

HOUSING MATERIAL: PBT

FLAMMABILITY: UL94V-0

COLOR: BLACK

TERMINAL:

TERMINALS: BRASS, TIN PLATED

SCREWS: 6-32, STEEL, NICKEL PLATED

MECHANICAL:

PITCH (TERMINAL SPACING): 9.50mm (.374")

WIRE RANGE: 12-22 AWG

RECOMMENDED TIGHTENING TORQUE: 12IN-LBS MAX.

ELECTRICAL PROPERTIES:

MAXIMUM CURRENT: 20A

OPERATING VOLTAGE: 300V

ENVIRONMENTAL PROPERTIES:

OPERATING TEMP RANGE: -40°C TO 120°C

1

SCREWS ON ONE SIDE IN WIRE READY POSITION.

2

SEE FIGURE.

3

WHITE INK STAMP.

4

NICKEL PLATED BRASS SCREWS.

5

PRELIMINARY PART NUMBER.

6

TE CONNECTIVITY LOGO LOCATED APPROXIMATE AREA SHOWN.

<div>5</div> <div>2</div>	104.7	112.2	—	—	10	4-1546307-7
<div>5</div> <div>2</div>	104.7	112.2	—	—	10	4-1546307-6
<div>5</div> <div>4</div>	104.7	112.2	—	—	10	4-1546307-5
<div>5</div> <div>2</div> <div>1</div>	104.7	112.2	—	—	10	3-1546307-3
	104.7	112.2	—	—	10	1-1546307-0
<div>5</div> <div>3</div> <div>2</div> <div>1</div>	95.2	102.7	—	9	9	5-1546307-0
<div>5</div> <div>3</div> <div>2</div> <div>1</div>	95.2	102.7	4	9	9	4-1546307-9
<div>3</div> <div>2</div> <div>1</div>	95.2	102.7	4	9	9	4-1546307-8
	95.2	102.7	—	—	9	1546307-9
	85.7	93.2	—	—	8	1546307-8
	76.2	83.7	—	—	7	1546307-7
<div>5</div> <div>4</div>	66.7	74.2	—	—	6	4-1546307-4
	66.7	74.2	—	—	6	1546307-6
<div>5</div> <div>2</div>	57.2	64.7	—	—	5	4-1546307-3
<div>5</div> <div>2</div>	57.2	64.7	—	—	5	4-1546307-2
<div>5</div> <div>2</div>	57.2	64.7	—	—	5	4-1546307-1
<div>5</div> <div>2</div>	57.2	64.7	—	—	5	4-1546307-0
<div>5</div> <div>4</div>	57.2	64.7	—	—	5	3-1546307-9
	57.2	64.7	—	—	5	1546307-5
<div>5</div> <div>2</div> <div>1</div>	47.7	55.2	—	—	4	3-1546307-2
	47.7	55.2	—	—	4	1546307-4
<div>5</div> <div>2</div>	38.2	45.7	—	—	3	3-1546307-8
<div>5</div> <div>2</div>	38.2	45.7	—	—	3	3-1546307-7
<div>5</div> <div>2</div>	38.2	45.7	—	—	3	3-1546307-6
<div>5</div> <div>2</div>	38.2	45.7	—	—	3	3-1546307-5
<div>5</div> <div>4</div>	38.2	45.7	—	—	3	3-1546307-4
	38.2	45.7	—	—	3	1546307-3
	28.7	36.2	—	—	2	1546307-2
	DIM B	DIM A	QC TAB .187 45° ②	QC TAB .187 FLAT ①	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

0 PLC ± —  
1 PLC ± 0.3  
2 PLC ± 0.25  
3 PLC ± —  
4 PLC ± —  
ANGLES ± 2°

MATERIAL

—

FINISH

—

DWN S SCHLEGEL 20AUG2002

CHK C RICHARD 8/20/02

APVD C RICHARD 8/20/02

PRODUCT SPEC

—

APPLICATION SPEC

—

WEIGHT

—

TE Connectivity

9.50MM (.374) DBL ROW BARRIER STRIP W/ WASHER

SIZE A3

CAGE CODE 00779

DRAWING NO C-1546307

RESTRICTED TO

—

CUSTOMER DRAWING

SCALE 1:1

SHEET 1 OF 3

REV D9

1470-19 (3/11)





# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-1546307-7](#)