Note: This datasheet may be out of date.

Please download the latest datasheet of PTGL05AR181M7P52B0 from the official website of Murata

Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=PTGL05AR181M7P52B0

#### PTGL05AR181M7P52B0












### Appearance & Shape







#### Features

- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise.

  Durable and strong against mechanical vibration and shock because it is a solid element.



Limited Usage	Consumer Grade
Other Usage	Transformers     Transistors     Fluorescent Lamps



### Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	500

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with no ur sales representatives or product engineers before ordering.

2. This datasheet has early being passifications because there is no expense for datafacturing the product of the product of

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/12/22

## PTGL05AR181M7P52B0



Max. Voltage	125V
Hold Current	30mA
Measure Condition of Hold Current	(at +60°C)
Hold Current (2)	38mA
Measure Condition of Hold Current (2)	(at +25°C)
Trip Current	64mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	75mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	0.3A
Resistance (25°C)	180Ω
Resistance Value Tolerance (at 25°C)	±20%
Power Consumption(typ)	0.7W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	6mm
Thickness	5mm
F: Lead Space	5mm

d: Lead Diameter	0.6mm
Shape	Lead
Mass	0.3g

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/


Last updated :2018/12/22


Note: This datasheet may be out of date Please download the latest datasheet of PTGL05AR181M7P52B0 from the official website of Murata

Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=PTGL05AR181M7P52B0


# PTGL05AR181M7P52B0







Resistance-Temperature Charac.



Protective Threshold Current Range

Operating Time (Typical Curve)

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

### **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

#### Murata:

PTGL05AR181M7P52B0 PTGL05BD102N9N52B0 PTGL05BD102N9N52A0