

# Product: <u>9395</u> ☑

# Microphone Cable, 1 Conductor 18 AWG, TC



# **Product Description**

18 AWG stranded (41x34) high-conductivity TC condcutor, EPDM rubber insulation, conductive textile (100%) plus TC spiral shields (70% coverage), paper tape, CPE jacket.

# **Technical Specifications**

# **Physical Characteristics (Overall)**

Condu	Conductor				
AWG	Stranding	Material	Nominal	Diameter	No. of Coax
18	41x34	High Conductivity Tinned Copper	0.047 in		1
Condu	uctor Count:		1		

#### Insulation

Material	Nominal Diameter
EPDM - Ethylene Propylene Diene Monomer	0.137 in

#### **Outer Shield Material**

Туре	Layer	Material	Coverage [%]
Spiral Serve / Screen	1	Conductive Textile	100 %
Spiral Serve / Screen	2	TC - Tinned Copper	70 %
Таре	3		100 %

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Separator Material
Neoprene	0.235 in	0.034 in	Paper

# **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
6.5 Ohm/1000ft	6.5 Ohm/1000ft	11.3 Ohm/1000ft	11.3 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield	
55 pF/ft	ľ

## Impedance

Nominal Characteristic Impedance 35 Ohm

#### Delay

Nominal Velocity of Propagation (VP) [%]	
62 %	

#### Current

Max. Recommended Current [A]

#### Voltage

Non-U	L Voltag	e Rating
300 V F	RMS	

#### **Temperature Range**

Operating Temp Range: -30°C To +60°C	Non-UL Temp Rating:	60°C
	Operating Temp Range:	-30°C To +60°C

# **Mechanical Characteristics**

Bulk Cable Weight:	35 lbs/1000ft
Max Recommended Pulling Tension:	36 lbs
Min Bend Radius/Minor Axis:	2.5 in

N/A

## Standards

RG Type:	

#### **Applicable Environmental and Other Programs**

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

#### Suitability

ę	Suitability - Indoor:	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
Plenum/Non-Plenum	
Plenum (Y/N):	No

# Part Number

# © 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 9395 0101000