



- 1 TIN PL .000150 MIN THK PER ASTM B 545
- 2 PART NO: 324466; .243 LB.  
PART NO: 1-324466-0; .243 LB.  
PART NO: 2-324466-1; .243 LB.  
PART NO: 2-324466-2; .269 LB.
- 3 RED COLOR CODE
- 4 CLEANED, UNPLATED
- 5 .045 MAX BURR ALLOWED INSIDE THE WIRE BARREL ID IN AREA OF SIGHT HOLE.

OBSOLETE	1.07	1.32	2.64	△	450-550 MCM	COPPER ASTM-B-75 ANNEALED	2-324466-2
	1.07	1.07	2.41	△△			<del>2-324466-1</del>
				△			1-324466-0
				△			324466
	"C"	"B"	"A"	FINISH	WIRE RANGE	MATERIAL	PART No

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± -
1 PLC	± -
2 PLC	± -
3 PLC	± -
4 PLC	± -
ANGLES	± -

MATERIAL

SEE TABLE

DWN  
DK SCHRUM  
4/24/89

CHK  
MS FEHER  
4/24/89

APVD  
WJ VOCKROTH  
11/8/89

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

TE Connectivity

SPLICE, BUTT, AMPPOWER  
WIRE SIZE: 500 MCM

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=324466

—

SCALE

SHEET

REV

2:1

1 OF 1

R



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[324466](#)