DASH NO MODEL NO Q	TA CONTAINED IN THIS DOCUMENT IS OPRIETARY TO TROMPETER ELECTRONICS INC. D SHALL NOT BE DISCLOSED, COPIED OR USED RECV REV REVISIONS DATE APPROVED R PROCUMENT OR NANURACTURE WITHOUT PRESS WRITTEN PERMISSION. C REVISED PER ECO 14093 6-6-01 MAM.
-1 BJ228 50 -2 UBJ228 75	IDICATES ORIGINAL
Ø.562 . 500-28UNEF-2A . 500-28UNEF-2A 2X Q . 060 . 060	SCALE 1/1
	RECOMMENDED PANEL CUTOUT SCALE 1/1
3. SOCKET CONTACT COAXIAL BNC TYPE INSULATED FEED THRU BULKHEAD JACK, 50 AND 75 OHM VERSIONS	INTERPRET DRAWING PER NIL-STD-100. TOL: UNLESS SPECIFIED. DIMENSIONS ARE IN INCHES AND INCLUDE FINISH THICKNESS UNLESS OTHERWISE SPECIFIED. TOL: UNLESS SPECIFIED.
2. MAX PANEL THICKNESS: .156 I. FINISH: TFS-IY (NICKEL) NOTES: UNLESS OTHERWISE SPECIFIED.	DRN JCM 6-5-01 B J 2 2 8 / U B J 2 2 8 CH/Q.M. 6/5/0/ FINISH: SIZE CAGE CODE DRAWING NO. APPROVED 6/5/0/ FINISH: SIZE CAGE CODE DRAWING NO. C NEXT ASSY PROVE FILE NO. 6/5/0/ DO NOT SCALE DWG SCALE 2/1 DATE 6/13/00 SHEET IC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions: