

LOC	DIST	REVISIONS				
AJ	16	P	LTR	DESCRIPTION	DATE	APVD
		A		REVISED PER EC 0514-0150-05	06OCT2005	REH JL

- 1

CARBON STEEL PER ASTM-A-108
- 2

BRASS PER ASTM-B-16
- 3

PHOSPHOR BRONZE PER ASTM-B-139
- 4

POLYMETHYLPENTENE: GENERAL PURPOSE
- 5



SILICONE RUBBER PER ZZ-R-765
- 6

ZINC DIE CAST PER ASTM-B-86
- 7

GOLD PLATE PER ASTM-B-488,
0.76μm [.000030] MIN THICKNESS
- 8

NICKEL PLATE PER QQ-N-290,
1.27μm [.000050] MIN THICKNESS
- 9

NICKEL PLATE PER QQ-N-290,
2.54μm [.000100] MIN THICKNESS



5415020-1

PART
NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.			DWN L. VARELA — 18APR2005		tyco Electronics		Tyco Electronics Corporation		
			CHK J. HAVENER 18APR2005				Harrisburg, PA 17105-3608		
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		AP'D J. LIPPERT 18APR2005		NAME		PLUG-JACK ADAPTER, RIGHT ANGLE, 75 OHM, BNC	
		0 PLG ± —		PRODUCT SPEC		SIZE		CAGE CODE	
		1 PLG ± —		108-12096		DRAWING NO		RESTRICTED TO	
		2 PLG ± —		APPLICATION SPEC		A1 00779		C=5415020	
3 PLG ± —		4 PLG ± —		FINISH		WEIGHT		—	
MATERIAL SEE NOTES		SEE NOTES		CUSTOMER DRAWING		SCALE 10:1		SHEET 1 of 1	
								REV A	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5415020-1](#)