



No. of pos.	A <sup>-0,76</sup>	B <sup>-0,25</sup>	C	D <sup>-0,3</sup>
9	31,19	16,46	25,00 <sup>+0,12 -0,10</sup>	6,12
15	39,52	24,79	33,30 <sup>+0,15</sup>	6,12
25	53,42	38,50	47,04 <sup>±0,13</sup>	5,99
37	69,70	54,96	63,50 <sup>+0,13 -0,11</sup>	5,99

Directive 2002/95/EC  
„RoHS“  
Compliant

Part No. for plug connector		
No. of pos.	UNC 4-40	M 3
9	16-000380	16-000330
15	16-000390	16-000340
25	16-000400	16-000350
37	16-000410	16-000360

NOTES:

- METALSHELLS: COPPER ALLOY; min. 315µin TIN over 40-80µin NICKEL
- THREADED INSERT: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- COLLAR: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- ⓑ JACKSCREW: STAINLESS STEEL 1.4305
- WIRE ROPE: STAINLESS STEEL 1.4401
- RETAINING WASHER: STAINLESS STEEL 1.4122
- TERMINAL RING: UNINSULATED, COPPER ALLOY; min. 200µinTIN over 80µin NICKEL
- MAXIMUM TORQUE VALUE FOR THREAD: 6in.LB
- CONNECTOR IS PART MARKED: PART NO. CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

1 x b	Ä 3186	17.11.2008	Petker	tolerance	ISO 2768-m	dim. in mm	
date	name	drawn	02.05.08	Sonnenberg	appd.	02.05.08	Fischer
norm	d-old	rev.	description	date	name	CONEC	

scale:	2:1 (5:1)	
material:	SEE NOTES	
title:	SCREEN CAP 9-37pos. FOR PLUG CONNECTOR with threaded insert, jackscrew and wire rope	
dwg no:	Inventor 10	DIN-A3
	16K1A2293	sh: 1
part no:	see table	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[16-000410](#) [16-000380](#) [16-000400](#) [16-000390](#)