


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
J	-	D5	REVISED PER ECR-17-018148	13DEC17	SC BH
		D6	REVISED PER ECR-19-017851	26NOV19	SM DZ



1. APPLICABLE CONTACT PART NUMBER;  
 TAB CONTACT: 175150-□ (#20-#16AWG)  
 175149-□ (#26-#22AWG)  
 2 TO BE USED WITH THE CONTACT WHICH IS RATED 105°C MAX  
 3 MATERIAL: PA66, UL94 V-0, GWIT 775°C

1-176271-5	130°C MAX	3	GREEN 绿	2	1-176282-5
1-176271-1	130°C MAX	3	NATURAL 自然色		1-176282-1 2
176271-□	105°C MAX	PA66	BLACK 黒	2	176282-9
			BLUE 青		176282-6
			YELLOW 黄		176282-4
			RED 赤		176282-2
	NATURAL 自然色			176282-1	
MATING CONN. PART NUMBER 嵌合相手型番	TEMPERATURE RATING 定格温度	TYPE 種類	HOUSING COLOR 色	Pos. 極数	PART NUMBER 型番
MATERIAL 材料					

1. 適用端子型番;  
 リセコンタクト: 175150-□ (#20-#16AWG)  
 175149-□ (#26-#22AWG)  
 2 適用コンタクトの使用温度は最大105°C

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN Y.NARISAWA 19NOV1990		AMP UNIVERSAL POWER CONN. 3.96mm PITCH CAP HOUSING 2 Pos. (SGL ROW) AMP ユニバーサルパワーコネクタ 2極 3.96mmピッチ キャップハウジング			
CHK Y.FUJITA 19NOV1990					
APVD N.ONOUE 20NOV1990					
PRODUCT SPEC 108-5302					
MATERIAL SEE TABLE	APPLICATION SPEC 114-5142	SIZE A3	CAGE CODE 00779	DRAWING NO C-176282	RESTRICTED TO
RESTRICTED CUSTOMER			SCALE NTS	SHEET 1 OF 1	REV D6