

Bus coupler - IBS ST 24 BKM-T - 2750154

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



INTERBUS-ST bus terminal module, 24 V DC, with 8-pos. MINI-COMBICON plug, IP20 protection, consisting of: Terminal part with screw connection and module electronics

Product Description

INTERBUS ST standard bus terminal modules

The INTERBUS bus terminal module connects the input/output modules of an ST station with the INTERBUS network.

Depending on the transmission medium used, the bus terminal modules are equipped with different bus connections. For copper conductors, D-SUB and MINI-COMBICON connectors are available. The fiber optic versions are equipped with F-SMA connectors.

The bus terminal modules are available in two different performance classes. A maximum of 4 or 8 input/output modules can be operated on one bus terminal module.

The bus terminal module takes on the following functions within a modular INTERBUS-ST station:

- Refreshing the INTERBUS remote bus signals
- Electrical isolation of the remote bus segments
- Decoupling of the outgoing remote bus or of the connected input/ output modules from the INTERBUS network with a software command
- Supply of the connected input/output modules with an electrically isolated voltage supply from an integrated power supply unit

Product Features

- Copper or fiber optic connection
- Additional I/Os onboard
- Additional remote/local bus branches



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 108298
Weight per Piece (excluding packing)	284.8 g
Custom tariff number	85389091
Country of origin	Germany

Bus coupler - IBS ST 24 BKM-T - 2750154

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	44 mm
Height	117 mm
Depth	116 mm

Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	30 % ... 75 % (non-condensing)
Permissible humidity (storage/transport)	30 % ... 95 % (non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (up to 1500 m above mean sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above mean sea level)
Degree of protection	IP20

Interfaces

Fieldbus system	Lokalbus
Designation	ST local bus
Connection method	ST local bus connector
Transmission speed	500 kBit/s
Fieldbus system	INTERBUS
Designation	INTERBUS
Connection method	8-pos. mini Combicon connector
Designation connection point	Incoming/Outgoing Remote Bus
Number of positions	8

Digital inputs

Connection method	Screw connection
-------------------	------------------

Power supply for module electronics

Supply voltage	24 V DC
Supply voltage range	20 V DC ... 30 V DC (including ripple)
Ripple	3.6 V _{pp} within the allowable voltage range
Current consumption	typ. 150 mA (without ST module expansions)
Communications power U _L	9 V DC
Current consumption	max. 500 mA (Total current consumption of all I/O modules on the ST local bus)

General

Bus coupler - IBS ST 24 BKM-T - 2750154

Technical data

General

Mounting type	DIN rail
Net weight	200 g

Standards and Regulations

Test section	Incoming remote bus / Outgoing remote bus 500 V AC 50 Hz 1 min.
	Incoming remote bus/ST interface 500 V AC 50 Hz 1 min.
Protection class	III, IEC 61140, EN 61140, VDE 0140-1

Classifications

eCl@ss

eCl@ss 4.0	27250203
eCl@ss 4.1	27250203
eCl@ss 5.0	27250203
eCl@ss 5.1	27242608
eCl@ss 6.0	27242608
eCl@ss 7.0	27242608
eCl@ss 8.0	27242608

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC001604

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

INTERBUS CLUB / EAC

Bus coupler - IBS ST 24 BKM-T - 2750154

Approvals

Ex Approvals

Approvals submitted

Approval details

INTERBUS CLUB

EAC

Accessories

Accessories

Bridge

Jumper - IB ST LBC - 2836492



Spare local bus cable, for INTERBUS-ST modules

Insertion bridge - EB 84 IB ST BU - 2836269



Insertion bridges, divisible, isolated comb spine, color blue, 84-pos.

Insertion bridge - EB 84 IB ST RD - 2836272



Insertion bridges, divisible, isolated comb spine, color red, 84-pos.

Bus coupler - IBS ST 24 BKM-T - 2750154

Accessories

Connector set

Connector set - IBS RB PLSET/MC 1,5/8 - 2722755



Replacement remote bus connector set, for INTERBUS-ST bus terminal block BKM-...

Device parameterization

Software - AX+ BASIC - 2985068



Software CD for FDT container for integrating device DTMs (free download)

Software - AX DTM LIB - 2988065



DTM library

Mounting material

Shield connection clip - IBS RB-SHIELD - 2722742



Replacement shield point, for INTERBUS-ST bus terminal block BKM-...

Spare parts

Bus coupler - IBS ST 24 BKM-T - 2750154

Accessories


Jumper - IB ST LBC - 2836492




Spare local bus cable, for INTERBUS-ST modules

Drawings

Connection diagram



Dimensional drawing



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2750154](#)