


## Programmable Spread Spectrum Clock Generator for EMI Reduction

### Features

- Wide Operating Output (SSCLK) Frequency Range
  - 3 to 200 MHz
- Programmable Spread Spectrum with Nominal 31.5 kHz modulation Frequency
- Center Spread:  $\pm 0.25\%$  to  $\pm 2.5\%$
- Down Spread:  $-0.5\%$  to  $-5.0\%$
- Input Frequency Range
  - External crystal: 8 to 30 MHz fundamental crystals
  - External reference: 8 to 166 MHz clock
- Integrated Phase-Locked Loop (PLL)
- Programmable Crystal Load Capacitor Tuning Array
- Low Cycle-to-Cycle Jitter
- 3.3 V Operation with 2.5 V Output Clock Drive Option
- Spread Spectrum On and Off Function
- Power Down or Output Enable Function
- Output Frequency Select Option
- Field-Programmable
- Package: 16-pin TSSOP

### Logic Block Diagram




## Contents

|  |    |
|--|----|
| <b>Pin Configuration</b> .....                       | 3  |
| <b>Pin Description</b> .....                         | 3  |
| <b>General Description</b> .....                     | 4  |
| <b>Programming Description</b> .....                 | 4  |
| <b>Field-Programmable CY25200</b> .....              | 4  |
| Factory-Programmed CY25200 .....                     | 4  |
| <b>Product Functions</b> .....                       | 5  |
| Control Pins (CP0, CP1, CP2 and CP3) .....           | 5  |
| Example .....  | 5  |
| CLKSEL .....   | 5  |
| Input Frequency (XIN, Pin 1 and XOUT, Pin 16) .....  | 5  |
| CXIN and CXOUT (Pin 1 and Pin 16) .....              | 5  |
| Output Frequency .....                               |    |
| (SSCLK1 through SSCLK6 Outputs) .....                | 5  |
| Spread Percentage .....                              |    |
| (SSCLK1 to SSCLK6 Outputs) .....                     | 6  |
| Modulation Frequency .....                           | 6  |
| <b>Absolute Maximum Ratings</b> .....                | 7  |
| <b>Recommended Crystal Specifications</b> .....      | 7  |
| <b>Recommended Operating Conditions</b> .....        | 7  |
| <b>DC Electrical Specifications</b> .....            | 8  |
| <b>Thermal Resistance</b> .....                      | 8  |
| <b>AC Electrical Specifications</b> .....            | 9  |
| <b>Switching Waveforms</b> .....                     | 11 |
| <b>Informational Graphs</b> .....                    | 12 |
| <b>Ordering Information</b> .....                    | 13 |
| Possible Configurations .....                        | 13 |
| Ordering Code Definitions .....                      | 13 |
| <b>Package Drawing and Dimensions</b> .....          | 14 |
| <b>Acronyms</b> .....                                | 15 |
| <b>Document Conventions</b> .....                    | 15 |
| Units of Measure .....                               | 15 |
| <b>Document History Page</b> .....                   | 16 |
| <b>Sales, Solutions, and Legal Information</b> ..... | 18 |
| Worldwide Sales and Design Support .....             | 18 |
| Products .....                                       | 18 |
| PSoC®Solutions .....                                 | 18 |
| Cypress Developer Community .....                    | 18 |
| Technical Support .....                              | 18 |

## Pin Configuration

**Figure 1. 16-pin TSSOP pinout**



## Pin Description

**Table 1. Pin Summary**

| Name               | Pin Number | Description  |
|--------------------|------------|--|
| XIN                | 1          | Crystal input or Reference Clock input   |
| XOUT               | 16         | Crystal output. Leave this pin floating if external clock is used  |
| VDD                | 2          | 3.3 V power supply for digital logic and SSCLK5 and 6 clock outputs                                      |
| AVDD               | 3          | 3.3 V analog-PLL power supply  |
| VSS                | 13         | Ground   |
| AVSS               | 5          | Analog ground  |
| VDDL               | 11         | 2.5 V or 3.3 V power supply for SSCLK1/2/3/4 clock outputs   |
| VSSL               | 6          | VDDL power supply ground   |
| SSCLK1             | 7          | Programmable spread spectrum clock output at VDDL level (2.5 V or 3.3 V)                                 |
| SSCLK2             | 8          | Programmable spread spectrum clock output at VDDL level (2.5 V or 3.3 V)                                 |
| SSCLK3             | 9          | Programmable spread spectrum clock output at VDDL level (2.5 V or 3.3 V)                                 |
| SSCLK4             | 12         | Programmable spread spectrum clock output at VDDL level (2.5 V or 3.3 V)                                 |
| SSCLK5/REFOUT/CP2  | 14         | Programmable spread spectrum clock or buffered reference output at VDD level (3.3 V) or control pin, CP2 |
| SSCLK6/REFOUT/CP3  | 15         | Programmable spread spectrum clock or buffered reference output at VDD level (3.3 V) or control pin, CP3 |
| CP0 <sup>[1]</sup> | 4          | Control pin 0  |
| CP1 <sup>[1]</sup> | 10         | Control pin 1  |

### Note

1. Pins are programmed to be any of the following control signals: OE: Output Enable, OE = 1, all the SSCLK outputs are enabled; PD#: Power down, PD# = 0, all the SSCLK outputs are three-stated and the part enters a low power state; SSON: Spread Spectrum Control (SSON = 0, No Spread and SSON = 1, Spread Signal), CLKSEL: SSCLK Output Frequency Select. See [Control Pins \(CP0, CP1, CP2 and CP3\)](#) for control pins programming options.

**Table 2. Fixed Function Pins**

| Pin Function             | Output Clock Frequency | Input Frequency | C <sub>XIN</sub> and C <sub>XOUT</sub> | Spread Percent               | Modulation Frequency |
|--------------------------|------------------------|-----------------|--|------------------------------|----------------------|
| Pin Name                 | SSCLK[1:6]             | XIN and XOUT    | XIN and XOUT                           | SSCLK[1:6]                   | SSCLK[1:6]           |
| Pin#                     | 7, 8, 9, 12, 14, 15    | 1 and 16        | 1 and 16                               | 7, 8, 9, 12, 14, 15          | 7, 8, 9, 12, 14, 15  |
| Units                    | MHz                    | MHz             | pF                                     | % and Center- or Down-spread | kHz                  |
| Program Value CLKSEL = 0 | USER SPECIFIED         | USER SPECIFIED  | USER SPECIFIED                         | USER SPECIFIED               | USER SPECIFIED       |
| Program Value CLKSEL = 1 | USER SPECIFIED         |                 |  |                              |                      |

**Table 3. Multi-Function Pins**

| Pin Function | Output Clock/REFOUT/OE/SSON/CLKSEL |                   | OE/PD#/SSON/CLKSEL |                |
|--------------|------------------------------------|-------------------|--------------------|----------------|
| Pin Name     | SSCLK5/REFOUT/CP2                  | SSCLK6/REFOUT/CP3 | CP0                | CP1            |
| Pin#         | 14                                 | 15                | 4                  | 10             |
| Units        | Function                           | Function          | Function           | Function       |
|              | USER SPECIFIED                     | USER SPECIFIED    | USER SPECIFIED     | USER SPECIFIED |

## General Description

The CY25200 is a Spread Spectrum Clock Generator (SSCG) IC used to reduce Electro Magnetic Interference (EMI) found in today's high speed digital electronic systems.

The device uses a Cypress proprietary Phase-Locked Loop (PLL) and Spread Spectrum Clock (SSC) technology to synthesize and modulate the frequency of the input clock. By frequency modulating the clock, the measured EMI at the fundamental and harmonic frequencies are reduced. This reduction in radiated energy significantly reduces the cost of complying with regulatory agency requirements (EMC) and improves time to market, without degrading system performance.

The CY25200 uses a factory and field-programmable configuration memory array to synthesize output frequency, spread %, crystal load capacitor, clock control pins, PD#, and OE options.

The spread % is factory and field-programmed to either center spread or down spread with various spread percentages. The range for center spread is from  $\pm 0.25\%$  to  $\pm 2.50\%$ . The range for down spread is from  $-0.5\%$  to  $-5.0\%$ . Contact the factory for smaller or larger spread % amounts, if required.

The input to the CY25200 is either a crystal or a clock signal. The input frequency range for crystals is 8 to 30 MHz and for clock signals is 8 to 166 MHz.

The CY25200 has six clock outputs, SSCLK1 to SSCLK6. The frequency modulated SSCLK outputs are programmed from 3 to 200 MHz.

The CY25200 products are available in a 16-pin TSSOP package with a commercial operating temperature range of 0 to 70 °C.

## Programming Description

### Field-Programmable CY25200

The CY25200 is programmed at the package level, and must be programmed prior to installation on a circuit board. Field programmable devices are denoted by an "F" in the ordering code, and are blank when shipped. The CY25200 is Flash technology based, which allows it to be reprogrammed up to 100 times. This allows for fast and easy design changes and product updates, and eliminates issues with old and out of date inventory.

Samples and small prototype quantities are programmed on the CY3672 programmer with the CY3695 socket adapter.

### Factory-Programmed CY25200

Factory programming by Cypress is available for high volume orders. All requests must be submitted to the local Cypress Field Application Engineer (FAE) or sales representative. After the request is processed, you will receive a new part number, samples, and data sheet with the programmed values. This part number is used for additional sample requests and production orders.

## Product Functions

### Control Pins (CP0, CP1, CP2 and CP3)

Four control signals are available through programming of pins 4, 10, 14, and 15.

CP0 (pin 4) and CP1 (pin10) are specifically designed to function as control pins. However, pins 14 (SSCLK5/REFOUT/CP2) and 15 (SSCLK6/REFOUT/CP3) are multi-functional and can be programmed to be either a control signal or an output clock (SSCLK or REFOUT). All of the control pins, CP0, CP1, CP2, and CP3 are programmable to one of the following functions:

- OE (Output Enable): if OE = 1, all SSCLK and REFOUT outputs are enabled.
- SSON (Spread spectrum control): if SSON = 1, spread is on; if SSON = 0, spread is off.
- CLKSEL (Clock select): frequency select for all SSCLK outputs.
- PD# (Power Down; active low): if PD# = 0, all the outputs are three-stated and the part enters a low power state.

Note that the PD# function is available only on CP0 or CP1; it is not available on CP2 or CP3.


### Example

Here is an example with three control pins:

- CLKIN = 33 MHz
- SSCLK1/2/3/4 = 100 MHz with  $\pm 1\%$  spread
- SSCLK 5 = REFOUT(33 MHz)
- CP0 (pin 4) = PD#
- CP1 (pin 10) = OE
- CP3 (pin 15) = SSON

The pinout for the above example is shown in [Figure 2](#).

**Figure 2. Example Pin Diagram**



### CLKSEL

The CLKSEL control pin enables you to select between two different SSCLK output frequencies. These must be related

frequencies that are derived off of a common PLL frequency. Specifically, CLKSEL does not change the PLL frequency. It only changes the output divider. For instance, 33.333 MHz and 66.666 MHz are both derived from a PLL frequency of 400 MHz, by dividing it down by 12 and 6 respectively. [Table 4 on page 6](#) shows an example of how this is implemented. The PLL frequency range is 100 to 400 MHz. The two output dividers in the CY25200 can be any integer between 2 and 130, providing two different but related frequencies as explained above.

[Table 4 on page 6](#) and [Figure 3 on page 6](#) show an example configuration using the frequencies just described. In this example, the configurable pins SSCLK5 (pin 14) and SSCLK6 (pin 15) are used as output clocks.

### Input Frequency (XIN, Pin 1 and XOUT, Pin 16)

The input to the CY25200 is a crystal or a clock. The input frequency range for crystals is 8 to 30 MHz, and for clock signal is 8 to 166 MHz.

### $C_{XIN}$ and $C_{XOUT}$ (Pin 1 and Pin 16)

The CY25200 has internal load capacitors at pin 1 ( $C_{XIN}$ ) and pin 16 ( $C_{XOUT}$ ).  $C_{XIN}$  always equals  $C_{XOUT}$ , and they are programmable from 12 pF to 60 pF, in 0.5 pF increments. This feature eliminates the need for external crystal load capacitors.

The following formula is used to calculate the value of  $C_{XIN}$  and  $C_{XOUT}$  for matching the crystal load ( $C_L$ ):

$$C_{XIN} = C_{XOUT} = 2C_L - C_P$$

Where  $C_L$  is the crystal load capacitor as specified by the crystal manufacturer and  $C_P$  is the parasitic PCB capacitance on each node of the crystal.

For example, if a crystal with  $C_L$  of 16 pF is used, and  $C_P$  is 2 pF,  $C_{XIN}$  and  $C_{XOUT}$  is calculated as:

$$C_{XIN} = C_{XOUT} = (2 \times 16) - 2 = 30 \text{ pF.}$$

If using a driven reference clock, set  $C_{XIN}$  and  $C_{XOUT}$  to the minimum value 12 pF, connect the reference to XIN/CLKIN, and leave XOUT unconnected.

### Output Frequency (SSCLK1 through SSCLK6 Outputs)

All the SSCLK outputs are produced by synthesizing the input reference frequency using a PLL and modulating the VCO frequency. SSCLK[1:4] are fixed function output clocks (SSCLK). SSCLK5 and SSCLK6 are also programmable to function the same as SSCLK[1:4], or as buffered copies of the input reference (REFOUT), or as control pin as discussed in [Control Pins \(CP0, CP1, CP2 and CP3\)](#). To use the 2.5 V output drive option on SSCLK[1:4], VDDL must be connected to a 2.5 V power supply (SSCLK[1:4] outputs are powered by VDDL). When using the 2.5 V output drive option, the maximum output frequency on SSCLK[1:4] is 166 MHz.

### Spread Percentage (SSCLK1 to SSCLK6 Outputs)

The SSCLK frequency is programmed to a percentage value from  $\pm 0.25\%$  to  $\pm 2.5\%$  for center spread and from  $-0.5\%$  to  $-5.0\%$  down spread. The granularity is  $0.25\%$ .


### Modulation Frequency

The default modulation frequency is 31.5 kHz. Other modulation frequencies available via the configuration software are 30.1 kHz and 32.9 kHz.

**Table 4. Using Clock Select, CLKSEL Control Pin**

| Input Frequency (MHz) | CLKSEL (Pin 4) | SSCLK1 (Pin 7) | SSCLK2 (Pin 8) | SSCLK3 (Pin 9) | SSCLK4 (Pin 12) | REFOUT (Pin 14) | REFOUT (Pin 15) |
|-----------------------|----------------|----------------|----------------|----------------|-----------------|-----------------|-----------------|
| 14.318                | CLKSEL = 0     | 33.33          | 33.33          | 33.33          | 33.33           | 14.318          | 14.318          |
|                       | CLKSEL = 1     | 66.66          | 66.66          | 66.66          | 66.66           | 14.318          | 14.318          |

**Figure 3. Using Clock Select, CLKSEL Control Pin Configuration pinout**



## Absolute Maximum Ratings

Supply Voltage (VDD) ..... -0.5 to +7.0 V  
 DC Input Voltage ..... -0.5 V to V<sub>DD</sub> + 0.5 V  
 Storage Temperature (non-condensing) ..... -55 °C to +125 °C

Junction Temperature ..... -40 °C to +125 °C  
 Data Retention at T<sub>j</sub> = 125 °C ..... > 10 years  
 Package Power Dissipation ..... 350 mW  
 Static Discharge Voltage (per MIL-STD-883, Method 3015) ..... ≥ 2000 V

## Recommended Crystal Specifications

| Parameter                      | Description  | Comments  | Min | Typ | Max | Unit |
|--------------------------------|--|---|-----|-----|-----|------|
| F <sub>NOM</sub>               | Nominal Crystal Frequency                                | Parallel resonance, fundamental mode, AT cut  | 8   | —   | 30  | MHz  |
| C <sub>LNOM</sub>              | Nominal Load Capacitance                                 | Internal load caps  | 6   | —   | 30  | pF   |
| R <sub>1</sub>                 | Equivalent Series Resistance (ESR)                       | Fundamental mode  | —   | —   | 25  | Ω    |
| R <sub>3</sub> /R <sub>1</sub> | Ratio of Third Overtone Mode ESR to Fundamental Mode ESR | Ratio used because typical R <sub>1</sub> values are much less than the maximum specification | 3   | —   | —   | Ω    |
| DL                             | Crystal Drive Level                                      | No external series resistor assumed   | —   | 0.5 | 2   | mW   |

## Recommended Operating Conditions

| Parameter                      | Description   | Min   | Typ | Max   | Unit |
|--------------------------------|---|-------|-----|-------|------|
| V <sub>DD</sub>                | Operating Voltage   | 3.135 | 3.3 | 3.465 | V    |
| V <sub>DDLHI</sub>             | Operating Voltage   | 3.135 | 3.3 | 3.465 | V    |
| V <sub>DDLLO</sub>             | Operating Voltage   | 2.375 | 2.5 | 2.625 | V    |
| T <sub>AC</sub>                | Ambient Commercial Temp   | 0     | —   | 70    | °C   |
| C <sub>LOAD</sub>              | Maximum Load Capacitance V <sub>DD</sub> /V <sub>DDL</sub> = 3.3 V  | —     | —   | 15    | pF   |
| C <sub>LOAD</sub>              | Maximum Load Capacitance V <sub>DDL</sub> = 2.5 V   | —     | —   | 15    | pF   |
| F <sub>SSCLK-HighVoltage</sub> | SSCLK1/2/3/4/5/6 when V <sub>DD</sub> = A <sub>VDD</sub> = V <sub>DDL</sub> = 3.3 V                       | 3     | —   | 200   | MHz  |
| F <sub>SSCLK-LowVoltage</sub>  | SSCLK1/2/3/4 when V <sub>DD</sub> = A <sub>VDD</sub> = 3.3 V and V <sub>DDL</sub> = 2.5 V                 | 3     | —   | 166   | MHz  |
| R <sub>REFOUT</sub>            | REFOUT when V <sub>DD</sub> = A <sub>VDD</sub> = 3.3 V and V <sub>DDL</sub> = 3.3 V or 2.5 V              | 8     | —   | 166   | MHz  |
| f <sub>REF1</sub>              | Clock Input   | 8     | —   | 166   | MHz  |
| f <sub>REF2</sub>              | Crystal Input   | 8     | —   | 30    | MHz  |
| t <sub>PU</sub>                | Power up time for all V <sub>DDs</sub> to reach minimum specified voltage (power ramps must be monotonic) | 0.05  | —   | 500   | ms   |

## DC Electrical Specifications

| Parameter <sup>[2]</sup> | Name                | Description   | Min | Typ | Max | Unit          |
|--------------------------|---------------------|---|-----|-----|-----|---------------|
| $I_{OH3.3}$              | Output High Current | $V_{OH} = V_{DD} - 0.5 \text{ V}$ ,<br>$V_{DD}/V_{DDL} = 3.3 \text{ V}$ | 12  | 24  | —   | mA            |
| $I_{OL3.3}$              | Output Low Current  | $V_{OL} = 0.5 \text{ V}$ ,<br>$V_{DD}/V_{DDL} = 3.3 \text{ V}$          | 12  | 24  | —   | mA            |
| $I_{OH2.5}$              | Output High Current | $V_{OH} = V_{DDL} - 0.5 \text{ V}$ ,<br>$V_{DDL} = 2.5 \text{ V}$       | 8   | 16  | —   | mA            |
| $I_{OL2.5}$              | Output Low Current  | $V_{OL} = 0.5 \text{ V}$ ,<br>$V_{DDL} = 2.5 \text{ V}$                 | 8   | 16  | —   | mA            |
| $V_{IH}$                 | Input High Voltage  | CMOS levels, 70% of $V_{DD}$  | 0.7 | —   | 1.0 | $V_{DD}$      |
| $V_{IL}$                 | Input Low Voltage   | CMOS levels, 30% of $V_{DD}$  | 0   | —   | 0.3 | $V_{DD}$      |
| $I_{VDD}^{[3]}$          | Supply Current      | $AV_{DD}/V_{DD}$ Current  | —   | —   | 33  | mA            |
| $I_{VDDL2.5}^{[3]}$      | Supply Current      | $V_{DDL}$ Current ( $V_{DDL} = 2.625 \text{ V}$ )                       | —   | —   | 20  | mA            |
| $I_{VDDL3.3}^{[3]}$      | Supply Current      | $V_{DDL}$ Current ( $V_{DDL} = 3.465 \text{ V}$ )                       | —   | —   | 26  | mA            |
| $I_{DDS}$                | Power Down Current  | $V_{DD} = V_{DDL} = AV_{DD} = 3.465 \text{ V}$                          | —   | —   | 50  | $\mu\text{A}$ |
| $I_{OHZ}$<br>$I_{OLZ}$   | Output Leakage      | $V_{DD} = V_{DDL} = AV_{DD} = 3.465 \text{ V}$                          | —   | —   | 10  | $\mu\text{A}$ |

## Thermal Resistance

| Parameter <sup>[4]</sup> | Description                              | Test Conditions   | 16-pin TSSOP | Unit                        |
|--------------------------|--|---|--------------|-----------------------------|
| $\theta_{JA}$            | Thermal resistance (junction to ambient) | Test conditions follow standard test methods and procedures for measuring thermal impedance, in accordance with EIA/JESD51. | 90           | $^{\circ}\text{C}/\text{W}$ |
| $\theta_{JC}$            | Thermal resistance (junction to case)    |   | 14           | $^{\circ}\text{C}/\text{W}$ |

### Notes

2. Not 100% tested, guaranteed by design.
3.  $I_{VDD}$  currents specified for SSCLK1/2/3/4/5/6 = 33.33 MHz with CLKIN = 14.318 MHz and 15 pF on all the output clocks.
4. These parameters are guaranteed by design and are not tested.

## AC Electrical Specifications

| Parameter         | Description                              | Condition  | Min | Typ | Max | Unit |
|-------------------|--|--|-----|-----|-----|------|
| DC                | Output Duty Cycle                        | SSCLK, Measured at $V_{DD}/2$  | 45  | 50  | 55  | %    |
|                   | Output Duty Cycle                        | REFCLK, Measured at $V_{DD}/2$<br>Duty Cycle of CLKIN = 50%.   | 40  | 50  | 60  | %    |
| SR1               | Rising/Falling Edge Slew Rate            | SSCLK1/2/3/4 < 100 MHz,<br>$V_{DD} = V_{DDL} = 3.3$ V  | 0.6 | —   | 2.0 | V/ns |
| SR2               | Rising/Falling Edge Slew Rate            | SSCLK1/2/3/4 $\geq$ 100 MHz,<br>$V_{DD} = V_{DDL} = 3.3$ V   | 0.8 | —   | 3.5 | V/ns |
| SR3               | Rising/Falling Edge Slew Rate            | SSCLK1/2/3/4 < 100 MHz,<br>$V_{DD} = V_{DDL} = 2.5$ V  | 0.5 | —   | 2.2 | V/ns |
| SR4               | Rising/Falling Edge Slew Rate            | SSCLK1/2/3/4 $\geq$ 100 MHz,<br>$V_{DD} = V_{DDL} = 2.5$ V   | 0.6 | —   | 3.0 | V/ns |
| SR5               | Rising/Falling Edge Slew Rate            | SSCLK5/6 < 100 MHz,<br>$V_{DD} = V_{DDL} = 3.3$ V  | 0.6 | —   | 1.9 | V/ns |
| SR6               | Rising/Falling Edge Slew Rate            | SSCLK5/6 $\geq$ 100 MHz,<br>$V_{DD} = V_{DDL} = 3.3$ V   | 1.0 | —   | 2.9 | V/ns |
| T <sub>CCJ1</sub> | Cycle-to-Cycle Jitter<br>SSCLK1/2/3/4    | CLKIN = SSCLK1/2/3/4 = 166 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V    | —   | —   | 110 | ps   |
|                   |  | CLKIN = SSCLK1/2/3/4 = 66.66 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V  | —   | —   | 170 | ps   |
|                   |  | CLKIN = SSCLK1/2/3/4 = 33.33 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V  | —   | —   | 140 | ps   |
|                   |  | CLKIN = SSCLK1/2/3/4 = 14.318 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V | —   | —   | 290 | ps   |
| T <sub>CCJ2</sub> | Cycle-to-Cycle Jitter<br>SSCLK5/6=REFOUT | CLKIN = SSCLK1/2/3/4 = 166 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V    | —   | —   | 100 | ps   |
|                   |  | CLKIN = SSCLK1/2/3/4 = 66.66 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V  | —   | —   | 120 | ps   |
|                   |  | CLKIN = SSCLK1/2/3/4 = 33.33 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V  | —   | —   | 180 | ps   |
|                   |  | CLKIN = SSCLK1/2/3/4 = 14.318 MHz,<br>$\pm 2\%$ spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = V_{DDL} = 3.3$ V | —   | —   | 180 | ps   |

**AC Electrical Specifications (continued)**

| Parameter        | Description                               | Condition  | Min  | Typ  | Max  | Unit |
|------------------|---|--|------|------|------|------|
| $T_{CCJ3}$       | Cycle-to-Cycle Jitter<br>SSCLK1/2/3/4     | CLKIN = SSCLK1/2/3/4 = 166 MHz,<br>±2% spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = 3.3\text{ V}$ , $V_{DDL} = 2.5\text{ V}$    | —    | —    | 110  | ps   |
|                  |   | CLKIN = SSCLK1/2/3/4 = 66.66 MHz,<br>±2% spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = 3.3\text{ V}$ , $V_{DDL} = 2.5\text{ V}$  | —    | —    | 170  | ps   |
|                  |   | CLKIN = SSCLK1/2/3/4 = 33.33 MHz,<br>±2% spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = 3.3\text{ V}$ , $V_{DDL} = 2.5\text{ V}$  | —    | —    | 190  | ps   |
|                  |   | CLKIN = SSCLK1/2/3/4 = 14.318 MHz,<br>±2% spread and<br>SSCLK5/6 = REFOUT,<br>$V_{DD} = 3.3\text{ V}$ , $V_{DDL} = 2.5\text{ V}$ | —    | —    | 330  | ps   |
| $T_{STP}$        | Power Down Time                           | Time from falling edge on PD# to stopped outputs (Asynchronous)  | —    | 150  | 300  | ns   |
| $T_{OE1}$        | Output Disable Time                       | Time from falling edge on OE to stopped outputs (Asynchronous)   | —    | 150  | 300  | ns   |
| $T_{OE2}$        | Output Enable Time                        | Time from rising edge on OE to outputs at a valid frequency (Asynchronous)   | —    | 150  | 300  | ns   |
| $F_{MOD}$        | Spread Spectrum Modulation Frequency      | SSCLK1/2/3/4/5/6   | 30.0 | 31.5 | 33.0 | kHz  |
| $T_{PU1}$        | Power Up Time,<br>Crystal is used         | Time from rising edge on PD# to outputs at valid frequency (Asynchronous)  | —    | 3    | 5    | ms   |
| $T_{PU2}$        | Power Up Time,<br>Reference clock is used | Time from rising edge on PD# to outputs at valid frequency (Asynchronous)  | —    | 2    | 3    | ms   |
| $T_{SKEW}^{[5]}$ | Clock Skew                                | Output to output skew between related clock outputs. Measured at $V_{DD}/2$ .  | —    | —    | 250  | ps   |

**Note**

5. Skew and phase alignment is guaranteed within all SSCLK outputs and within both REFOUT outputs. All SSCLK outputs are related, and all REFOUT outputs are related, but SSCLK and REFOUT outputs are not related to each other.

## Switching Waveforms

Figure 4. Duty Cycle Timing ( $DC = t_{1A}/t_{1B}$ )





Figure 5. Output Rise and Fall Time (SSCLK and REFCLK)



Output Rise time ( $Tr$ ) =  $(0.6 \times V_{DD})/SR1$  (or SR3)

Output Fall time ( $Tf$ ) =  $(0.6 \times V_{DD})/SR2$  (or SR4)

Refer to AC Electrical Characteristics table for SR (Slew Rate) values.

Figure 6. Power Down and Power Up Timing









Figure 7. Output Enable and Disable Timing



## Informational Graphs

The informational graphs are meant to convey the typical performance levels. No performance specifications are implied or guaranteed.



## Ordering Information


| Ordering Code     | Package Type  | Programming | Operating Temperature Range |
|-------------------|---|-------------|-----------------------------|
| CY25200KFZXC      | 16-pin TSSOP (Pb-free)                                | Field       | Commercial, 0 °C to 70 °C   |
| CY25200KFZXCT     | 16-pin TSSOP – Tape and Reel (Pb-free)                | Field       | Commercial, 0 °C to 70 °C   |
| CY25200KFZXI      | 16-pin TSSOP (Pb-free)                                | Field       | Industrial, -40 °C to 85 °C |
| CY25200KFZXIT     | 16-pin TSSOP – Tape and Reel (Pb-free)                | Field       | Industrial, -40 °C to 85 °C |
| <b>Programmer</b> |   |             |                             |
| CY3672-USB        | Programmer for Field Programmable Devices             | N/A         | N/A                         |
| CY3695            | CY22050/CY22150/CY25200 Socket Adapter for CY3672-USB | N/A         | N/A                         |

Some product offerings are factory programmed customer specific devices with customized part numbers. The Possible Configurations table shows the available device types, but not complete part numbers. Contact your local Cypress FAE or Sales Representative for more information.

## Possible Configurations

| Ordering Code <sup>[6]</sup> | Package Type                           | Programming | Operating Temperature Range |
|------------------------------|--|-------------|-----------------------------|
| CY25200ZXC-xxx               | 16-pin TSSOP (Pb-free)                 | Factory     | Commercial, 0 °C to 70 °C   |
| CY25200ZXC-xxxT              | 16-pin TSSOP – Tape and Reel (Pb-free) | Factory     | Commercial, 0 °C to 70 °C   |
| CY25200ZXI-xxx               | 16-pin TSSOP (Pb-free)                 | Factory     | Industrial, -40 °C to 85 °C |
| CY25200ZXI-xxxT              | 16-pin TSSOP – Tape and Reel (Pb-free) | Factory     | Industrial, -40 °C to 85 °C |

## Ordering Code Definitions




### Note

6. "xxx" denotes a specific device configuration, and is referred to as the "dash number". "w" denotes the configuration revision.

## Package Drawing and Dimensions

Figure 8. 16-pin TSSOP (4.40 mm Body) Z16.173/ZZ16.173 Package Outline, 51-85091



51-85091 \*E

## Acronyms

| Acronym | Description                             |
|---------|---|
| CMOS    | Complementary Metal Oxide Semiconductor |
| EMC     | Electromagnetic Compatibility           |
| EMI     | Electromagnetic Interference            |
| FAE     | Field Application Engineer              |
| OE      | Output Enable                           |
| OSC     | Oscillator                              |
| PLL     | Phase Locked Loop                       |
| SSC     | Spread Spectrum Clock                   |
| SSCG    | Spread Spectrum Clock Generator         |
| TSSOP   | Thin Shrunk Small Outline Package       |

## Document Conventions

### Units of Measure

| Symbol | Unit of Measure |
|--------|-----------------|
| °C     | degree Celsius  |
| kΩ     | kilohm          |
| kHz    | kilohertz       |
| MHz    | megahertz       |
| µA     | microampere     |
| ms     | millisecond     |
| mW     | milliwatt       |
| ns     | nanosecond      |
| Ω      | ohm             |
| %      | percent         |
| pF     | picofarad       |
| ps     | picosecond      |
| V      | volt            |

## Document History Page

| Document Title: CY25200, Programmable Spread Spectrum Clock Generator for EMI Reduction<br>Document Number: 38-07633 |         |                 |                 |  |
|--|---------|-----------------|-----------------|--|
| Rev.   | ECN No. | Orig. of Change | Submission Date | Description of Change  |
| **   | 204243  | RGL             | See ECN         | New data sheet.  |
| *A   | 220043  | RGL             | See ECN         | Updated <a href="#">Ordering Information</a> :<br>No change in part numbers.<br>Minor Change: Replaced Z with X in MPNs in ordering information for Pb free.   |
| *B   | 267832  | RGL             | See ECN         | Added Field Programmable Devices related information in all instances across the document.<br>Updated <a href="#">Ordering Information</a> :<br>Updated part numbers.  |
| *C   | 291094  | RGL             | See ECN         | Updated <a href="#">AC Electrical Specifications</a> :<br>Added $t_{SKW}$ parameter and its details.   |
| *D   | 1821908 | DPF / AESA      | See ECN         | Updated <a href="#">Recommended Operating Conditions</a> :<br>Updated details in "Description" column corresponding to $F_{SSCLK-Low}$ Voltage parameter (Replaced SSCLK5/6 with SSCLK1/2/3/4).<br>Updated <a href="#">AC Electrical Specifications</a> :<br>Removed $T_{CCJ4}$ parameter and its details.   |
| *E   | 2442066 | KVM / AESA      | See ECN         | Updated <a href="#">Ordering Information</a> :<br>Updated part numbers.<br>Added Note "Not recommended for new designs." and referred the same note in CY25200ZXC_XXXW, CY25200ZXC_XXXWT, CY25200FZXC and CY25200FZXCT.<br>Updated <a href="#">Package Drawing and Dimensions</a> .<br>No change in revisions.<br>Updated caption of spec 51-85091 *A (Replaced Z16.173 with ZZ16).<br>Updated to new template.  |
| *F   | 2758387 | KVM / AESA      | 09/01/2009      | Extensive text edits in all instances across the document.<br>Removed Benefits.<br>Added Description.<br>Updated <a href="#">Pin Description</a> :<br>Updated <a href="#">Table 2</a> .<br>Updated <a href="#">Table 3</a> .<br>Updated <a href="#">Programming Description</a> :<br>Updated <a href="#">Modulation Frequency</a> :<br>Updated description.<br>Updated <a href="#">DC Electrical Specifications</a> :<br>Updated minimum and typical values of $I_{OH3.3}$ and $I_{OL3.3}$ parameters.<br>Updated <a href="#">AC Electrical Specifications</a> :<br>Updated details in "Unit" column (Filled all missing units).<br>Updated details in "Description" column corresponding to $T_{STP}$ , $T_{OE1}$ and $T_{OE2}$ parameters.<br>Updated Note 5 (for clarity).<br>Standardized all parameter names to upper case.<br>Updated <a href="#">Ordering Information</a> :<br>Updated part numbers.<br>Updated existing Note "Not recommended for new designs." as "Not recommended for new designs. Part numbers without a "K" are being replaced by part numbers with a "K". There are no changes to device specifications as a result of the part number change." |

**Document History Page (continued)**

| <b>Document Title: CY25200, Programmable Spread Spectrum Clock Generator for EMI Reduction</b><br><b>Document Number: 38-07633</b> |                |                        |                        |   |
|--|----------------|------------------------|------------------------|---|
| <b>Rev.</b>  | <b>ECN No.</b> | <b>Orig. of Change</b> | <b>Submission Date</b> | <b>Description of Change</b>  |
| *G   | 2897246        | KVM                    | 03/22/10               | <p>Updated <a href="#">Ordering Information</a>:<br/>         Removed inactive parts.</p> <p>Removed Note "Not recommended for new designs. Part numbers without a "K" are being replaced by part numbers with a "K". There are no changes to device specifications as a result of the part number change." and its references.</p> <p>Added <a href="#">Possible Configurations</a>.</p> <p>Referred Note 6 in "Ordering Code" column.</p> <p>Updated <a href="#">Package Drawing and Dimensions</a>:<br/>         spec 51-85091 – Changed revision from *A to *B.</p> |
| *H   | 3103982        | BASH                   | 07/12/2010             | <p>Added <a href="#">Ordering Code Definitions</a>.</p> <p>Updated <a href="#">Package Drawing and Dimensions</a>:<br/>         spec 51-85091 – Changed revision from *B to *C.</p> <p>Added <a href="#">Acronyms</a> and <a href="#">Units of Measure</a>.</p> <p>Minor edits.</p> <p>Updated to new template.</p>   |
| *I   | 4209874        | CINM                   | 12/16/2013             | <p>Updated <a href="#">Ordering Information</a>:<br/>         Updated part numbers.</p> <p>Updated <a href="#">Possible Configurations</a>:<br/>         Updated part numbers.</p> <p>Updated <a href="#">Package Drawing and Dimensions</a>:<br/>         spec 51-85091 – Changed revision from *C to *D.</p> <p>Updated to new template.</p> <p>Completing Sunset Review.</p>   |
| *J   | 4581659        | AJU                    | 11/28/2014             | <p>Updated <a href="#">Functional Description</a>:<br/>         Added "For a complete list of related documentation, click <a href="#">here</a>." at the end.</p> <p>Updated <a href="#">Package Drawing and Dimensions</a>:<br/>         spec 51-85093 – Changed revision from *D to *E.</p>   |
| *K   | 4623539        | TAVA                   | 01/14/2015             | <p>Updated <a href="#">Ordering Information</a>:<br/>         Updated <a href="#">Possible Configurations</a>:<br/>         Updated details in "Ordering Code" column.</p>  |
| *L   | 5532023        | PSR                    | 11/24/2016             | <p>Updated <a href="#">Functional Description</a>:<br/>         Updated description.</p> <p>Updated <a href="#">Programming Description</a>:<br/>         Removed "CyberClocks™ Online Software".</p> <p>Added <a href="#">Thermal Resistance</a>.</p> <p>Updated <a href="#">Package Drawing and Dimensions</a>:<br/>         Removed table "16-pin TSSOP Package Characteristics".</p> <p>Updated to new template.</p> <p>Completing Sunset Review.</p>   |

## Sales, Solutions, and Legal Information

### Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at [Cypress Locations](#).

#### Products

|                               |  |
|-------------------------------|--|
| ARM® Cortex® Microcontrollers | <a href="http://cypress.com/arm">cypress.com/arm</a>               |
| Automotive                    | <a href="http://cypress.com/automotive">cypress.com/automotive</a> |
| Clocks & Buffers              | <a href="http://cypress.com/clocks">cypress.com/clocks</a>         |
| Interface                     | <a href="http://cypress.com/interface">cypress.com/interface</a>   |
| Internet of Things            | <a href="http://cypress.com/iot">cypress.com/iot</a>               |
| Lighting & Power Control      | <a href="http://cypress.com/powerpsoc">cypress.com/powerpsoc</a>   |
| Memory                        | <a href="http://cypress.com/memory">cypress.com/memory</a>         |
| PSoC                          | <a href="http://cypress.com/psoc">cypress.com/psoc</a>             |
| Touch Sensing                 | <a href="http://cypress.com/touch">cypress.com/touch</a>           |
| USB Controllers               | <a href="http://cypress.com/usb">cypress.com/usb</a>               |
| Wireless/RF                   | <a href="http://cypress.com/wireless">cypress.com/wireless</a>     |

#### PSoC® Solutions

[PSoC 1](#) | [PSoC 3](#) | [PSoC 4](#) | [PSoC 5LP](#)

#### Cypress Developer Community

[Forums](#) | [Projects](#) | [Video](#) | [Blogs](#) | [Training](#) | [Components](#)

#### Technical Support

[cypress.com/support](http://cypress.com/support)

---

© Cypress Semiconductor Corporation, 2004-2016. This document is the property of Cypress Semiconductor Corporation and its subsidiaries, including Spansion LLC ("Cypress"). This document, including any software or firmware included or referenced in this document ("Software"), is owned by Cypress under the intellectual property laws and treaties of the United States and other countries worldwide. Cypress reserves all rights under such laws and treaties and does not, except as specifically stated in this paragraph, grant any license under its patents, copyrights, trademarks, or other intellectual property rights. If the Software is not accompanied by a license agreement and you do not otherwise have a written agreement with Cypress governing the use of the Software, then Cypress hereby grants you a personal, non-exclusive, nontransferable license (without the right to sublicense) (1) under its copyright rights in the Software (a) for Software provided in source code form, to modify and reproduce the Software solely for use with Cypress hardware products, only internally within your organization, and (b) to distribute the Software in binary code form externally to end users (either directly or indirectly through resellers and distributors), solely for use on Cypress hardware product units, and (2) under those claims of Cypress's patents that are infringed by the Software (as provided by Cypress, unmodified) to make, use, distribute, and import the Software solely for use with Cypress hardware products. Any other use, reproduction, modification, translation, or compilation of the Software is prohibited.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS DOCUMENT OR ANY SOFTWARE OR ACCOMPANYING HARDWARE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. To the extent permitted by applicable law, Cypress reserves the right to make changes to this document without further notice. Cypress does not assume any liability arising out of the application or use of any product or circuit described in this document. Any information provided in this document, including any sample design information or programming code, is provided only for reference purposes. It is the responsibility of the user of this document to properly design, program, and test the functionality and safety of any application made of this information and any resulting product. Cypress products are not designed, intended, or authorized for use as critical components in systems designed or intended for the operation of weapons, weapons systems, nuclear installations, life-support devices or systems, other medical devices or systems (including resuscitation equipment and surgical implants), pollution control or hazardous substances management, or other uses where the failure of the device or system could cause personal injury, death, or property damage ("Unintended Uses"). A critical component is any component of a device or system whose failure to perform can be reasonably expected to cause the failure of the device or system, or to affect its safety or effectiveness. Cypress is not liable, in whole or in part, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from or related to all Unintended Uses of Cypress products. You shall indemnify and hold Cypress harmless from and against all claims, costs, damages, and other liabilities, including claims for personal injury or death, arising from or related to any Unintended Uses of Cypress products.

Cypress, the Cypress logo, Spansion, the Spansion logo, and combinations thereof, PSoC, CapSense, EZ-USB, F-RAM, and Traveo are trademarks or registered trademarks of Cypress in the United States and other countries. For a more complete list of Cypress trademarks, visit [cypress.com](http://cypress.com). Other names and brands may be claimed as property of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cypress Semiconductor](#):

[CY25200KFZXC](#) [CY25200KFZXCT](#) [CY25200KZXI-006](#) [CY25200KFZXIT](#) [CY25200KFZXI](#)