

E2 - SERIES

Lever Action 1.5 AMPS @ 28 VDC

SPECIFICATIONS AND ORDERING INFORMATION

The E2 Series is our lever action switch, originally designed for the electric guitar market. It offers positive 2-5 position switching, a 30° or a 15° index, and solder lug terminals.



SPECIFICATIONS

ELECTRICAL

Current and Voltage Rating: Make and break resistive load

1.5 amps @ 28 VDC; 0.5 amp @ 115 VAC.

Current Carrying Capacity: 9 amps.

Dielectric Strength: 1,000 VAC between current carrying parts and ground.

Contact Resistance: Average initial 3.5 milliohms.

Insulation Resistance: In excess of 750,000 megohms.

MECHANICAL

Materials and Finishes: All parts utilize non-corrosive materials as standard.

Clips and Rotors: Brass with silver plate as standard.

Insulation: Glass epoxy.

Index: Cam and roller with coil spring.

Index Life: 25,000 cycles minimum.

Index Torque: Switches have lowest practical torque consistent with crisp detenting and smooth, reliable operation.

Index Angles: Positive 30°, 15° and spring return.

Index Stops: Fixed stops standard.

Stop Strength: 2.82 Nm minimum.

STANDARD PART NUMBER


LEVER

SWITCHES - 30° INDEXING - FIXED STOPS - SOLDER LUG TERMINALS


ACTIVE POLES/ POLES	POLES/ SECTION	NO. OF SECTIONS	SHORTING	NON-SHORTING	DESCRIPTION	DETAIL
02	03	2	1	E2G0203S-1	E2G0203N-1	E
02	05	2	1	E2G0205S-15 2 POSITIVE INDEX POSITIONS BOTH SIDES OF CENTER.	E
02	03	2	1	E2G0203S	E2G0203N	E
02	03	2	1	E2G0203S-2	E2G0203N-2	E
04	02	4	1	E2G0402S-3	E2G0402N-3	E
04	02	4	1	E2G0402S	E2G0402N	E

DIMENSIONS


STANDARD CONSTRUCTION



DETAIL E



DETAIL F



ELECTROSWITCH • ELECTRONIC PRODUCTS
UNIT OF ELECTRO SWITCH CORP.

2010 Yonkers Road, Raleigh, NC 27604

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Electroswitch:](#)

[E2G0203S-1](#)