








































## RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
3. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
4. HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
5. FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.
6. FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.

$\triangle_6$	101.19 [3.984]	99.06 [3.900]	39	40	9-146469-0
$\triangle_6$	98.65 [3.884]	96.52 [3.800]	38	39	8-146469-9
$\triangle_6$	96.11 [3.784]	93.98 [3.700]	37	38	8-146469-8
$\triangle_6$	93.57 [3.684]	91.44 [3.600]	36	37	8-146469-7
$\triangle_6$	91.03 [3.584]	88.90 [3.500]	35	36	8-146469-6
$\triangle_6$	88.49 [3.484]	86.36 [3.400]	34	35	8-146469-5
$\triangle_6$	85.95 [3.384]	83.82 [3.300]	33	34	8-146469-4
$\triangle_6$	83.41 [3.284]	81.28 [3.200]	32	33	8-146469-3
$\triangle_6$	80.87 [3.184]	78.74 [3.100]	31	32	8-146469-2
$\triangle_6$	78.33 [3.084]	76.20 [3.000]	30	31	8-146469-1
$\triangle_6$	75.79 [2.984]	73.66 [2.900]	29	30	8-146469-0
$\triangle_6$	73.25 [2.884]	71.12 [2.800]	28	29	7-146469-9
$\triangle_6$	70.71 [2.784]	68.58 [2.700]	27	28	7-146469-8
$\triangle_6$	68.17 [2.684]	66.04 [2.600]	26	27	7-146469-7
$\triangle_6$	65.63 [2.584]	63.50 [2.500]	25	26	7-146469-6
$\triangle_6$	63.09 [2.484]	60.96 [2.400]	24	25	7-146469-5
$\triangle_6$	60.55 [2.384]	58.42 [2.300]	23	24	7-146469-4
$\triangle_6$	58.01 [2.284]	55.88 [2.200]	22	23	7-146469-3
$\triangle_6$	55.47 [2.184]	53.34 [2.100]	21	22	7-146469-2
$\triangle_6$	52.93 [2.084]	50.80 [2.000]	20	21	7-146469-1
$\triangle_6$	50.39 [1.984]	48.26 [1.900]	19	20	7-146469-0
$\triangle_6$	47.85 [1.884]	45.72 [1.800]	18	19	6-146469-9
$\triangle_6$	45.31 [1.784]	43.18 [1.700]	17	18	6-146469-8
$\triangle_6$	42.77 [1.684]	40.64 [1.600]	16	17	6-146469-7
$\triangle_6$	40.23 [1.584]	38.10 [1.500]	15	16	6-146469-6
$\triangle_6$	37.69 [1.484]	35.56 [1.400]	14	15	6-146469-5
$\triangle_6$	35.15 [1.384]	33.02 [1.300]	13	14	6-146469-4
$\triangle_6$	32.61 [1.284]	30.48 [1.200]	12	13	6-146469-3
$\triangle_6$	30.07 [1.184]	27.94 [1.100]	11	12	6-146469-2
$\triangle_6$	27.53 [1.084]	25.40 [1.000]	10	11	6-146469-1
$\triangle_6$	24.99 [.984]	22.86 [.900]	9	10	6-146469-0
$\triangle_6$	22.45 [.884]	20.32 [.800]	8	9	5-146469-9
$\triangle_6$	19.91 [.784]	17.78 [.700]	7	8	5-146469-8
$\triangle_6$	17.37 [.684]	15.24 [.600]	6	7	5-146469-7
$\triangle_6$	14.83 [.584]	12.70 [.500]	5	6	5-146469-6
$\triangle_6$	12.29 [.484]	10.16 [.400]	4	5	5-146469-5
$\triangle_6$	9.75 [.384]	7.62 [.300]	3	4	5-146469-4
$\triangle_6$	7.21 [.284]	5.08 [.200]	2	3	5-146469-3
$\triangle_6$	4.67 [.184]	2.54 [.100]	1	2	5-146469-2
$\triangle_6$	2.13 [.084]	-	-	1	5-146469-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

	101.19 [3.984]	99.06 [3.900]	39	40	4-146469-0
	98.65 [3.884]	96.52 [3.800]	38	39	3-146469-9
	96.11 [3.784]	93.98 [3.700]	37	38	3-146469-8
	93.57 [3.684]	91.44 [3.600]	36	37	3-146469-7
	91.03 [3.584]	88.90 [3.500]	35	36	3-146469-6
	88.49 [3.484]	86.36 [3.400]	34	35	3-146469-5
	85.95 [3.384]	83.82 [3.300]	33	34	3-146469-4
	83.41 [3.284]	81.28 [3.200]	32	33	3-146469-3
	80.87 [3.184]	78.74 [3.100]	31	32	3-146469-2
	78.33 [3.084]	76.20 [3.000]	30	31	3-146469-1
	75.79 [2.984]	73.66 [2.900]	29	30	3-146469-0
	73.25 [2.884]	71.12 [2.800]	28	29	2-146469-9
	70.71 [2.784]	68.58 [2.700]	27	28	2-146469-8
	68.17 [2.684]	66.04 [2.600]	26	27	2-146469-7
	65.63 [2.584]	63.50 [2.500]	25	26	2-146469-6
	63.09 [2.484]	60.96 [2.400]	24	25	2-146469-5
	60.55 [2.384]	58.42 [2.300]	23	24	2-146469-4
	58.01 [2.284]	55.88 [2.200]	22	23	2-146469-3
	55.47 [2.184]	53.34 [2.100]	21	22	2-146469-2
	52.93 [2.084]	50.80 [2.000]	20	21	2-146469-1
	50.39 [1.984]	48.26 [1.900]	19	20	2-146469-0
	47.85 [1.884]	45.72 [1.800]	18	19	1-146469-9
	45.31 [1.784]	43.18 [1.700]	17	18	1-146469-8
	42.77 [1.684]	40.64 [1.600]	16	17	1-146469-7
	40.23 [1.584]	38.10 [1.500]	15	16	1-146469-6
	37.69 [1.484]	35.56 [1.400]	14	15	1-146469-5
	35.15 [1.384]	33.02 [1.300]	13	14	1-146469-4
	32.61 [1.284]	30.48 [1.200]	12	13	1-146469-3
	30.07 [1.184]	27.94 [1.100]	11	12	1-146469-2
	27.53 [1.084]	25.40 [1.000]	10	11	1-146469-1
	24.99 [.984]	22.86 [.900]	9	10	1-146469-0
	22.45 [.884]	20.32 [.800]	8	9	146469-9
	19.91 [.784]	17.78 [.700]	7	8	146469-8
	17.37 [.684]	15.24 [.600]	6	7	146469-7
	14.83 [.584]	12.70 [.500]	5	6	146469-6
	12.29 [.484]	10.16 [.400]	4	5	146469-5
	9.75 [.384]	7.62 [.300]	3	4	146469-4
	7.21 [.284]	5.08 [.200]	2	3	146469-3
	4.67 [.184]	2.54 [.100]	1	2	146469-2
	2.13 [.084]	-	-	1	146469-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIM E. BRANDBERG CHK G. DUBNICZKI	05MAR97 05MAR97	POSITIONS  TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES (UNLESS SPECIFIED): 0 PLC ± — 1 PLC ± — 2 PLC ± 0.51[.02] 3 PLC ± 0.127[.005] 4 PLC ± 0.0127[.0005] ANGLES ± —		NAME APVD G. DUBNICZKI PRODUCT SPEC — APPLICATION SPEC —	
		HEADER ASSEMBLY, MOD II, STACKING, SINGLE ROW, .025 SQ.POST, UNSHROUDED		SIZE CASE CODE DRAWING NO.	
MATERIAL 		FINISH SEE TABLE		WEIGHT — A1 00779 © 146469	
		CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1 REV A1	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[9-146469-0](#)