NOTES 1. APPLICABLE CABLE. INSULATOR OUTER DIAMETER 0.90 TO 1.00 DIA CONDUCTOR SIZE(STRANDED) (Ø5) DRAIN WIRE WIRE VINYL SEATH 30 ± 0.3 AWG 26-27 OR EQUIVALET. VINYL SEATH Φ 5.0 *(1) OUTER DIAMETER INSULATOR CONDUCTOR AWG 25 OR EQUIVALET DRAIN WIRE 6.09 ±0.3 7/0.18 DIA. *(2) *(1) CABLE ENTRY IS 5.6MIN. *(2) CONSTRUCTION IS FOR REFERENCE. Dec.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved. 2 ADAPTER SHALL BE USED TO ALIGN INDIVIDUAL WIRE. In case that the application demands a high level of reliability, such as automotive, please contact a company representative for further information. 3. THE DIMENSION IN PARENTHESIS IS FOR REFERENCE. BUSH (2:1)
ATTACED HOOD (A) (2:1) ATTACED (17.5) 12.9 ^{+0.5} 6.6 ± 0.3 H00D (B) (2:1) ATTACED D (0.65) ADAPTER (2:1) $\left(2\right)$ ATTACED BRASS OVER :TIN REFLOW PLATING 1 μ m min UNDER:COPPERPLATING 0.5 μ m min PVC LIGHT BEIGE CONTACT:GOLD PLATING 1.27 μ m min TERMINAL:GOLD PLATING 0.03 μ m min UNDER:NICKEL PLATING 2 μ m min PHOSPHOR BRONZE POLYCARBONATE LIGHT BEIGE 6 POLYCARBONATE LIGHT BEIGE POLYCARBONATE TRANSPARENCY 4 POLYCARBONATE TRANSPARENCY NO. MATERIAL FINISH , REMARKS NO. MATERIAL FINISH , REMARKS COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE SCALE UNITS 4:1 08. 06. 11 DRAWING NO. APPROVED : YH. ENAMI EDC3-120682-02 HIROSE ELECTRIC 08. 06. 11 PART CHECED : HO. MIWA TM11APA1-88P 08. 06. 10 NO. DESIGNED : KI. NAGANUMA CO., LTD. CODE 08. 06. 10 NO. CL222-2783-4-00 :KI. NAGANUMA DRAWN FORM HC0011-5-7

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hirose Electric: