

1 - HOUSING HAS BOSS AROUND PLUNGER TO MEET BSI AND VDE AGENCY 8,0/.315 CLEARANCE REQUIREMENT

- 2 OPERATING POSITIONS:
- | | |
|-----------|--|
| CIR 11-12 | $\frac{15,24 \pm 0,76}{.600 \pm .030}$ |
| CIR 21-22 | $\frac{14,48 \pm 0,76}{.570 \pm .030}$ |
| CIR 31-32 | $\frac{15,37 \pm 0,76}{.605 \pm .030}$ |

- 3 - BLACK PLASTIC HOUSING AND PLUNGER
- ④ QUICK-CONNECT TERMINALS CONFORM TO $\frac{6.35}{.250}$ WIDE X $\frac{0.81}{.032}$ THICK
NEMA DC-2 SPECIFICATION
- 5 - DO NOT SNAP RELEASE PLUNGER, MAY CAUSE DAMAGE TO PLUNGER ASSEMBLY
- 6 - WHEN DEPRESSING THE PLUNGER, CIRCUITS 11-12 AND 31-32 MUST
CLOSE WITHIN A RANGE OF $\frac{0.05}{.002}$ TO $\frac{2.00}{.079}$ BEFORE CIRCUIT 21-22 OPENS
- 7 - WHEN RELEASING THE PLUNGER, CIRCUITS 11-12 AND 31-32 MUST
OPEN WITHIN A RANGE OF $\frac{0.05}{.002}$ TO $\frac{2.00}{.079}$ AFTER CIRCUIT 21-22 CLOSES


-  CIR 11-12, 31-32 $\frac{4,32}{.170}$ MIN
 CIR 21-22 $\frac{3,56}{.140}$ MIN

5A - 125 VAC; 2A - 24 VDC
(CKT 11-12 & 31-32)
0.1A - 125 VAC - DC (CKT 21 - 22)
60/75°C (Cu)

MICRO SWITCH
a Honeywell Division

SWITCH – BASIC

CATALOG LISTING
WW2K29H-D9

THIRD ANGLE PROJECTION			
			
SCALE 2:1			
DO NOT SCALE PRINT			
TOLERANCES			
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±			
NO PLACES ONE PLACE TWO PLACES THREE PLACES ANGLES	DIM. mm xxx xxx	TOL mm-in 1/64 0.4 / 0.05 0.15 / 0.006 5°	DIM. in xx xxx xxxx
			0.8 / 0.03 0.38 / 0.01 0.15 / 0.00
SI METRIC		US CUSTOMARY	
			
WEIGHT			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[WW2K29H-D9](#)