Product data sheet Characteristics

XZCP29P11L5

pre-wired connectors XZ - straight female - M12 - 8 pins - cable PVC 5m

Product availability: Stock - Normally stocked in distribution facility

Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	Application
Electrical connection	Straight female connector M12, 8 pins
Collar material	Stainless steel 316L
Status LED	Without
Cable length	16.4 ft (5 m)

Complementary

Cable connector fixing	Screw-on	
Cable outer diameter	0.2 in (5.2 mm)	
Cable composition	8 x 0.25 mm²	
Wire insulation material	PVC	
[Ue] rated operational voltage	300 V DC 250 V AC	
[In] rated current	2 A	
Contact resistance	<= 5000 μOhm	
Insulating resistance	>= 1 GΩ	
Product weight	0.64 lb(US) (0.29 kg)	

Environment

IP degree of protection	IP67	
Ambient air temperature for operation	23194 °F (-590 °C) (flexing) -31194 °F (-3590 °C) (static)	
Ambient air temperature for storage	-31212 °F (-35100 °C)	

Ordering and shipping details

Discount Schedule DS2	
GTIN 0078590159188	87
Nbr. of units in pkg. 1	
Package weight(Lbs) 0.61	
Product availability Stock - Normall	y stocked in distribution facility
Returnability Y	
Country of origin PL	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0649 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCP29P11L5