



FERRULE
MATERIAL: POLYESTER MLDG COMPOUND
COLOR: BLACK

—CAP
MATERIAL: POLYESTER MLDG COMPOUND
COLOR: RED

—#16 AWG Si INSULATED
LEAD WIRE
COLOR: WHITE

86.3534

1 TO MATE WITH AMP LGH 1/2L RECEPTACLE
WITH .89 [22.6] BARREL DEPTH

2 MARK PER MIL-STD-130.

3. OPERATING VOLTAGE: 15 KVDC AT 0 TO 70,000 FEET, -55°C TO 125°C .

4 PIGTAILS ARE SOLDER DIPPED.

5 INSULATION CUT, BUT NOT REMOVED.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 29-SEP-89		 TE Connectivity				
		CHK T.SHUEY 09-OCT-89						
DIMENSIONS:		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		NAME LEAD ASSY SGL END, POSITIVE STOP LGH-1/2L				
INCHES [mm]		APVD D.FABY 09-OCT-89						
		PRODUCT SPEC						
		APPLICATION SPEC						
MATERIAL		WEIGHT		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
-		0.000000		A2	00779	C=863534	-	
CUSTOMER DRAWING				SCALE	2:1	SHEET	1 of 1	REV
								J

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[863534-9](#)