



Notes:

- Electrical Specifications:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Contact Resistance: 20mOhm max.
 - Insulation Resistance: 500MOhm min. @ 100 VDC
 - Current Rating: 1.2A max. at 25° C
 - Working Voltage: 100 VDC
 - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
 - Operating Temperature: -40° C to +85° C
- Material and Finish:
 - Receptacle Housing: Polyester (Color: see Part Number Table); UL94 V-0
 - Panel Nut: Brass, Finish: Nickel Plated
 - Panel Gasket: Silicon, Color: White
 - Cat.5e RJ45 IDC Jack Metal Shell: Copper Alloy, Nickel Plated
 - Cat.5e RJ45 IDC Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
 - Cat.5e RJ45 IDC Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
- Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- IP67 rated when covered or fully mated with the appropriate mating connector
- RoHS compliant

Directive 2002/95/EC RoHS Compliant

| | | | | | | |
|----------------------------------|---|-----------|-----------|-----------|-----------|-----------|
| Description | Colored Plastic Receptacle Housing with Shielded Cat.5e RJ45 IDC Jack | | | | | |
| Plastic Receptacle Housing Color | Black | Blue | Green | Yellow | Red | White |
| Part Number | 17-10015 | 17-102374 | 17-102384 | 17-102394 | 17-102404 | 17-102414 |

| | | | | | | |
|--|-------------|------------|--|--|----------------------------|------------|
| THIS DRAWING MAY NOT BE COPIED, REPRODUCED, IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND | Customer: | | Tolerance Unless otherwise specified | | Scale: 1.5:1 Dim. in mm | |
| | Name | Title | Approval Date | 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3° | | |
| | | | | 2011 | Date | Name |
| | | | | Draw. | Jan. 18 | Vincent Ke |
| | | | | Appd. | Jan. 28 | J. Chaudry |
| | | | Norm | | | |
| | | | D-old | | | |
| b | Mar/08/2011 | Vincent ke | Title: Receptacle Assembly Kit Colored Plastic Receptacle Housing with Shielded Cat. 5e RJ45 IDC Jack | | | |
| a | original | | Drawing No.: 17K1A186 | | | |
| Rev. | Changes | Date | Part No.: SEE PART NUMBER TABLE | | | |
| | | | Drawing No.: 17K1A186 | | | |
| | | | Part No.: SEE PART NUMBER TABLE | | | |



DIN A3
Sheet 1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[17-10015](#)